submitted in lieu of Form 3160-5 UNITED STATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

	Sundry Notices and Reports on Wells	JAN 25 - 27			
		• •	<u> ि : 5].</u>	Lease Number	
_		RECEIVED FACTORION		NMSF-078503	
1.	Type of Well 07	PARTHER	6.	If Indian, All. or Tribe Name	
	GAS			I ribe Name	
	AC 75	79 30 377	7.	Unit Agreement Name	
2.	Name of Operator	13		-	
	Burlington (S)	263 UA		C T 20 5 TI	
	RESOURCES OIL & GAS COMPANY LP	الم 2006 ما الم	}	San Juan 29-7 Unit	
		TIVED OF			
2		ST. 3 (2)	8.	Well Name & Number	
3.	Address & Phone No. of Operator			#109N	
	PO Box 4289, Farmington, NM 87499 (505) 326-9700	21 1/2	9.	API Well No.	
		3/P/81/000			
4.	Location of Well, Footage, Sec., T, R, M			30-039-29701	
₹.	Location of wen, Poolage, Sec., 1, K, M		10.	Field and Pool	
	Unit P (SESE), 1025' FSL & 365' FEL, Sec. 30, T29N, R7W, NMPM		B	Basin DK / Blanco MV	
			11.	County and State	
			11.	Rio Arriba Co., NM	
	CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE of Submission Type of Action Notice of Intent Abandonment Recompletion New Construct Plugging Non-Routine F Casing Repair Final Abandonment Altering Casing Conversion to	s ion racturing	I, OTHER I		
13. 1/13 casi w/2 tag	Type of Submission Notice of Intent Notice of Intent Recompletion X Subsequent Report Type of Action Abandonment Recompletion Plugging Non-Routine F Casing Repair Water Shut off	s ion racturing Injection 1 to 226'. Circ. ho 21.5 cf – 21.64 bl ulate cement to su	X Other - SPU ble. RIH w/7 bl slurry) Typ rface. 1/20/0	jts 9-5/8", 32.3# H-40 be I-II Portland cement 16 Installed 3/4" PVC to	
13. 1/13 casi w/2 tag bbls	Type of Submission Notice of Intent Notice of Intent Intention Notice of Intentio	s ion racturing Injection I to 226'. Circ. ho 21.5 cf – 21.64 bl ulate cement to su - 11 bbl slurry) Ne	X Other - SPU ble. RIH w/7 bl slurry) Typ rface. 1/20/0	jts 9-5/8", 32.3# H-40 be I-II Portland cement 16 Installed 3/4" PVC to	
1/13 casi w/2 tag bbl: Cas	Type of Submission Notice of Intent Notice of Intent Notice of Intent Notice of Intent Recompletion Recompletion Non-Routine F Casing Repair Final Abandonment Altering Casing Conversion to Describe Proposed or Completed Operations Non-Routine F Casing Repair Conversion to Describe Proposed or Completed Operations Non-Routine F Casing Repair Conversion to Describe Proposed or Completed Operations Non-Routine F Casing Repair Conversion to Describe Proposed or Completed Operations Non-Routine F Casing Repair Conversion to Describe Proposed or Completed Operations Non-Routine F Casing Repair Conversion to Describe Proposed or Completed Operations Non-Routine F Casing Repair Conversion to Describe Proposed or Completed Operations Non-Routine F Casing Repair Conversion to Describe Proposed or Completed Operations Non-Routine F Casing Repair Conversion to Describe Proposed or Completed Operations Non-Routine F Casing Repair Conversion to Describe Proposed or Completed Operations Non-Routine F Casing Repair Conversion to Describe Proposed or Completed Operations Non-Routine F Casing Repair Value Shut off Conversion to Describe Proposed or Completed Operations Non-Routine F Casing Repair Value Shut off Conversion to Describe Proposed or Completed Operations Non-Routine F Casing Repair Value Shut off Conversion to Describe Proposed or Completed Operations	s ion racturing Injection I to 226'. Circ. ho 21.5 cf – 21.64 bl ulate cement to su - 11 bbl slurry) Ne	X Other - SPU ble. RIH w/7 bl slurry) Typ rface. 1/20/0	jts 9-5/8", 32.3# H-40 be I-II Portland cement 16 Installed 3/4" PVC to	
13. 1/13 casi w/2 tag bbli Cas AP	Type of Submission Notice of Intent Recompletion New Construct Plugging Non-Routine F Casing Repair Water Shut off Altering Casing Conversion to Describe Proposed or Completed Operations Notice of Intent Recompletion New Construct Plugging Non-Routine F Casing Repair Conversion to Describe Proposed or Completed Operations Notice of Plan Recompletion New Construct Notice of Plan Recompletion New Construct Plugging Non-Routine F Casing Repair Conversion to Describe Proposed or Completed Operations Notice of Plan Recompletion New Construct New Construct Plugging Non-Routine F Casing Repair Conversion to Describe Proposed or Completed Operations Notice of Plan Recompletion New Construct Non-Routine F Operation Non-Routine F Operation Non-Routine F Non-Routine F Non-Routine F Operation Non-Routine F Non-Routine F Operation Non-Routine F Non-Routine F Non-Routine F Operation Non-Routine F	s ion racturing Injection I to 226'. Circ. ho 21.5 cf – 21.64 bl ulate cement to su - 11 bbl slurry) Ne	X Other - SPU ble. RIH w/7 bl slurry) Typ rface. 1/20/0	jts 9-5/8", 32.3# H-40 be I-II Portland cement 16 Installed 3/4" PVC to	
13. 1/13 casi w/2 tag bbli Cas AP	Type of Submission Notice of Intent Recompletion New Construct Plugging Non-Routine For Casing Repair Latering Casing Repair Noter Shut off Conversion to Pescribe Proposed or Completed Operations Note of Intent Recompleted Operations Note of Intent Recompleted Operations Note of Intent Recompleted Operations Note of Intent Recompletion of Abandonment New Construct Plugging Non-Routine For Water Shut off Conversion to Describe Proposed or Completed Operations Note of Intent Recompletion New Construct Plugging Non-Routine For Casing Repair Note of Intent Recompletion New Construct Plugging Non-Routine For Water Shut off Casing Repair New Construct New Construct New Construct Plugging Non-Routine For Water Shut off Casing Repair New Construct Ne	s ion racturing Injection I to 226'. Circ. ho 21.5 cf – 21.64 bl ulate cement to su - 11 bbl slurry) Ne	ole. RIH w/7 ol slurry) Typ rface. 1/20/0 eat cement to	jts 9-5/8", 32.3# H-40 be I-II Portland cement 16 Installed ¾" PVC to bring to surface. Circ. ¼	
13. 1/13 casis w/2 tag bblic Cass AP. 14. Sig	Type of Submission Notice of Intent Abandonment Recompletion New Construct Plugging Non-Routine F Casing Repair Water Shut off Altering Casing Conversion to Pescribe Proposed or Completed Operations 8/06 MIRU Mote #1. Spud 12-1/4" hole @ 0900 hrs 1/18/06. Drilleing and set @ 223'. Pumped preflush of 4 bbls H2O ahead of 76 sx (10% Flyash. Dropped plug and displaced w/7.2 bbls H2O. Didn't circ cement. Tagged cement @ 90'. Mixed and pumped 45 sx (62.55 cf-s cement to surface. Install WH. sing PT will be conducted by the drilling rig and shown on the next report of the property of that the foregoing is true and correct. Patsy Clugston Type of Action Abandonment Abandonment Change of Planger Plugging Non-Routine F Water Shut off Casing Repair Water Shut off Altering Casing Non-Routine F Water Shut off Casing Repair Water Shut off Casing Repair Water Shut off Casing Repair Water Shut off Altering Casing Water Shut off Casing Repair Water Shut off Altering Casing Water Shut off Casing Repair Water Shut off Water Shut off Casing Repair	Injection I to 226'. Circ. ho 21.5 cf – 21.64 bl ulate cement to su - 11 bbl slurry) Ne	ole. RIH w/7 ol slurry) Typ rface. 1/20/0 eat cement to	jts 9-5/8", 32.3# H-40 be I-II Portland cement 16 Installed ¾" PVC to bring to surface. Circ. ¼	
13. 1/13 casis w/2 tag bbls Cass AP: 14. Sig	Type of Submission Notice of Intent Abandonment Recompletion New Construct Plugging Non-Routine F Casing Repair Water Shut off Conversion to Describe Proposed or Completed Operations 8/06 MIRU Mote #1. Spud 12-1/4" hole @ 0900 hrs 1/18/06. Drille Ing and set @ 223'. Pumped preflush of 4 bbls H2O ahead of 76 sx (10% Flyash. Dropped plug and displaced w/7.2 bbls H2O. Didn't circ cement. Tagged cement @ 90'. Mixed and pumped 45 sx (62.55 cf-s cement to surface. Install WH. Sing PT will be conducted by the drilling rig and shown on the next report of the proposed of the prop	Injection I to 226'. Circ. ho 21.5 cf – 21.64 bl ulate cement to su - 11 bbl slurry) Ne	ole. RIH w/7 ol slurry) Typ rface. 1/20/0 eat cement to	its 9-5/8", 32.3# H-40 be I-II Portland cement location of the Installed 3" PVC to bring to surface. Circ. 1/4 Date 1/23/06 ACCEPTED FOR RECOMMENTAL TO THE TOTAL	
13. 1/13 casis w/2 tag bbls Cas AP: 14. Sig	Type of Submission Notice of Intent Abandonment Recompletion New Construct Recompletion Non-Routine Flugging Non-Routine Final Abandonment Final Abandonment Plugging Casing Repair Casing Repair Water Shut off Altering Casing Conversion to Describe Proposed or Completed Operations 8/06 MIRU Mote #1. Spud 12-1/4" hole @ 0900 hrs 1/18/06. Drilleding and set @ 223". Pumped preflush of 4 bbls H2O ahead of 76 sx (10% Flyash. Dropped plug and displaced w/7.2 bbls H2O. Didn't circ dement. Tagged cement @ 90". Mixed and pumped 45 sx (62.55 cf-st cement to surface. Install WH. Sing PT will be conducted by the drilling rig and shown on the next report of the properties of the prope	Injection I to 226'. Circ. ho 21.5 cf – 21.64 bl ulate cement to su - 11 bbl slurry) Ne	ole. RIH w/7 ol slurry) Typ rface. 1/20/0 eat cement to	it Date 1/23/06 ACCEPTED FOR RECO	
13. 1/13 casi w/2 tag bbli Cas AP: 14. Sig (Th AP CO) Title	Type of Submission Notice of Intent Abandonment Recompletion New Construct Plugging Non-Routine F Casing Repair Water Shut off Conversion to Describe Proposed or Completed Operations 8/06 MIRU Mote #1. Spud 12-1/4" hole @ 0900 hrs 1/18/06. Drille Ing and set @ 223'. Pumped preflush of 4 bbls H2O ahead of 76 sx (10% Flyash. Dropped plug and displaced w/7.2 bbls H2O. Didn't circ cement. Tagged cement @ 90'. Mixed and pumped 45 sx (62.55 cf-s cement to surface. Install WH. Sing PT will be conducted by the drilling rig and shown on the next report of the proposed of the prop	Injection It to 226'. Circ. ho. 21.5 cf – 21.64 blulate cement to sure 11 bbl slurry) New Poort.	ole. RIH w/7 ol slurry) Typ rface. 1/20/0 eat cement to	its 9-5/8", 32.3# H-40 be I-II Portland cement 06 Installed ¾" PVC to bring to surface. Circ. ¼ The surface of	