submitted in lieu of Form 3160-5 UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT Sundry Notices and Reports on Wells 5. Lease Number NMSF-080750 RECEIVE Type of Well 6. If Indian, All. or **Tribe Name GAS** 7. **Unit Agreement Name** Name of Operator Burlington RESOURCES OIL & GAS COMPANY LP 8. Well Name & Number Address & Phone No. of Operator Sunray F #1M PO Box 4289, Farmington, NM 87499 (505) 326-9700 9. API Well No. 30-045-30830 Location of Well, Footage, Sec., T, R, M Sec., T--N, R--W, NMPM 10. Field and Pool Unit J (NWSE) 1745' FSL & 1420' FEL, Sec. 26, T30N R10W NMPM Surface Unit P(SESE) 700' FSL & 700' FEL Bottom Blanco MV/ Basin DK **County and State** San Juan Co., NM 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA Type of Submission Type of Action Change of Plans Abandonment X Other - 7"-4 1/2" Casing Notice of Intent New Construction Recompletion Subsequent Report Non-Routine Fracturing Plugging Casing Repair Water Shut off Final Abandonment Altering Casing Conversion to Injection 13. Describe Proposed or Completed Operations 12/29/05 RIH w/8 34" bit & tagged cement @ 315'. D/O cement & ahead to 4350' Intermediate TD. Circulate hole. RIH w/102its of 7"-23# L80 LT&C csg & set @4343'. Circulate hole. 4/16/05 Pumped preflush w/10bbls FW, 10bbls mud, 10bbls FW. Pump 19sxs(57cu-10bbls)prem lite cmt w/3% CaCl2, .25pps Cell-o-Flake, 5pps LCM1, .4%FL-52, .4%SMS. Lead in w/554sxs(1180cu-210bbls)Prem lite w/3% CaCl2, .25pps Cell-o-Flake, 5pps LCM1, .4% FL52, .4% SMS. Tail w/90sxs (132cu-23bbls)Type 3 cmt w/1% CaCl2, .25pps Cell-o-Flake, .2% FL52. Drop plug and displaced w/169bbls FW. Bumped plug from 1256# to 1760# @ 0826 hrs 1/5/06. Circulate 69bbls cmt to reserve pit. ND BOP. NU B-section and BOPE. PT csg 1500psi for 30mis, ok. 1/6/06 RIH 6 1/4" bit and tagged cmt @ 4290. D/O ahead to TD 7623'. TD reached 1/10/06. Circulated hole. 1/11/06 RIH w/4 1/2" 179jts of 11.6# L80 LT&C csg set @ 7622'. Preflush W/10bbls mud, 2bbls FW. Pumped lead cement w/9sxs(27cu-5bbls)prem lite w/.25pps Cell-o-Flake, .3% CD32, 6.25pps LCM1, 1% FL52. Tail 251sxs(497cu-89bbls)prem lite cmt w/.25 Cell-o-Flake, 3%CD32, 6.25pps LCM1, 1% FL52. Drop plug & displaced w/118bbls H2O. Bump plug from 106psi to 1090psi @ 0947hrs 1/11/06. RD. Rig released @ 1600hrs 1/11/06. Will show top of cement & casing PT on next report. PT will be conducted by completing rig. 14. I hereby certify that the foregoing is true and correct.

NMOCD