

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

2005 AUG 16 PM 1 23

1. **Type of Well**
GAS

2. **Name of Operator**
CDX RIO, LLC

3. **Address & Phone No. of Operator**

2010 Afton Place, Farmington, New Mexico 87401 (505) 326-3003

4. **Location of Well, Footage, Sec., T, R, M**
2335'FNL, 1300'FEL, Sec.3, T-26-N, R-5-W, NMPM

RECEIVED
070 FARMINGTON NM



5. **Lease Number**
Jicarilla Contract 151
6. **If Indian, All. or Tribe Name**
Jicarilla Apache
7. **Unit Agreement Name**

8. **Well Name & Number**

Jicarilla 151 #8F
9. **API Well No.**

30-039-29204
10. **Field and Pool**
Tapacito Gallup
WC Basin Mancos/Basin DK
11. **County and State**

Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment <input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion <input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging <input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair <input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing <input type="checkbox"/> Conversion to Injection
	<input checked="" type="checkbox"/> Other Spud

13. Describe Proposed or Completed Operations

8-2-05 MIRU. SDON.
8-3-05 Spud well @ 6:30 p.m. 8-3-05. Drill to 100'.
8-4-05 Drill @ 100-201'.
8-5-05 Drill @ 201-289'. Lost circ.
8-6-05 Circ hole clean. TIH to 280'. Pump 100 sx Class "B" cmt w/3% Econolite, 10 pps Gilsonite, 0.5 pps Flocele, 2% calcium chloride (291 cu.ft.). Displace w/wtr. No cmt returns to surface. WOC. Drill @ 289-309'.
Lost circ.
8-7-05 TOOH. TIH to 124'. Pump 100 sx Class "B" cmt w/5 pps Gilsonite, 0.75 pps Flocele, 2% calcium chloride (126 cu.ft.). WOC. Drill @ 309-440'.
8-8-05 Drill from 440' to 650'. Circ hole clean. TOOH. TIH w/16 jts 9 5/8" 36# K-55 ST&C csg, set @ 645'. Cmdt w/510 sx Class "B" cmt w/2% calcium chloride, 0.25 pps Celloflake (602 cu.ft.). Circ 45 bbl cmt to surface. WOC.
8-9-05 NU BOP. PT blind rams, outside valves, inside valves, kill line valve & check to 1000 psi high, 250 psi low, OK. PT pipe rams floor valve & kelly valve to 1000 psi high, 250 psi low, OK. Drilling ahead.

APD ROW related

14. I hereby certify that the foregoing is true and correct.

Signed Nancy Oltmanns Title Agent

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

AUG 18 2005

Date
FARMINGTON FIELD OFFICE
BY do

NMOCD