

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other instructions on reverse side)

FOR APPROVED

OMB NO. 1004-0137

Expires: December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO.

NMSF-079074

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 30-6 Unit NMMN 78420B

8. FARM OR LEASE NAME, WELL NO.

San Juan 30-6 Unit #467S

9. API WELL NO.

30-039-29408

10. FIELD AND POOL, OR WILDCAT

BASIN FRUITLAND COAL

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

SEC. 22, T30N, R7W, NMPM

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL:

OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐

b. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☐ Other ☐

RECEIVED

FARMINGTON NM

2. NAME OF OPERATOR

BURLINGTON RESOURCES OIL & GAS COMPANY

3. ADDRESS AND TELEPHONE NO.

PO BOX 4289, Farmington, NM 87499 (505) 326-9700

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface SEC. 22, T30N, R7W, NMPM
SEnw 2365 FNL 1420 FWL

At top prod. interval reported below

At total depth

14. PERMIT NO.

DATE ISSUED

12. COUNTY OR

PARISH
San Juan

13. STATE

New Mexico

15. DATE SPUNDED

7/2/05

16. DATE T.D. REACHED

2/16/06

17. DATE COMPL. (Ready to prod.)

2/20/06

18. ELEVATIONS (DF, RKB, RT, BR, ETC.)*

6714' GL, 6726' KB

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

3682'

21. PLUG, BACK T.D., MD & TVD

3680'

22. IF MULTIPLE COMPL., HOW MANY*

23. INTERVALS DRILLED BY

ROTARY TOOLS

CABLE TOOLS

yes

24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)*

3423'-3595' Fruitland Coal

25. WAS DIRECTIONAL SURVEY MADE

YES

26. TYPE ELECTRIC AND OTHER LOGS RUN

NONE

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
9 5/8"	32.3# H-40	405'	12 1/4"	86 cu ft	
7	23# J-55	3352'	8 3/4"	919 cu ft	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
5 1/2"	3335'	3687'	NONE		2 3/8"	3648'	

31. PERFORATION RECORD (Interval, size and number)

3423'-3595'

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
3423'-3595'	NONE

33. PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
2/20/06		Flowing				SI	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N FOR TEST PERIOD	OIL-BBL	GAS-MCF	WATER-BBL	GAS-OIL RATIO
2/17/06	1 hour		→				
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL-BBL	GAS-MCF	WATER-BBL	OIL GRAVITY-API (CORR.)	
SI 0	74	→	0	1445 mcf	0		

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

TEST WITNESSED BY

ACCEPTED FOR RECORD

35. LIST OF ATTACHMENTS

None

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED Joni Clark TITLE Sr. Staff Regulatory Specialist

DATE 3/1/06

FARMINGTON FIELD OFFICE
BY [Signature]

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department of agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries);

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	GEOLOGIC MARKERS		
				NAME	MEAS. DEPTH	TRUE VERT. DEPTH

o Alamo	2534'	2738'	White, cr-gr ss.			
rtland	2738'	3360'	Gry sh interbedded w/tight, gry, fine-gr ss.			
uitland	3360'	3604'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Ojo Alamo Kirtland Fruitland Pic.Cliffs	2534' 2738' 3360' 3604'	
ctured Cliffs	3604'		Bn-Gry, fine grn, tight ss.			