This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator BR			Lease	Name SAN	Well No. 21			
ocation of W	ell: Unit Lett	ter K S	ec 05	Twp 029N	Rge	004W API	# 30-039-21453	
	Name of Reservoir or Pool			Type of Prod		Method of Prod	Prod Medium	
Upper Completion	PC		Gas		Flow		Tubing	
Lower Completion					Flow		Tubing	
			Pre-Flow S	hut-In Pressu	re Data			
Upper Completion	Hour, Date, 5/19/2	015	Length o	Length of Time Shut-In 216 hours		ss. PSIG 268	Stabilized?(Yes or No) Yes	
Lower Completion	Hour, Date, \$ 5/19/2			of Time Shut-In hours	SI Pre	ss. PSIG 647	Stabilized?(Yes or No) Yes	
			Flo	w Test No. 1				
Commenced	at:	5/26/2015		Zone Pro	oducing (Uppe	r or Lower): LC	OWER	
Time Lapsed Time			PRESSURE		Prod Zone			
(date/tim	e)	Since*	Upper zone	Lower zone	Temperature		Remarks	
5/26/201	5	0	268	647				
5/27/201	5	24	263	127				
5/28/201	5/28/2015 48		224	80				
Production rat	e during test							
Dil: BPOD Based on: B			Bbls. In	Bbls. In Hrs.		Grav.	GOR	
Gas		MCFPD; Test th	nru (Orifice or M	eter)				
			Mid-Test S	hut-In Pressu	re Data			
Upper Completion	pper Hour, Date, Shut-In			Length of Time Shut-In		ss. PSIG	Stabilized?(Yes or No)	
Lower Hour, Date, Shut-In Completion		I ength o	of Time Shut-In	SI Pre	ss. PSIG	Stabilized?(Yes or No)		

(Continue on reverse side)

OIL CONS. DIV DIST. 3

JUL 07 2015

Northwest New Mexico Packer-Leakage Test

Flow Test No. 2

Commenced at:			Zone Pro	oducing (Uppe	er or Lower)	
Time (date/time)	Lapsed Time Since*	PRESSURE		Prod Zone		Danasalas
		Upper zone	Lower zone	Temperature		Remarks
Production rate durin	g test D Based on:	Bbls. In	Hrs.		Grav.	GOR
	D Based on:				Grav.	GOR
Oil: BPO Gas Remarks:	D Based on:MCFPD; Test t	hru (Orifice or M			Grav.	GOR _
Oil: BPO Gas Remarks:	D Based on:	hru (Orifice or M			Grav.	GOR _
Oil: BPO Gas Remarks:	D Based on:MCFPD; Test t	hru (Orifice or M			Grav.	GOR _
Oil:BPO Gas Remarks: There is a decrease	D Based on: MCFPD; Test to the lower pressure and the lower pressur	hru (Orifice or M	leter)			
Oil:BPO Gas Remarks: There is a decrease I hereby certify that the	D Based on: MCFPD; Test to the lower pressure and the information herein one information h	thru (Orifice or M zone. contained is true	leter)e and complete	e to the best o		
Oil:BPO Gas Remarks: There is a decrease I hereby certify that the decrease Approved: Jahn	D Based on: MCFPD; Test to the lower pressure and the lower pressure and the information herein to the lower pressure and the lower pres	thru (Orifice or M zone. contained is true	fleter)e and complete	e to the best o	f my knowled	
Oil:BPO Gas Remarks: There is a decrease I hereby certify that the decrease Approved: Jahn	D Based on: MCFPD; Test to the lower pressure and the information herein one information h	thru (Orifice or M zone. contained is true	leter)e and complete	e to the best o	f my knowled	
Oil:BPO Gas Remarks: There is a decrease I hereby certify that the second content of the second co	D Based on: MCFPD; Test to the lower pressure and the lower pressure and the information herein to the lower pressure and the lower pres	thru (Orifice or Mozone. contained is true	fleter)e and complete	e to the best o	f my knowled	

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual
 completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion.
 Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or
 chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or
 the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when
 requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.

- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure
 for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall
 remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

^{5.} Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above