

API 30-045-07516

OIL CONS. DIV DIST. 3

DEC 18 2015



Gallegos Canyon Unit 167
Dakota
API # 30-045-07516
Sec 18, T28N, R11W
San Juan County, NM

Well History

6/6/64: Spud date.
7/7/64: Completion date
2/17/95: Pulled plunger. Tagged fill at 5952'. Fluid level at 5375'
2/23/95: Cleaned out wellbore.
3/1/01: Wireline. Tagged fill @ 6067'. Fluid level at 5820'.
Set FB stop @ 6019'
11/4/09: Attempted to wireline. Location smelled of H2S.
Tested at 16 ppm.

Ground Elevation 5525
KB Measurement

Deviation Survey

Depth	Deviation
330	0.25
1016	0.5
2076	0.5
2080	1.25
2612	0.75
3260	1.25
3700	0.25
4186	0.25
4700	1
5142	0.75
5666	1
6004	1

TOC: surface

Surface Casing Data

13 3/4" hole
10 3/4", 32.75# casing at 316'
Cmt w/ 200 sx

TOC: Unknown

Formation Tops

Pictured Clif	1465
Lewis Shale	1663
Mesaverde	3030
Mancos Shal	4197
Gallup	5089
Base Gallup	5450
Greenhorn S	5884
Graneros Sh	5942
Graneros Da	5,978
Main Dakota	6,059

Tubing Details

2 3/8" tubing

Length

Stage tool @ 4301'

Perforation Data

5982-5992
6005-6010
Frac'd w/ 30,828 gals wtr, and 20,000# 20/40 & 7000# 10/20 sand
6066-6090
Frac'd w/ 47,964 gals wtr, and 30,000# 20/40 & 8000# 10/20 sand

Production Casing Data

9 7/8" hole
4 1/2", 10.5# casing to 6184'
Stage 1: 500 sx
Stage 2: 1100 sx cmt

2 3/8" tubing at 6070.61'

PBTD 6120
Total Depth 6155