

API 30-045-2401

OIL CONS. DIV DIST. 3

DEC 18 2015



Crawford GC B 1E

Chacra

API # 30-045-24011

T-29N, R-12-W, Sec. 24

San Juan County, New Mexico

History

Spud Date: 01/10/1980

Plugged Dakota & Recompl Chacra 6/2003

Rod Details (12/2010)

	Length
ROD, POLISHED: 1.25 X 16 FT	16'
ROD, PONY: 0.75 X 2 FT	2'
ROD, PONY: 0.75 X 4 FT	4'
ROD, PONY: 0.75 X 6 FT	6'
COROD: 0.75 X 6 FT	6'
RODS: 0.75 X 25 GRD. D, 116 JTS	2899.99'
PUMP, 2.0 X 1.25 X 14	14'

Chacra Perfs

2700'-2844'
w/ 3 jspm; total of 48 shots

Dakota Perfs

6191'-6205'
w/ 2 spf of 30 holes of 1/2" dia
6274'-6322'
w/ 2 spf total of 106 holes of 1/2" dia

BH repair
@ 1350'

EOT @ 2954'

PBTD: 6369'
TD: 6395'

G.L. 5632'
K.B. 5645'

12-1/4" Hole
8-5/8", 20#, J-55 @ 306
w/ 315 sx cmt w/ 2% CaCl₂
circulated to surface

Tubing Details (12/2010)

	Length
TUBING, 2.375, 4.7#, J-55, EUE, 93 JTS	2922.47'
NIPPLE, PROFILE, "F", 2.375 OD, 2.780 ID	0.95'
MULE SHOE, 2.375	18.14'

Frac'd

w/ 500 gals of HCL acid, followed by 58,534#
16/30 sand, Pump 70% N₂ foam

CIBP set @ 3300'

DV Tool set @ 4595'
150' of cement behind casing above DV tool

Frac'd

30,000 gal frac fluid, 127,000 # sand
60,000 gal frac fluid and 195,000 # sand

7-7/8" Hole
4 1/2", 11.6#, K-55 @ 6395'
900 sxs class B Neat cement
containing 56:35 Poz gel, 2# medium tuff plug