This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator CO	P		Leas	e Name SAN	JUAN 28-7 UN	IIT	Well No. 20A
Location of W	ell: Unit l	_etter J S	ec 08	Twp 028N	I Rge	007W API	# 30-039-22207
	Name of Reservoir or Pool			Type of Prod		Method of Prod	Prod Medium
Upper Completion	PC		Gas	4	Flow		Tubing
Lower Completion	MV		Gas		Artific	ial Lift	Tubing
			Pre-Flow S	Shut-In Pressu	ure Data		
Upper Completion	Hour, Date, Shut-In 5/12/2016			Length of Time Shut-In 96 hours		ss. PSIG 204	Stabilized?(Yes or No) Yes
Lower Completion	Hour, Date, Shut-In 5/12/2016			Length of Time Shut-In 153 hours		ss. PSIG 108	Stabilized?(Yes or No) Yes
			Flo	ow Test No. 1			
Commenced	at:	5/16/2016		Zone Pro	oducing (Uppe	r or Lower): UF	PER
Time (date/tim	ne)	Lapsed Time Since*	PRES Upper zone	SSURE Lower zone	Prod Zone Temperature		Remarks
5/17/2016		24	63	108		Achieved 20% cr	oss over
5/18/2016 9:35:19 AM		57	56	108	÷	Achieved 20% cross over	
Production rat	e during t	est					
Dil: BPOD Based on:			Bbls. In	Bbls. In Hrs.		Grav.	GOR
Gas		MCFPD; Test th	ru (Orifice or N	leter)			
			Mid-Test 9	Shut-In Pressu	ire Data		
Upper Completion	Hour, Date, Shut-In			Length of Time Shut-In		ss. PSIG	Stabilized?(Yes or No)
Lower Completion	Hour, Date, Shut-In		Length	Length of Time Shut-In		s. PSIG	Stabilized?(Yes or No)

(Continue on reverse side)

OIL CONS. DIV DIST. 3

MAY 2 5 2016

Flow Test No. 2

Commenced at:			Zone Pro	Zone Producing (Upper or Lower)			
Time	Lapsed Time	PRESSURE		Prod Zone			
(date/time)	Since*	Upper zone	Lower zone	Temperature	Remarks		
		_					
Production rate during Oil:BPO	D Based on: MCFPD; Test to	Bbls. In		Grav.	GOR		
Remarks:							
hereby certify that th	ne information herein o	contained is true	and complete	to the best of my know	vledge.		
Approved:	-JUNE	20/6	Operat	tor: COP			
	onservation Division		_	By: Austin Haws			
1 4	Dudan						
By: Josh	moran .		Title:	Title: Multi-Skilled Operator			
Title: DEPUTY O	IL& GAS INSP	Eulda	Date:	Monday, May 23, 20	16		
	DISTRICT #3						

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual
 completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion.
 Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or
 chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or
 the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when
 requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.

- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure
 for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall
 remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals therafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.