(August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED OMB No. 1004- 0135

Expires: November 30, 2000

5. Lease Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS			NOG-0103-1465			
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.				6. If Indian, Allottee, or Tribe Name NAVAJO ALLOTTED		
7. If Unit or CA. Agreement Designation 1. Type of Well						
Oil Well X Gas Well	Other			8. Well Name and No.		
2. Name of Operator				MEG COM #1		
COLEMAN OIL & GAS	, INC.	3b. Phone No. (incli	udo ama cada)	9. API Well No.	20000	
3a. Address	F	(EDE) 00	•	30-045- 10. Field and Pool, or E		
PO DRAWER 3337 4. Location of Well (Footage, Sec., T.,	Farmington NM 87499-333 R., M., or Survey Description)	(303) 32	7-0550	4	ruitland Coal	
				11. County or Parish, St	1 200 1 200	
1715' FNL	AND 1850' FEL, SECT	TION 19, T26N, F	11W	SAN JUAN COUNT	Y, NM	
12. CHECK APPROP	PRIATE BOX(S) TO INDI	CATE NATURE O	NOTICE, REPOR	T, OR OTHER DATA	4	
TYPE OF SUBMISSION			TYPE OF ACTION			
X Notice of Intent	Acidize	Deepen	Production (Start/	Resume)	r Shut-off	
	Altering Casing	Fracture Treat	Reclamation	Well	Integrity	
Subsequent Report	Casing Repair	New Construction	Recomplete	X Other	SEE BELOW	
	Change Plans	Plug and abando	Temporarily Aband	don		
Final Abandonment Notice	Convert to Injection	Plug back	Water Disposal			
If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths or pertinent markers and sands. Attach the Bond under which the work will performed or provide the Bond No. on file with the BLM BlA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notice shall be filed only after all requirements, including reclamantion, have been completed, and the operator has determined that the site is ready for final inspection.) Coleman Oil & Gas, Inc., intends to dispose of produced water into the Cowsaround SWD #1 as per the conditions stated in the Department of the Interior Onshore Oil & Gas Order No. 7 for Off-Lease Water Disposal. APPROVED JUN - 6 2003 JUN						
14. I hereby certify that the foregoing is Name (Printed/ Typed) WENDY ROGERS Signature	s true and correct.	Title P Date	RODUCTION ACCT	2.2.7.2.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.	7	
_/Vendy Xe	MPIS	06-0				
Approved by	THIS SPACE	Title	a (4) regordates (18) es	IDate		
			· · · · · · · · · · · · · · · · · · ·			
Conditions of approval if any are attack	had Anninval of this notice dose	not warrant or IOffice				

certify that the applicant holds again or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title 18 U.S.C. Section 1001 AND Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitiousor fraudulent statements or representations as to any matter within its jurisdiction.

Onshore Order No. 7 and Title 43 CFR 3162.5-1

The above noted 43 CFR 3162.5	d lease/well d	isposes wat le following	er without informati	approval. O on be submit	nshore Order N ted in order to	(o. 7 and process	. Title water	disposal	
43 CFR 3102.3	-r'i voidereeen				•		• •	•	
requests.	•	•	•		•			•	
		1	. on the le	BASIN	FRUITLANI	COAL			

equesa.
Name of formations producing water on the lease BASIN FRUITLAND COAL /bbls
2. Amount of water produced from all formations in barrels per day. 141 per day @ 4/200.
Attach a current water analysis of produced water from all zones showing at least the total dissolved solids, ph, and the concentrations of chlorides and sulfates.
4. How water is stored on the lease. TANK
5. How water is moved to the disposal facility. TRUCK
6. Identify the Disposal Facility by:
a. Facility operators name. COLEMAN OIL & GAS, INC.
b. Name of facility or well name & number. COWSAROUND SWD #1
.c. Type of facility or well (WDW)(WIW) etc. SWD
d. Location by 1/4 1/4 section 16 township 26N range 12W
7. Attach a copy of the State issued permit for the Disposal Facility.
Submit to this office, the above required information on a Sundry Notice 3160-5. Submit 1 original at 2 copies. (You may also complete this form and attach it to the Sundry Notice.)
BACK UP DISPOSALIS: ELM RIDGE - CBU CARSON

BASIN DISPOSAL

Analytical Laboratory Report for:

Coleman Oil



Production Water Analysis

Listed below please find water analysis report from: MEG, #1

Lab Test No:

2003117473

Sample Date:

04/17/2003

Specific Gravity: 1.023

TDS:

33330

pH:


6.48

Cations:	mg/L	as:	
Calcium	234	(Ca [↔])	
Magnesium	90.78	(Mg ⁺⁺)	
Sodium	12370	(Na [†])	
Iron	6.79	(Fe ⁺⁺)	
Barium	5.46	(Ba ⁺⁺)	
Strontium	22.83	(Sr)	
Manganese	0.15	(Mn)	
Anions:	mg/L_	as:	
Bicarbonate	789	(HCO,)	
Sulfate	11	(SO ₄ ⁼)	
Chloride	19800	(Ci)	
Gases:			
Carbon Dioxide	97	(CO ₂)	
Hydrogen Sulfide	0	(H ₂ S)	

Meg #1

Coleman Oil

Lab Test No: 2003117473



DownHole SAT[™] Scale Prediction @ 100 deg. F

Mineral Scale	Saturation Index	Momentary Excess (lbs/1000 bbls)	
Calcite (CaCO3)	.508	201	
Aragonite (CaCO3)	.43	274	
Witherite (BaCO3)	.00376	-15.72	
Strontianite (SrCO3)	.101	-2.28	
	212	646	
Magnesite (MgCO3)	.00127	-794.79	
Anhydrite (CaSO4)	.0015	-799.25	
Gypsum (CaSO4*2H2O)	.514	-1.79	
Barite (BaSO4)	.00209	-200.25	
Celestite (SrSO4)	1	-54.25	
Silica (SiO2)	0	-1.31	
Brucite (Mg(OH)2)	< 0.001	-116.73	
Magnesium silicate	0		
Siderite (FeCO3)	28.99	.232	
Halite (NaCl)	.00328	-182292	
Thenardite (Na2SO4)	< 0.001	-62887	
Iron sulfide (FeS)	0	0679	

Interpretation of DHSat Results:

The Saturation Index is calculated for each mineral species independently and is a measure of the degree of supersaturation (driving force for precipitation) under the conditions modeled. This value ranges from 0 to infinity with 1.0 representing a condition of equilibrium where scale will neither dissolve nor precipitate. Values less than 1.0 are undersaturated and values greater than 1.0 are supersaturated. The scale is logarithmic, i.e. a Saturation Index of 3 is 10 times more saturated than a value of 2.

The Momentary excess is a measure of how much scale would have to precipitate to bring the system back to a non-scaling condition. This value ranges from negative (dissolving) infinity to positive (precipitating) infinity. The Momentary Excess represents the amount of scale possible while the Saturation Level represents the probability that scale will form.



NEW MEXICO ENERGY, MINERALS and NATURAL RESOURCES DEPARTMENT

GARY E. JOHNSON

Governor

Betty Rivera

Cabinet Secretary

Lori Wrotenbery
Director
Oil Conservation Division

ADMINISTRATIVE ORDER SWD-764 (2nd Corrected)

APPLICATION OF PENDRAGON ENERGY PARTNERS FOR PRODUCED WATER DISPOSAL, SAN JUAN COUNTY, NEW MEXICO.

ADMINISTRATIVE ORDER OF THE OIL CONSERVATION DIVISION

Under the provisions of Rule 701(B), Pendragon Energy Partners made application to the New Mexico Oil Conservation Division on February 9, 2000, for permission to complete for produced water disposal its Cowsaround SWD Well No. 1 (API No. 30-045-30096) located 2220 feet from the South line and 1680 feet from the West line (Unit K) of Section 16, Township 26 North, Range 12 West, NMPM, San Juan County, New Mexico.

THE DIVISION DIRECTOR FINDS THAT

- (1) The application has been duly filed under the provisions of Rule 701(B) of the Division Rules and Regulations;
- (2) Satisfactory information has been provided that all offset operators and surface owners have been duly notified;
- (3) The applicant has presented satisfactory evidence that all requirements prescribed in Rule 701 will be met; and
 - (4) No objections have been received within the waiting period prescribed by said rule.

IT IS THEREFORE ORDERED THAT:

The applicant herein, is hereby authorized to complete its Cowsaround SWD Well No. 1 (API No. 30-045-30096) located 2220 feet from the South line and 1680 feet from the West line (Unit K) of Section 16, Township 26 North, Range 12 West, NMPM, San Juan County, New Mexico, in such a manner as to permit the injection of produced water for disposal purposes into the Mesaverde formation from approximately 2,000 feet to 3,882 feet through 2 7/8 inch plastic-lined tubing set in a packer located at approximately 1,908 feet.

IT IS FURTHER ORDERED THAT:

The operator shall take all steps necessary to ensure that the injected water enters only the proposed injection interval and is not permitted to escape to other formations or onto the surface.

Prior to commencing injection operations into the well, the casing shall be pressure tested from the surface to the packer setting depth to assure the integrity of said casing.

The casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge at the surface or left open to the atmosphere to facilitate detection of leakage in the casing, tubing, or packer.

The injection well or system shall be equipped with a pressure limiting device which will limit the wellhead pressure on the injection well to no more than 400 psi.

The Director of the Division may authorize an increase in injection pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the injected fluid from the Mesaverde formation. Such proper showing shall consist of a valid step-rate test run in accordance with and acceptable to this office.

The operator shall notify the supervisor of the Aztec district office of the Division of the date and time of the installation of disposal equipment and of any mechanical integrity test so that the same may be inspected and witnessed.

The operator shall immediately notify the supervisor of the Aztec district office of the Division of the failure of the tubing, casing, or packer in said well and shall take such steps as may be timely and necessary to correct such failure or leakage.

PROVIDED FURTHER THAT, jurisdiction is retained by the Division for the entry of such further orders as may be necessary for the prevention of waste and/or protection of correlative rights or upon failure of the operator to conduct operations (1) to protect fresh water or (2) consistent with the requirements in this order, whereupon the Division may, after notice and hearing, terminate the injection authority granted herein.

The operator shall submit monthly reports of the disposal operations on Division Form C-115, in accordance with Rule Nos. 706 and 1120 of the Division Rules and Regulations.

The injection authority granted herein shall terminate one year after the effective date of this order if the operator has not commenced injection operations into the subject well, provided however, the Division, upon written request by the operator, may grant an extension thereof for good cause shown.

Administrative Order SWD-764 (2nd Corrected) Pendragon Energy Partners April 1, 2002 Page 3

Approved at Santa Fe, New Mexico, on this 1st day of April, 2002.

LORI WROTENBERY, Director

LW/DRC

cc: Oil Conservation Division – Aztec State Land Office – Oil and Gas Division

NOG01031465

Meg com #1 API No. 3004530999

Conditions of Approval for Disposal of Produced Water Under Onshore Oil and Gas Order No. 7

- 1. All existing earthen pits (emergency, reserve, production) must be closed according to the standards contained in either the Approved Application for Permit to Drill (AAPD) or if applicable the New Mexico Pit Closure standards by July 9, 2003.
- 2. The closed pit areas will be recontoured and reseeded according to the standards contained in either the AAPD. If no reclaimation proceedures are contained in the AAPD, an on-site will be scheduled with the Federal Indian Minerals Office at (505) 599-6375 prior to beginning pit closure.
- All excess or unused equipment, pipe, pipe fittings and trash shall be removed at the time the pits are closed.
- 4. All storage tanks (oil or water) shall be surrounded by a berm/dike sufficient to contain 150% of the capacity of the total volume of the tanks surrounded or 1 day of production whichever is greater. Berm/dike walls will be compacted with appropriate equipment to assure proper construction.
- 5. All above ground facilities shall be painted in accordance with the AAPD. If no painting requirements are contained in the AAPD, an on-site will be scheduled with the Federal Indian Minerals Office at (505) 599-6375.
- 6. Bermed/diked areas will be fenced to existing standards at the time the pits are closed and the berms/dikes and fencing shall be maintained.
- 7. Access to the inside of all fenced areas shall be included in fence design.
- 8. Compressor units on this well location not equipped with a drip pan for containment of fluids shall be lined with an impervious material at least 8 mils thick and a 12 inch berm. The compressor will be painted to match the well facilities. Any variance to this will be approved by the authorized officer (AO). When compressor units are washed, or any other equipment associated with the locations, the fluids (i.e., scrubber cleaners) will be properly disposed of to avoid ground contamination or hazard to livestock or wildlife.
- 9. Use of pesticides and herbicides shall comply with applicable federal/state laws. Pesticides and herbicides shall be used only in accordance with their registered uses and within limitations imposed by the Secretary of the Interior. Prior to the use of pesticides, holder shall obtain from the AO written approval of a plan showing the type and quantity of material to be used, pest(s) to be controlled, method of application, location of storage and disposal of containers, and any other information deemed necessary. Emergency use of pesticides shall be approved in writing by the AO prior to use.
- 10. The holder shall be responsible for weed control and selective control of invasive weeds on disturbed and reclaimed areas within the limits of the well pad, associated road and pipeline ROW. The holder is responsible for consultation with the AO and/or local authorities for acceptable weed control methods within limits imposed in the conditions of approval.
- 11. Discovery of Threatened/Endangered/Sensitive Species (TES) Plant/Animal: If, in its operations, the operator/holder discovers any Threatened/Endangered/Sensitive Species Plant/Animal, then work in the vicinity of the discovery will be suspended and the discovery promptly reported to the Federal Indian Minerals Office at (505) 599-6375. BLM will then specify what action is to be taken. Failure to notify the BLM about a discovery may result in civil or criminal penalties in accordance with the Endangered Species Act of 1973 (as amended).