

State of New Mexico
Energy, Minerals and Natural Resources Department

Susana Martinez
Governor

Tony Delfin
Acting Cabinet Secretary

David R. Catanach, Division Director
Oil Conservation Division



New Mexico Oil Conservation Division approval and conditions listed below are made in accordance with OCD Rule 19.15.7.11 and are in addition to the actions approved by BLM on the following 3160-3 APD form.

Operator Signature Date: 4-7-16

Well information:

Operator WPX, Well Name and Number W Lybrook Unit # 759 H

API# 30045-35766 Section 23, Township 23D N/S, Range 9 E/W

Conditions of Approval: (See the below checked and handwritten conditions)

- Notify Aztec OCD 24hrs prior to casing & cement.
- Hold C-104 for directional survey & "As Drilled" Plat
- Hold C-104 for NSL, NSP, DHC
- Spacing rule violation. Operator must follow up with change of status notification on other well to be shut in or abandoned
- Regarding the use of a pit, closed loop system or below grade tank, the operator must comply with the following as applicable:
 - A pit requires a complete C-144 be submitted and approved prior to the construction or use of the pit, pursuant to 19.15.17.8.A
 - A closed loop system requires notification prior to use, pursuant to 19.15.17.9.A
 - A below grade tank requires a registration be filed prior to the construction or use of the below grade tank, pursuant to 19.15.17.8.C
- Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
- Submit Gas Capture Plan form prior to spudding or initiating recompletion operations
- Regarding Hydraulic Fracturing, review EPA Underground Injection Control Guidance 84
- Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system.
- Well-bore communication is regulated under 19.15.29 NMAC. This requires well-bore Communication to be reported in accordance with 19.15.29.8.

Chuck Herin
NMOCD Approved by Signature

12-8-2016
Date

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

APR 08 2016

FORM APPROVED
OMB No. 1004-0136
Expires January 31, 2004

APPLICATION FOR PERMIT TO DRILL OR REENTER

Farmington Field Office
Bureau of Land Management

5. Lease Serial No.
NO-G-1312-1863

6. If Indian, Allottee or Tribe Name

7. If Unit or CA Agreement, Name and No.
NMNM 133613X 135216X

8. Lease Name and Well No.
W. Lybrook Unit #759H

9. API Well No.
30-045-35766

10. Field and Pool, or Exploratory
Lybrook Mancos W

11. Sec., T., R., M., or Blk. and Survey or Area
SHL: Sec 23, T23N, R9W

BHL: Sec 25, T23N, R9W

12. County or Parish
San Juan

13. State
NM

17. Spacing Unit dedicated to this well
400-Acres / 12,807.24 Acres

20. BLM/BIA Bond No. on file
B001576

22. Approximate date work will start*
May 1, 2016

23. Estimated duration
1 month

24. Attachments

1a. Type of Work: DRILL REENTER

1b. Type of Well: Oil Well Gas Well Other Single Zone Multiple Zone

2. Name of Operator
WPX Energy Production, LLC

3a. Address
P.O. Box 640 Aztec, NM 87410

3b. Phone No. (include area code)
(505) 333-1808

4. Location of Well (Report location clearly and in accordance with any State requirements. *)

At surface M 601' FSL & 628' FWL, sec 23, T23N, R9W
At proposed prod. zone N 330' FSL & 2374' FWL, sec 25 T23N, R9W

14. Distance in miles and direction from nearest town or post office*
From intersection US Hwy & 550 US Hwy 64 in Bloomfield NM, South 37.8 miles to Mile Marker 113.4

15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 601'

16. No. of Acres in lease
160 Acres

17. Spacing Unit dedicated to this well
400-Acres / 12,807.24 Acres

18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 20'

19. Proposed Depth
14163' MD / 4618' TVD

20. BLM/BIA Bond No. on file
B001576

21. Elevations (Show whether DF, KDB, RT, GL, etc.)
6748' GR


22. Approximate date work will start*
May 1, 2016

23. Estimated duration
1 month


The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, shall be attached to this form:

- Well plat certified by a registered surveyor.
- A Drilling Plan.
- A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office).

- Bond to cover the operations unless covered by an existing bond on file (see item 20 above).
- Operator certification.
- Such other site specific information and/or plans as may be required by the authorized officer.

25. Signature  Name (Printed/Typed)
Marie E. Jaramillo

Date
4/7/16

Title
Permit Technician III
Approved by (Signature) 

Name (Printed/Typed)
Office FFO

Title
AFN

Date
11/28/16

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*(Instructions on reverse)
WPX Energy Production, LLC, proposes to develop the Lybrook Mancos W formation at the above described location in accordance with the attached drilling and surface use plans.

The well pad surface is under jurisdiction of IA and is on lease and will be twinned with the W. Lybrook Unit #726H/728H/729H/760H & 761H.

This location has been archaeologically surveyed by Western Archeological Consultants. Copies of their report have been submitted directly to the BLM.

The new access of 21.1' of BLM & new access of 4584.3' of Navajo Allotted is on lease access road will be built and permitted via the APD.

A new pipeline of 68.3' of BLM & new pipeline of 4779.8' of Navajo Allotted is on lease well connect pipeline will be built and permitted via the APD.

BLM'S APPROVAL OR ACCEPTANCE OF THIS APPLICATION DOES NOT CONSTITUTE AN AUTHORIZATION FOR THE OPERATOR FROM OBTAINING ANY OTHER AUTHORIZATION REQUIRED FOR OPERATIONS ON FEDERAL AND INDIAN LANDS

DRILLING OPERATIONS AUTHORIZED ARE SUBJECT TO COMPLIANCE WITH ATTACHED "GENERAL REQUIREMENTS"

This action is subject to technical and procedural review pursuant to 43 CFR 3165.3 and appeal pursuant to 43 CFR 3165.4

NMOCDAV

OIL CONS. DIV DIST. 3
NOV 29 2016

KD

District I
1625 N. French Drive, Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II
811 S. First Street, Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720

District III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170

District IV
1220 S. St. Francis Drive, Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department

Form C-102
Revised August 1, 2011

Submit one copy to
Appropriate District Office

OIL CONSERVATION DIVISION
1220 South St. Francis Drive
Santa Fe, NM 87505

AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

*API Number 30-045-35764		*Pool Code 98157	*Pool Name LYBROOK MANCOS W
*Property Code 315250	*Property Name W LYBROOK UNIT		*Well Number 759H
*OGRID No. 120782	*Operator Name WPX ENERGY PRODUCTION, LLC		*Elevation 6748

10 Surface Location


UL or lot no.	Section	Township	Range	Lot Ion	Feet from the	North/South line	Feet from the	East/West line	County
M	23	23N	9W		601	SOUTH	628	WEST	SAN JUAN

11 Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Ion	Feet from the	North/South line	Feet from the	East/West line	County
N	25	23N	9W		330	SOUTH	2374	WEST	SAN JUAN

*Dedicated Acres 400.0	SW/4 NW/4, N/2 SW/4 SE/4 SW/4 - Section 25 N/2 NE/4, SE/4 NE/4 - Section 26 E/2 SW/4, SW/4 SE/4 - Section 23	*Joint or Infill	*Consolidation Code	*Order No. R-14051 - 12,807.24 Acres
---------------------------	-----------------------------------------------------------------------------------------------------------------------	------------------	---------------------	-----------------------------------------

NO ALLOWABLE WILL BE ASSIGNED
TO THIS COMPLETION UNTIL ALL
INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS
BEEN APPROVED BY THE DIVISION



17 OPERATOR CERTIFICATION
I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom-hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division

Signature: *Marie E. Jaramillo* Date: 4/7/16
Printed Name: Marie E. Jaramillo
E-mail Address: marie.jaramillo@wpxenergy.com

18 SURVEYOR CERTIFICATION
I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision and that the same is true and correct to the best of my belief.

Date Revised: FEBRUARY 11, 2016
Survey Date: SEPTEMBER 10, 2015

Signature and Seal of Professional Surveyor

JASON C. EDWARDS
NEW MEXICO
REGISTERED PROFESSIONAL SURVEYOR
15269

JASON C. EDWARDS
Certificate Number 15269

WPXENERGY

WPX Energy

Operations Plan

(Note: This procedure will be adjusted onsite based upon actual conditions)

Date: April 14, 2016
Well Name: W Lybrook Unit 759H
SH Location: SWSW Sec 23 23N-09W
BH Location: SESW Sec 25 23N-09W
Field: Lybrook Mancos W
Surface: IA
Elevation: 6748' GR
Minerals: IA

Measured Depth: 14,163.27'

I. GEOLOGY

Surface formation - NACIMIENTO

A. FORMATION TOPS: (KB)

NAME	MD	TVD	NAME	MD	TVD
OJO ALAMO	377	337	POINT LOOKOUT	3571	3404
KIRTLAND	499	499	MANCOS	3760	3579
PICTURED CLIFFS	1071	1067	GALLUP	4124	3918
LEWIS	1193	1186	KICKOFF POINT	4,086.62	3,882.65
CHACRA	1382	1368	TOP TARGET	5077	4648
CLIFF HOUSE	2571	2475	LANDING POINT	5,312.32	4,689.00
MENEFEE	2589	2492	BASE TARGET	5,312.32	4,689.00
			TD	14,163.27	4,618.00

B. MUD LOGGING PROGRAM:

Mudlogger on location from surface csg to TD.

C. LOGGING PROGRAM:

LWD GR from surface casing to TD.

D. NATURAL GAUGES:

Gauge any noticeable increases in gas flow. Record all gauges in Tour book and on morning reports.

II. DRILLING

A. MUD PROGRAM:

LSND mud (WBM) will be used to drill the 12-1/4" Surface hole, the 8 3/4" Directional Vertical hole, and the curve portion of the wellbore. A LSND (WBM) or (OBM) will be used to drill the lateral portion of well. Treat for lost circulation as necessary. Obtain 100% returns prior to cementing. Notify Engineering of any mud losses.

B. BOP TESTING:

While drill pipe is in use, the pipe rams and the blind rams will be function tested once each trip. The BOPE will be tested to 2,000 psi (High) for 10 minutes and the annular tested to 1,500 psi for 10 minutes. Pressure test surface casing to 1,500 psi for 30 minutes and intermediate casing to 1,500 psi for 30 minutes. Utilize a BOPE Testing Unit with a recording chart and appropriate test plug for testing. All tests and inspections will be recorded in the tour book as to time and results.

III. MATERIALS

A. CASING PROGRAM:

CASING TYPE	OH SIZE (IN)	DEPTH (MD)	CSG SIZE	WEIGHT	GRADE	CONN
SURFACE	12.25"	320.00'	9.625"	36 LBS	J-55 or equiv	STC
INTERMEDIATE	8.75"	5,312.32'	7"	23 LBS	J-55 or equiv	LTC
PRODUCTION	6.125"	5162.32' - 14,163.27'	4.5"	11.6 LBS	P-110 or equiv	LTC
TIE BACK	6.125"	Surf. - 5162.32'	4.5"	11.6 LBS	P-110 or equiv	LTC

B. FLOAT EQUIPMENT:

1. SURFACE CASING:

9-5/8" notched regular pattern guide shoe. Run (1) standard centralizer on each of the bottom (4) joints of Surface Casing.

2. INTERMEDIATE CASING:

7" cement nose guide shoe with a self-fill insert float. Place float collar one joint above the shoe. Install (1) centralizer on each of the bottom (3) joints and one standard centralizer every (3) joints to 2,500 ft. Run (1) centralizer at 2,500 ft., 2,300ft., 2,000ft., 1,500 ft., and 1,000 ft. If losses are encountered during the drilling of the intermediate section a DV tool will be utilized and a 2 stage cement job may be planned to ensure cement circ back to surface. The DV tool will be placed 100' above the top of the Chacra formation. If cement is circulated back to surface on the first stage, a cancellation device will be dropped to shift the dv tool closed and the 2nd stage cement job will be aborted at that time, if no cement is seen at surface on the 1st stage the stage tool will be opened and a 2nd stage cement job will be pumped.

3. PRODUCTION LINER:

Run 4-1/2" Liner with cement nose guide Float Shoe + 2jts. of 4-1/2" casing + Landing Collar + 4-1/2" pup joint + 1 RSi (Sliding Sleeve) positioned inside the 330ft Hard line. Centralizer program will be determined by Wellbore condition and when Lateral is evaluated by Geoscientists and Reservoir Engineers. Set seals on Liner Hanger. Test TOL to 1500 psi for 15 minutes.

C. CEMENT:

(Note: Volumes may be adjusted onsite due to actual conditions)

1. Surface:

5 bbl Fresh Water Spacer, 100 sx (160 cu.ft.) of 14.5 ppg Type I-II (Neat G) + 20% Fly Ash cement w/ 7.41 gal/sack mix water ratio @ 1.61 cu ft/sx yield. Calculated @ volume + 50% excess. WOC 12 hours. Test csg to 600psi. Total Volume: (160 cu-ft/100 sx/ Bbls). TOC at Surface.

2. Intermediate:

Spacer #1: 20 bbl (112 cuft) Chemwash. Lead Cement: 98 bbls, 278 sks, (548 cuft), 12.3 ppg @ 1.97 cuft/sk yield. Tail Cement: 59 bbls, 254 sks, (331 cuft), 13.5 ppg @ 1.3 cuft/sk yield. Displacement: Displace w/ +/- 209 bbl Drilling mud or water. Total Cement: 156 bbls, 532 sks, (879 cuft)

3. Prod Liner:

Spacer #1: 10 bbl (56 cu-ft) Water Spacer. Spacer #2: 40 bbl 9.5 ppg (224.6 cu-ft) Toned Spacer III. Spacer #3: 10 bbl Water Spacer. Lead Cement: Extencem™ System. Yield 1.36 cuft/sk 13.3 ppg (882 sx /1200 cuft /214 bbls). Tail Spacer: 20 BBL of MMCR. Displacement: Displace 'Planned WBD'lw/ +/-193 bbl Fr Water. Total Cement

D. COMPLETION:

Run CCL for perforating

A. PRESSURE TEST:

1. Pressure test 4-1/2" casing to 4500 psi max, hold at 1500 psi for 30 minutes. Increase pressure to Open RSI sleeves.

B. STIMULATION:

1. Stimulate with approximately 2,805,000# 20/40 mesh sand and 340,000# 16/30 mesh sand in 619,113 gallons water with 42,696 mscf N2 for 17 stages.
2. Isolate stages with flow through frac plug.
3. Drill out frac plugs and flowback lateral.

C. RUNNING TUBING:

1. Production Tubing: Run 2-7/8", 6.5#, J-55, EUE tubing with a SN on top of bottom joint. Land tubing near Top of Liner.

If this horizontal well is drilled past the applicable setbacks, an unorthodox location application is not required because the completed interval in this well, as defined by 19.15.16.7 B(1) NMAC, will be entirely within the applicable setbacks. This approach complies with all applicable rules, including 19.15.16.14 A(3) NMAC, 19.15.16.14 B(2) NMAC, 19.15.16.15 B(2) NMAC, and 19.15.16.15. B(4) NMAC.



NOTES:

A 4-1/2" 11.6# P-110 Liner will be run to TD and landed +/- 150 ft. into the 7" 23# J-55 Intermediate casing with a Liner Hanger and pack-off assembly then cemented to top of liner hanger.



After cementing and TOL clean up operations are complete, the TOL will be tested to 1500 psi (per BLM).



Well Name: W Lybrook UT #759H
 Surface Location: 2309-23M WLU
 NAD 1927 (NADCON CONUS) , US State Plane 1927 (Exact solution) New Mexico West 3003
 Ground Elevation: 6748.00
 +N/-S 0.00 +E/-W 0.00 Northing 1894520.52 Easting 520347.65 Latitude 36.206791 Longitude -107.764363 Slot A6
 GL @ 6748.00usft (Original Well Elev)



Project: T23N R6W
 Site: 2309-23M WLU
 Well: W Lybrook UT #759H
 Wellbore: Wellbore #1
 Design: Design #1 11Jan16 sam



Slot Name	+N/-S	+E/-W	Northing	Easting
A1	-80.08	-89.40	1894440.38	520258.31
A2	-66.61	-74.35	1894453.86	520273.35
A3	-53.51	-59.60	1894466.97	520288.09
A4	-26.57	-29.80	1894493.83	520317.87
A5	-13.47	-14.75	1894507.04	520332.91
A6	0.00	0.00	1894520.52	520347.65

DESIGN TARGET DETAILS								
Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude	Shape
Start 60 Tan #759H	4573.73	1000.91	466.49	1895521.76	520813.43	36.209541	-107.762782	Point
End 60 Tan #759H	4603.73	954.01	503.08	1895484.89	520850.04	36.209439	-107.762658	Point
POE #759H	4689.00	734.38	730.82	1895255.42	521077.95	36.208808	-107.761886	Point
BHL #759H	4618.00	-5549.70	6963.37	1888975.77	527314.96	36.191543	-107.740765	Point

ANNOTATIONS									
TVD	MD	Inc	Azi	+N/-S	+E/-W	V Sect	Departure	Annotation	
500.00	500.00	0.00	0.00	0.00	0.00	0.00	0.00	Start Build 2.00	
1561.92	1587.88	21.76	7.53	202.33	26.73	-105.20	204.09	Hold 21.76 Inclination	
3882.65	4086.62	21.76	7.53	1120.58	148.04	-582.64	1130.32	Start Build DLS 9.00 TFO 134.67	
4573.73	4913.88	60.00	135.24	1000.91	466.49	-259.02	1538.93	Hold 60.00 Inclination	
4603.73	4973.88	60.00	135.24	964.02	503.08	-207.41	1590.89	Start Build DLS 9.00 TFO 0.00	
4668.40	5144.76	75.38	135.24	852.11	614.06	-50.87	1748.50	Start DLS 9.00 TFO -0.01	
4689.00	5312.32	90.46	135.24	734.38	730.82	113.81	1914.30	POE at 90.46 Inc 135.24 Deg	
4618.00	14163.27	90.46	135.24	-5549.70	6963.37	8904.36	10764.97	TD at 14163.27	



WPX Energy

T23N R9W

2309-23M WLU

W Lybrook UT #759H - Slot A6

Wellbore #1

Plan: Design #1 11Jan16 sam

Standard Survey Report

12 January, 2016

WPX Survey Report

Company: WPX Energy	Local Co-ordinate Reference: Well W Lybrook UT #759H (A6) - Slot A6
Project: T23N R9W	TVD Reference: GL @ 6748.00usft (Original Well Elev)
Site: 2309-23M WLU	MD Reference: GL @ 6748.00usft (Original Well Elev)
Well: W Lybrook UT #759H	North Reference: True
Wellbore: Wellbore #1	Survey Calculation Method: Minimum Curvature
Design: Design #1 11Jan16 sam	Database: COMPASS

Project T23N R9W			
Map System: US State Plane 1927 (Exact solution)	System Datum: Mean Sea Level		
Geo Datum: NAD 1927 (NADCON CONUS)			
Map Zone: New Mexico West 3003			

Site 2309-23M WLU			
Site Position:	Northing: 1,894,520.52 usft	Latitude: 36.206791	
From: Map	Easting: 520,347.65 usft	Longitude: -107.764363	
Position Uncertainty: 0.00 usft	Slot Radius: 13.200 in	Grid Convergence: 0.04 °	

Well W Lybrook UT #759H - Slot A6					
Well Position	+N/-S 0.00 usft	Northing: 1,894,520.52 usft	Latitude: 36.206791		
	+E/-W 0.00 usft	Easting: 520,347.65 usft	Longitude: -107.764363		
Position Uncertainty	0.00 usft	Wellhead Elevation: 0.00 usft	Ground Level: 6,748.00 usft		

Wellbore Wellbore #1					
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2015	1/11/2016	9.34	62.90	49,882

Design Design #1 11Jan16 sam					
Audit Notes:					
Version:	Phase: PLAN	Tie On Depth: 0.00			
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (bearing)	
	0.00	0.00	0.00	128.55	

Survey Tool Program Date 1/12/2016					
From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description	
0.00	14,163.27	Design #1 11Jan16 sam (Wellbore #1)	MWD	MWD - Standard	

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (bearing)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
320.00	0.00	0.00	320.00	0.00	0.00	0.00	0.00	0.00	0.00	
9 5/8"										
500.00	0.00	0.00	500.00	0.00	0.00	0.00	0.00	0.00	0.00	
Start Build 2.00										
1,000.00	10.00	7.53	997.47	43.15	5.70	-22.43	2.00	2.00	0.00	
1,500.00	20.00	7.53	1,479.82	171.28	22.63	-89.06	2.00	2.00	0.00	
1,587.88	21.76	7.53	1,561.92	202.33	26.73	-105.20	2.00	2.00	0.00	
Hold 21.76 Inclination										
2,000.00	21.76	7.53	1,944.68	353.78	46.74	-183.95	0.00	0.00	0.00	

WPX

Survey Report

Company: WPX Energy	Local Co-ordinate Reference: Well W Lybrook UT #759H (A6) - Slot A6
Project: T23N R9W	TVD Reference: GL @ 6748.00usft (Original Well Elev)
Site: 2309-23M WLU	MD Reference: GL @ 6748.00usft (Original Well Elev)
Well: W Lybrook UT #759H	North Reference: True
Wellbore: Wellbore #1	Survey Calculation Method: Minimum Curvature
Design: Design #1 11Jan16 sam	Database: COMPASS

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (bearing)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
2,500.00	21.76	7.53	2,409.06	537.52	71.01	-279.48	0.00	0.00	0.00
3,000.00	21.76	7.53	2,873.44	721.26	95.28	-375.02	0.00	0.00	0.00
3,500.00	21.76	7.53	3,337.82	905.01	119.56	-470.56	0.00	0.00	0.00
4,000.00	21.76	7.53	3,802.20	1,088.75	143.83	-566.09	0.00	0.00	0.00
4,086.62	21.76	7.53	3,882.65	1,120.58	148.04	-582.64	0.00	0.00	0.00
Start Build DLS 9.00 TFO 134.67									
4,500.00	26.19	110.57	4,273.93	1,166.10	246.99	-533.63	9.00	1.07	24.93
4,913.88	60.00	135.24	4,573.73	1,000.91	466.49	-259.02	9.00	8.17	5.96
Hold 60.00 Inclination									
4,973.88	60.00	135.24	4,603.73	964.02	503.08	-207.41	0.00	0.00	0.00
Start Build DLS 9.00 TFO 0.00									
5,000.00	62.35	135.24	4,616.32	947.77	519.19	-184.69	9.00	9.00	0.00
5,144.76	75.38	135.24	4,668.40	852.11	614.06	-50.87	9.00	9.00	0.00
Start DLS 9.00 TFO -0.01									
5,312.00	90.43	135.24	4,689.00	734.61	730.60	113.49	9.00	9.00	0.00
7"									
5,312.32	90.46	135.24	4,689.00	734.38	730.82	113.81	9.00	9.00	0.00
POE at 90.46 Inc 135.24 Deg									
5,500.00	90.46	135.24	4,687.49	601.13	862.98	300.21	0.00	0.00	0.00
6,000.00	90.46	135.24	4,683.48	246.14	1,215.06	796.79	0.00	0.00	0.00
6,500.00	90.46	135.24	4,679.47	-108.86	1,567.15	1,293.38	0.00	0.00	0.00
7,000.00	90.46	135.24	4,675.46	-463.85	1,919.23	1,789.97	0.00	0.00	0.00
7,500.00	90.46	135.24	4,671.45	-818.85	2,271.31	2,286.56	0.00	0.00	0.00
8,000.00	90.46	135.24	4,667.44	-1,173.84	2,623.39	2,783.15	0.00	0.00	0.00
8,500.00	90.46	135.24	4,663.43	-1,528.84	2,975.48	3,279.73	0.00	0.00	0.00
9,000.00	90.46	135.24	4,659.42	-1,883.83	3,327.56	3,776.32	0.00	0.00	0.00
9,500.00	90.46	135.24	4,655.41	-2,238.83	3,679.64	4,272.91	0.00	0.00	0.00
10,000.00	90.46	135.24	4,651.40	-2,593.82	4,031.73	4,769.50	0.00	0.00	0.00
10,500.00	90.46	135.24	4,647.39	-2,948.82	4,383.81	5,266.09	0.00	0.00	0.00
11,000.00	90.46	135.24	4,643.38	-3,303.81	4,735.89	5,762.67	0.00	0.00	0.00
11,500.00	90.46	135.24	4,639.36	-3,658.81	5,087.98	6,259.26	0.00	0.00	0.00
12,000.00	90.46	135.24	4,635.35	-4,013.80	5,440.06	6,755.85	0.00	0.00	0.00
12,500.00	90.46	135.24	4,631.34	-4,368.80	5,792.14	7,252.44	0.00	0.00	0.00
13,000.00	90.46	135.24	4,627.33	-4,723.79	6,144.23	7,749.03	0.00	0.00	0.00
13,500.00	90.46	135.24	4,623.32	-5,078.79	6,496.31	8,245.61	0.00	0.00	0.00
14,000.00	90.46	135.24	4,619.31	-5,433.78	6,848.39	8,742.20	0.00	0.00	0.00
14,163.27	90.46	135.24	4,618.00	-5,549.70	6,963.37	8,904.36	0.00	0.00	0.00
TD at 14163.27									

WPX
Survey Report

Company:	WPX Energy	Local Co-ordinate Reference:	Well W Lybrook UT #759H (A6) - Slot A6
Project:	T23N R9W	TVD Reference:	GL @ 6748.00usft (Original Well Elev)
Site:	2309-23M WLU	MD Reference:	GL @ 6748.00usft (Original Well Elev)
Well:	W Lybrook UT #759H	North Reference:	True
Wellbore:	Wellbore #1	Survey Calculation Method:	Minimum Curvature
Design:	Design #1 11Jan16 sam	Database:	COMPASS

Design Targets										
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (bearing)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude	
Start 60 Tan #759H - plan hits target center - Point	0.00	0.00	4,573.73	1,000.91	466.49	1,895,521.76	520,813.43	36.209541	-107.762782	
End 60 Tan #759H - plan hits target center - Point	0.00	0.00	4,603.73	964.01	503.08	1,895,484.89	520,850.05	36.209439	-107.762658	
BHL #759H - plan hits target center - Point	0.00	0.00	4,618.00	-5,549.70	6,963.37	1,888,975.77	527,314.96	36.191543	-107.740765	
POE #759H - plan hits target center - Point	0.00	0.00	4,689.00	734.38	730.82	1,895,255.42	521,077.95	36.208809	-107.761886	

Casing Points						
Measured Depth (usft)	Vertical Depth (usft)	Name	Casing Diameter (in)	Hole Diameter (in)		
320.00	320.00	9 5/8"	9.625	12.250		
5,312.00	4,689.00	7"	7.000	8.750		

Plan Annotations					
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment	
		+N/-S (usft)	+E/-W (usft)		
500	500	0	0	Start Build 2.00	
1588	1562	202	27	Hold 21.76 Inclinaton	
4087	3883	1121	148	Start Build DLS 9.00 TFO 134.67	
4914	4574	1001	466	Hold 60.00 Inclinaton	
4974	4604	964	503	Start Build DLS 9.00 TFO 0.00	
5145	4668	852	614	Start DLS 9.00 TFO -0.01	
5312	4689	734	731	POE at 90.46 Inc 135.24 Deg	
14,163	4618	-5550	6963	TD at 14163.27	

Checked By: _____ Approved By: _____ Date: _____

✓ A. Cuttings

1. Drilling operations will utilize a closed-loop system. Drilling of the horizontal laterals will be accomplished with water-based mud. All cuttings will be placed in roll-off bins and hauled to a commercial disposal facility or land farm. WPX will follow Onshore Oil and Gas Order No. 1 regarding the placement, operation, and removal of closed-loop systems. No blow pit will be used.
2. Closed-loop tanks will be adequately sized for containment of all fluids.

B. Drilling Fluids

1. Drilling fluids will be stored onsite in above-ground storage tanks. Upon termination of drilling operations, the drilling fluids will be recycled and transferred to other permitted closed-loop systems or returned to the vendor for reuse, as practical. All residual fluids will be hauled to a commercial disposal facility.

C. Spills

1. Any spills of non-freshwater fluids will be immediately cleaned up and removed to an approved disposal site.

D. Sewage

1. Portable toilets will be provided and maintained during construction, as needed (see Figures 4 and 5 in Appendix B for the location of toilets).

E. Garbage and other water material


1. All garbage and trash will be placed in a metal trash basket. The trash and garbage will be hauled off site and dumped in an approved landfill, as needed.

F. Hazardous Waste

1. No chemicals subject to reporting under Superfund Amendments and Reauthorization Act Title III in an amount equal to or greater than 10,000 pounds will be used, produced, stored, transported, or disposed of annually in association with the drilling, testing, or completing of these wells.
2. No extremely hazardous substances, as defined in 40 CFR 355, in threshold planning quantities will be used, produced, stored, transported, or disposed of annually in association with the drilling, testing, or completing of these wells.
3. All fluids (i.e., scrubber cleaners) used during washing of production equipment will be properly disposed of to avoid ground contamination or hazard to livestock or wildlife.

G. Produced Water:

1. WPX Energy will dispose of produced water from this well at one of the following facilities:
 - a. Lybrook Yard WDW #1, API #30-039-27533, NMOCD permit #SWD-907, operated by Elm Ridge Resources, located in NE ¼, Section 14, Township 23 North, Range 7 West
 - b. Jillson Federal #1, NMOCD order #R-10168, operated by ConocoPhillips, located in NW ¼, Section 8, Township 24 North, Range 3 West
 - c. Basin Disposal, permit #NM-01-005, located in the NW ¼, Section 3, Township 29 North, Range 11 West
 - d. Sunco SWD #001, API #30-045-28653, NMOCD permit SWD-457, operated by Key Energy, located in NW ¼, Section 2, Township 29 North, Range 12 West
2. Water will be hauled by truck. Some produced water may also be used in drilling and completion operations as an alternative disposal method.



3,000 PSI read Crotch system



Directions from the Intersection of US Hwy 550 & US Hwy 64
in Bloomfield, NM to WPX Energy Production, LLC W Lybrook Unit #759H
601' FSL & 628' FWL, Section 23, T23N, R9W, N.M.P.M., San Juan County, NM

Latitude: 36.206804°N Longitude: 107.764976°W Datum: NAD1983

From the intersection of US Hwy 550 & US Hwy 64 in Bloomfield, NM, travel Southerly on US Hwy 550 for 37.8 miles to Mile Marker 113.4;

Go Right (South-westerly) on County Road #7890 for 0.8 miles to fork in roadway;

Go Left (Southerly) remaining on County Road #7890 for 1.3 miles to four-way intersection;

Go Left (South-easterly) remaining on County Road #7890 for 0.6 miles to fork in roadway;

Go Right (South-westerly) remaining on County Road #7890 for 0.5 miles to WPX W Lybrook Unit #720H proposed access on right-hand side of County Road #7890;

Go Right (Westerly) exiting County Road #7890 following along WPX W Lybrook Unit #720H proposed access for 3123.1' to fork in proposed access;

Go Left (Westerly) which is straight, continuing for 4605.4' to staked WPX W Lybrook Unit #759H location.