



NEW MEXICO ENERGY, MINERALS
& NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION
AZTEC DISTRICT OFFICE
1000 RIO BRAZOS ROAD
AZTEC NM 87410
(505) 334-6178 FAX: (505) 334-6170
[http://emmr.state.nm.us/ocd/District III/district.htm](http://emmr.state.nm.us/ocd/District%20III/district.htm)

BRADENHEAD TEST REPORT

(submit 1 copy to above address)

Date of Test 1-12-15 Operator Z. Norvell API #30-045-23618

Property Name Oshes Well No. 1M Location: Unit Section Township Range

Well Status(Shut-In or Producing) Initial PSI: Tubing 135 Intermediate 147 Casing 175 Bradenhead 28

OPEN BRADENHEAD AND INTERMEDIATE TO ATMOSPHERE INDIVIDUALLY FOR 15 MINUTES EACH

Testing	PRESSURE			INTERM		
	BH	Int	Csg	Int	Csg	
TIME						
5 min	0		172			
10 min	0		172			
15 min	0		172			
20 min	0		172			
25 min	0		172			
30 min	0		172			

FLOW CHARACTERISTICS	
BRADENHEAD	INTERMEDIATE
Steady Flow <u>✓</u>	
Surges <u> </u>	
Down to Nothing <u> </u>	
Nothing <u> </u>	
Gas <u>✓</u>	
Gas & Water <u> </u>	
Water <u> </u>	

RECEIVED

FEB 02 2015

NMOCD
DISTRICT III

If bradenhead flowed water, check all of the descriptions that apply below:

CLEAR FRESH SALTY SULFUR BLACK

5 MINUTE SHUT-IN PRESSURE

BRADENHEAD D

INTERMEDIATE N/A

REMARKS:

Draw wellbore diagram

By R. J. Lora
Phonad
(Position)

Witness Mona Tschling

E-mail address

30-045-23618

ENERVEST

Elevation: 5,838' GL +12' KB 5,850'

O'Shea #1M

Location: 1430'FNL, 1750'FEL, Sec 3, TN31N,
R13W, San Juan County, NM
Lease #: 024066 FEE

Surface Casing

OD: 8 5/8"
Wt: 24#
Grade: K-55ST&C
Depth: 288'
Cmt Vol: 200 sks
TOC: surface
Hole: 12 1/4"

Field: La Plata
Zone: Blanco Mesa Verde - Basin Dakota
API #: 30-045-23618
Spud Date: 10-15-1979

Formation Tops

Cliff House:	3810'
Menefee:	3980'
PT Lookout:	4451'
Mancos:	4766'
Gallup:	5907'
Dakota:	6692'

Production Tubing

OD: 2 3/8"
Wt: 4.7#
Grade: J-55
EOT @: 6,749.43'

Tbg : 207 jts. 2 3/8" EUE 8 rd J-55 W/ SN & ST collar.
SN @ 6748.13. EOT @ 6749.43'

Perf : **Mesa Verde Perfs: 4478'-4742'**

Stage Tool @ 4970'
2nd Stg. Cement 265sks.

Perf : **Dakota Perfs: 6706' - 6906'**

Production Casing

OD: 5 1/2"
Wt: 15.5#
Grade: K-55 STC
Depth: 6921'
Cmt Vol: 12 1/2 sks
TOC:
Hole: 7 7/8"

TD: 6928' PBTD: 6909'

Well History: