

State of New Mexico
Energy, Minerals and Natural Resources Department

Susana Martinez
Governor

Ken McQueen
Cabinet Secretary

Matthias Sayer
Deputy Cabinet Secretary

David R. Catanach, Division Director
Oil Conservation Division



New Mexico Oil Conservation Division approval and conditions listed below are made in accordance with OCD Rule 19.15.7.11 and are in addition to the actions approved by BLM on the following 3160-3 APD form.

Operator Signature Date: 11/3/2017

Well information;

Operator WPA, Well Name and Number 10 Lybrook Unit 755H

API# 30-045-35816, Section 14, Township 23 N/S, Range 9 E/W

Conditions of Approval: (See the below checked and handwritten conditions)

- Notify Aztec OCD 24hrs prior to casing & cement.
- Hold C-104 for directional survey & "As Drilled" Plat
- Hold C-104 for NSL, NSP, DHC
- Spacing rule violation. Operator must follow up with change of status notification on other well to be shut in or abandoned
- Regarding the use of a pit, closed loop system or below grade tank, the operator must comply with the following as applicable:
 - A pit requires a complete C-144 be submitted and approved prior to the construction or use of the pit, pursuant to 19.15.17.8.A
 - A closed loop system requires notification prior to use, pursuant to 19.15.17.9.A
 - A below grade tank requires a registration be filed prior to the construction or use of the below grade tank, pursuant to 19.15.17.8.C
- Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
- Submit Gas Capture Plan form prior to spudding or initiating recompletion operations
- Regarding Hydraulic Fracturing, review EPA Underground Injection Control Guidance 84
- Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system.
- Well-bore communication is regulated under 19.15.29 NMAC. This requires well-bore Communication to be reported in accordance with 19.15.29.8.

Charles Linn
NMOCD Approved by Signature

2-10-2017
Date

Lessee WPX
BIA-NAV
note-4/1/16

10400007416
ATS-FOLD-

Form 3160-5
(March 2012)

NOS: _____
APDP: _____
MP: _____
SMA: BIA-NAV
BOND: BIA-NAV
CA/PA: NMMN135216A

FORM APPROVED
OMB No. 1004-0137
Expires October 31, 2014

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NOG14031948
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/> Single Zone <input checked="" type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name EASTERN NAVAJO
2. Name of Operator WPX ENERGY LLC		7. If Unit or CA Agreement, Name and No. INITIAL MANCOS PA / NMMN135216A
3a. Address 720 S Main Aztec NM 87410		8. Lease Name and Well No. W LYBROOK UT 755H
3b. Phone No. (include area code) (505)333-1822		9. API Well No. 30-045-35816
4. Location of Well (Report location clearly and in accordance with any State requirements.) At surface: NESE / 1867 FSL / 674 FEL / LAT 36.224787 / LONG -107.751536 At proposed prod. zone: NENE / 697 FNL / 330 FEL / LAT 36.203148 / LONG -107.732647		10. Field and Pool, or Exploratory LYBROOK MANCOS W / LYBROOK MA
14. Distance in miles and direction from nearest town or post office* 37.8 miles		11. Sec., T. R. M. or Blk. and Survey or Area SEC 14 / T23N / R9W / NMP
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 20 feet	16. No. of acres in lease 160	12. County or Parish SAN JUAN
17. Spacing Unit dedicated to this well 440	18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 674 feet	13. State NM
19. Proposed Depth 4679 feet / 14812 feet	20. BLM/BIA Bond No. on file IND: B001576	OIL CONS. DIV DIST. 3 JAN 31 2017
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 6719 feet	22. Approximate date work will start* 12/01/2016	23. Estimated duration 30 days
24. Attachments		

KP

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, must be attached to this form:

- Well plat certified by a registered surveyor.
- A Drilling Plan.
- A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office).
- Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
- Operator certification
- Such other site specific information and/or plans as may be required by the BLM.

25. Signature (Electronic Submission)	Name (Printed/Typed) Lacey Granillo / Ph: (505)333-1816	Date 11/03/2016
Title Permitting Tech III		
Approved by (Signature) 	Name (Printed/Typed)	Date 1/27/17
Title AFM	Office FARMINGTON	

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

*(Instructions on page 2)

DRILLING OPERATIONS
AUTHORIZATIONS ARE SUBJECT TO
COMPLIANCE WITH ATTACHED
"GENERAL REQUIREMENTS"

BLM'S APPROVAL OR ACCEPTANCE OF THIS
ACTION DOES NOT RELIEVE THE LESSEE AND
OPERATOR FROM OBTAINING ANY OTHER
AUTHORIZATION REQUIRED FOR OPERATIONS
ON FEDERAL AND INDIAN LANDS

This action is subject to technical
and procedural review pursuant to
43 CFR 3165.3 and appeal
pursuant to 43 CFR 3165.4

NMOCDV

WPX Energy

Operations Plan

(Note: This procedure will be adjusted onsite based upon actual conditions)

Date:	November 3, 2016	Field:	Lybrook Mancos W
Well Name:	W Lybrook Unit 755H	Surface:	
SH Location:	NESE Sec 14 23N-09W	Elevation:	6719' GR
BH Location:	NENE Sec 25 23N-09W	Minerals:	

Measured Depth: 14,811.52'

I. GEOLOGY

Surface formation - NACIMIENTO

A. FORMATION TOPS: (GR)

NAME	MD	TVD	NAME	MD	TVD
OJO ALAMO	388.00	388.00	POINT LOOKOUT	3,726.00	3,455.00
KIRTLAND	550.00	550.00	MANCOS	3,925.00	3,630.00
PICTURED CLIFFS	1,123.00	1,118.00	GALLUP	4,309.00	3,969.00
LEWIS	1,245.00	1,237.00	KICKOFF POINT	4,299.34	3,960.46
CHACRA	1,436.00	1,419.00	TOP TARGET	5,259.00	4,679.00
CLIFF HOUSE	2,673.00	2,526.00	LANDING POINT	5,540.31	4,738.58
MENELEE	2,692.00	2,543.00	BASE TARGET	5,540.31	4,738.58
			TD	14,811.52	4,679.00

B. MUD LOGGING PROGRAM:

Mudlogger on location from surface csg to TD.

C. LOGGING PROGRAM:

LWD GR from surface casing to TD.

D. NATURAL GAUGES:

Gauge any noticeable increases in gas flow. Record all gauges in Tour book and on morning reports.

II. DRILLING

A. MUD PROGRAM:

LSND mud (WBM) will be used to drill the 12-1/4" Surface hole, the 8 3/4" Directional Vertical hole, and the curve portion of the wellbore. A LSND (WBM) or (OBM) will be used to drill the lateral portion of well. Treat for lost circulation as necessary. Obtain 100% returns prior to cementing. Notify Engineering of any mud losses.

B. BOP TESTING:

While drill pipe is in use, the pipe rams and the blind rams will be function tested once each trip. The BOPE will be tested to 2,000 psi (High) for 10 minutes and the annular tested to 1,500 psi for 10 minutes. Pressure test surface casing to 1,500 psi for 30 minutes and intermediate casing to 1,500 psi for 30 minutes. Utilize a BOPE Testing Unit with a recording chart and appropriate test plug for testing. All tests and inspections will be recorded in the tour book as to time and results.

III. MATERIALS

A. CASING PROGRAM:

CASING TYPE	OH SIZE (IN)	DEPTH (MD)	CSG SIZE	WEIGHT	GRADE	CONN
SURFACE	12.25"	320.00'	9.625"	36 LBS	J-55 or equiv	STC
INTERMEDIATE	8.75"	5,540.31'	7"	23 LBS	J-55 or equiv	LTC
PRODUCTION	6.125"	5390.31' - 14,811.52'	4.5"	11.6 LBS	P-110 or equiv	LTC
TIE BACK	6.125"	Surf. - 5390.31'	4.5"	11.6 LBS	P-110 or equiv	LTC

B. FLOAT EQUIPMENT:

1. SURFACE CASING:

9-5/8" notched regular pattern guide shoe. Run (1) standard centralizer on each of the bottom (4) joints of Surface Casing.

2. INTERMEDIATE CASING:

7" cement nose guide shoe with a self-fill insert float. Place float collar one joint above the shoe. Install (1) centralizer on each of the bottom (3) joints and one standard centralizer every (3) joints to 2,500 ft. Run (1) centralizer at 2,500 ft., 2,300ft., 2,000ft., 1,500 ft., and 1,000 ft. If losses are encountered during the drilling of the intermediate section a DV tool will be utilized and a 2 stage cement job may be planned to ensure cement circ back to surface. The DV tool will be placed 100' above the top of the Chacra formation. If cement is circulated back to surface on the first stage, a cancelation device will be dropped to shift the dv tool closed and the 2nd stage cement job will be aborted at that time, if no cement is seen at surface on the 1st stage the stage tool will be opened and a 2nd stage cement job will be pumped.

3. PRODUCTION LINER:

Run 4-1/2" Liner with cement nose guide Float Shoe + 2jts. of 4-1/2" casing + Landing Collar + 4-1/2" pup joint + 1 RSI (Sliding Sleeve) positioned inside the 330ft Hard line. Centralizer program will be determined by Wellbore condition and when Lateral is evaluated by Geoscientists and Reservoir Engineers. Set seals on Liner Hanger. Test TOL to 1500 psi for 15 minutes.

C. CEMENT:

(Note: Volumes may be adjusted onsite due to actual conditions)

1. Surface:

5 bbl Fresh Water Spacer, 100 sx (160 cu.ft.) of 14.5 ppg Type I-II (Neat G) + 20% Fly Ash cement w/ 7.41 gal/sack mix water ratio @ 1.61 cu ft/sx yield. Calculated @ volume + 50% excess. WOC 12 hours. Test csg to 600psi. Total Volume: (160 cu-ft/100 sx/ Bbls).TOC at Surface.

2. Intermediate:

Spacer #1: 20 bbl (112 cuft) Chemwash. Lead Cement: 104 bbls, 297 sks, (585 cuft), 12.3 ppg @ 1.97 cuft/sk yield. Tail Cement: 59 bbls, 254 sks, (331 cuft), 13.5 ppg @ 1.3 cuft/sk yield. Displacement: Displace w/ +/- 218 bbl Drilling mud or water. Total Cement: 163 bbls, 552 sks, (916 cuft)

3. Prod Liner:

Spacer #1: 10 bbl (56 cu-ft) Water Spacer. Spacer #2: 40 bbl 9.5 ppg (224.6 cu-ft) Toned Spacer III. Spacer #3: 10 bbl Water Spacer. Lead Cement: Extencem™ System. Yield 1.36 cuft/sk 13.3 ppg (923 sx /1256 cuft /224 bbls). Tail Spacer: 20 BBL of MMCR. Displacement: Displace w/ +/-202bbl Fr Water. Total Cement (923 sx /1256bbls).

D. COMPLETION:

Run CCL for perforating

A. PRESSURE TEST:

1. Pressure test 4-1/2" casing to 4500 psi max, hold at 1500 psi for 30 minutes. Increase pressure to Open RSI sleeves.

B. STIMULATION:

1. Stimulate with approximately 2,805,000# 20/40 mesh sand and 340,000# 16/30 mesh sand in 619,113 gallons water with 42,696 mscf N2 for 17 stages.
2. Isolate stages with flow through frac plug.
3. Drill out frac plugs and flowback lateral.

C. RUNNING TUBING:

1. Production Tubing: Run 2-7/8", 6.5#, J-55, EUE tubing with a SN on top of bottom joint. Land tubing near Top of Liner.

If this horizontal well is drilled past the applicable setbacks, an unorthodox location application is not required because the completed interval in this well, as defined by 19.15.16.7 B(1) NMAC, will be entirely within the applicable setbacks. This approach complies with all applicable rules, including 19.15.16.14 A(3) NMAC, 19.15.16.14 B(2) NMAC, 19.15.16.15 B(2) NMAC, and 19.15.16.15. B(4) NMAC.

NOTES:





A 4-1/2" 11.6# P-110 Liner will be run to TD and landed +/- 150 ft. into the 7" 23# J-55 Intermediate casing with a Liner Hanger and pack-off assembly then cemented to top of liner hanger.

After cementing and TOL clean up operations are complete, the TOL will be tested to 1500 psi (per BLM).



Well Name: W Lybrook UT #755H
 Surface Location: 2309-141 WLU
 NAD 1927 (NADCON CONUS), US State Plane 1927 (Exact solution) New Mexico West 3003
 Ground Elevation: 6719.00
 GL @ 6719.00usft (Original Well Elev)

+N/-S +E/-W Northing Easting Latitude Longitude Slot
 0.00 0.00 1901069.64 524307.45 36.224774 -107.750922 A3



DESIGN TARGET DETAILS								
Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude	Shape
Start 60 Tan #755H	4603.30	-1002.90	-1243.23	1900065.68	523065.07	36.222019	-107.755137	Point
End 60 Tan #755H	4653.30	-1064.39	-1182.25	1900004.25	523126.11	36.221850	-107.754930	Point
POE #755H	4738.58	-1293.32	-955.24	1899775.51	523353.31	36.221221	-107.754160	Point
BHL #755H	4679.00	-7876.57	5572.60	1893197.81	529886.74	36.203134	-107.732034	Point

ANNOTATIONS									
TVD	MD	Inc	Azi	+N/-S	+E/-W	V Sect	Departure	Annotation	
500.00	500.00	0.00	0.00	0.00	0.00	0.00	0.00	Start Build 2.00	
1851.58	1907.53	28.15	244.85	-144.00	-306.76	-59.61	338.88	Hold 28.15 Inclination	
3960.46	4299.34	28.15	244.85	-623.53	-1328.24	-258.12	1467.31	Start Build DLS 9.00 TFO -121.10	
4603.30	5102.89	60.00	135.24	-1002.90	-1243.23	100.68	1923.69	Hold 60.00 Inclination	
4653.30	5202.89	60.00	135.24	-1064.39	-1182.25	186.10	2010.29	Start Build DLS 9.00 TFO 0.00	
4716.59	5368.36	74.89	135.24	-1172.60	-1074.95	336.40	2162.68	Start DLS 9.00 TFO 0.01	
4738.58	5540.31	90.37	135.24	-1293.32	-955.24	504.09	2332.69	POE at 90.37 Inc 135.24 Deg	
4679.00	14811.52	90.37	135.24	-7876.57	5572.60	9648.53	11603.71	TD at 14811.52	

WPX Energy

T23N R9W

2309-14I WLU

W Lybrook UT #755H - Slot A3

Wellbore #1

Plan: Design #1 28Sept16 sam

Standard Planning Report

28 September, 2016

WPX Energy is a registered trademark of WPX Energy LLC. All other trademarks are the property of their respective owners. © 2016 WPX Energy LLC. All rights reserved.



WPX
Planning Report

Database:	COMPASS	Local Co-ordinate Reference:	Well W Lybrook UT #755H (A3) - Slot A3
Company:	WPX Energy	TVD Reference:	GL @ 6719.00usft (Original Well Elev)
Project:	T23N R9W	MD Reference:	GL @ 6719.00usft (Original Well Elev)
Site:	2309-14I WLU	North Reference:	True
Well:	W Lybrook UT #755H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1 28Sept16 sam		

Project	T23N R9W		
Map System:	US State Plane 1927 (Exact solution)	System Datum:	Mean Sea Level
Geo Datum:	NAD 1927 (NADCON CONUS)		
Map Zone:	New Mexico West 3003		

Site	2309-14I WLU				
Site Position:		Northing:	1,901,091.09 usft	Latitude:	36.224833
From:	Map	Easting:	524,273.81 usft	Longitude:	-107.751036
Position Uncertainty:	0.00 usft	Slot Radius:	13.200 in	Grid Convergence:	0.05 °

Well	W Lybrook UT #755H - Slot A3					
Well Position	+N/-S	-21.48 usft	Northing:	1,901,069.64 usft	Latitude:	36.224774
	+E/-W	33.62 usft	Easting:	524,307.45 usft	Longitude:	-107.750922
Position Uncertainty		0.00 usft	Wellhead Elevation:	0.00 usft	Ground Level:	6,719.00 usft

Wellbore	Wellbore #1				
Magnetics	Model Name	Sample Date	Declination	Dip Angle	Field Strength
	IGRF200510	12/31/2009	(°)	(°)	(nT)
			9.99	63.07	50,612

Design	Design #1 28Sept16 sam			
Audit Notes:				
Version:	Phase:	PLAN	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD)	+N/-S	+E/-W	Direction
	(usft)	(usft)	(usft)	(bearing)
	0.00	0.00	0.00	144.72

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (bearing)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
500.00	0.00	0.00	500.00	0.00	0.00	0.00	0.00	0.00	0.00	
1,907.53	28.15	244.85	1,851.59	-144.00	-306.76	2.00	2.00	0.00	244.85	
4,299.34	28.15	244.85	3,960.46	-623.53	-1,328.24	0.00	0.00	0.00	0.00	
5,102.89	60.00	135.24	4,603.30	-1,002.90	-1,243.23	9.00	3.96	-13.64	-121.10	Start 60 Tan #755H
5,202.89	60.00	135.24	4,653.30	-1,064.39	-1,182.25	0.00	0.00	0.00	0.00	End 60 Tan #755H
5,368.36	74.89	135.24	4,716.59	-1,172.60	-1,074.95	9.00	9.00	0.00	0.00	
5,540.31	90.37	135.24	4,738.58	-1,293.32	-955.24	9.00	9.00	0.00	0.01	POE #755H
14,811.52	90.37	135.24	4,679.00	-7,876.57	5,572.60	0.00	0.00	0.00	0.00	BHL #755H

WPX
Planning Report

Database:	COMPASS	Local Co-ordinate Reference:	Well W Lybrook UT #755H (A3) - Slot A3
Company:	WPX Energy	TVD Reference:	GL @ 6719.00usft (Original Well Elev)
Project:	T23N R9W	MD Reference:	GL @ 6719.00usft (Original Well Elev)
Site:	2309-14I WLU	North Reference:	True
Well:	W Lybrook UT #755H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1 28Sept16 sam		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (bearing)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
320.00	0.00	0.00	320.00	0.00	0.00	0.00	0.00	0.00	0.00
9 5/8"									
500.00	0.00	0.00	500.00	0.00	0.00	0.00	0.00	0.00	0.00
Start Build 2.00									
1,000.00	10.00	244.85	997.47	-18.49	-39.40	-7.66	2.00	2.00	0.00
1,500.00	20.00	244.85	1,479.82	-73.42	-156.39	-30.39	2.00	2.00	0.00
1,907.53	28.15	244.85	1,851.59	-144.00	-306.76	-59.61	2.00	2.00	0.00
Hold 28.15 Inclination									
2,000.00	28.15	244.85	1,933.11	-182.54	-346.25	-67.29	0.00	0.00	0.00
2,500.00	28.15	244.85	2,373.97	-262.78	-559.78	-108.79	0.00	0.00	0.00
3,000.00	28.15	244.85	2,814.82	-363.03	-773.32	-150.28	0.00	0.00	0.00
3,500.00	28.15	244.85	3,255.68	-463.27	-986.86	-191.78	0.00	0.00	0.00
4,000.00	28.15	244.85	3,696.53	-563.51	-1,200.40	-233.28	0.00	0.00	0.00
4,299.34	28.15	244.85	3,960.46	-623.53	-1,328.24	-258.12	0.00	0.00	0.00
Start Build DLS 9.00 TFO -121.10									
4,500.00	23.96	204.04	4,142.12	-681.33	-1,388.18	-245.55	9.00	-2.09	-20.34
5,000.00	51.92	140.71	4,545.72	-939.79	-1,300.37	16.15	9.00	5.59	-12.67
5,102.89	60.00	135.24	4,603.30	-1,002.90	-1,243.23	100.68	9.00	7.85	-5.32
Hold 60.00 Inclination									
5,202.89	60.00	135.24	4,653.30	-1,064.39	-1,182.25	186.10	0.00	0.00	0.00
Start Build DLS 9.00 TFO 0.00									
5,368.36	74.89	135.24	4,716.59	-1,172.60	-1,074.95	336.40	9.00	9.00	0.00
Start DLS 9.00 TFO 0.01									
5,500.00	86.74	135.24	4,737.56	-1,264.71	-983.61	464.35	9.00	9.00	0.00
5,540.00	90.34	135.24	4,738.58	-1,293.10	-955.46	503.79	9.00	9.00	0.00
7"									
5,540.31	90.37	135.24	4,738.58	-1,293.32	-955.24	504.09	9.00	9.00	0.00
POE at 90.37 Inc 135.24 Deg									
6,000.00	90.37	135.24	4,735.63	-1,619.73	-631.57	957.50	0.00	0.00	0.00
6,500.00	90.37	135.24	4,732.41	-1,974.77	-279.53	1,450.66	0.00	0.00	0.00
7,000.00	90.37	135.24	4,729.20	-2,329.81	72.52	1,943.82	0.00	0.00	0.00
7,500.00	90.37	135.24	4,725.99	-2,684.84	424.57	2,436.99	0.00	0.00	0.00
8,000.00	90.37	135.24	4,722.77	-3,039.88	776.62	2,930.15	0.00	0.00	0.00
8,500.00	90.37	135.24	4,719.56	-3,394.92	1,128.67	3,423.31	0.00	0.00	0.00
9,000.00	90.37	135.24	4,716.35	-3,749.96	1,480.72	3,916.47	0.00	0.00	0.00
9,500.00	90.37	135.24	4,713.13	-4,104.99	1,832.77	4,409.64	0.00	0.00	0.00
10,000.00	90.37	135.24	4,709.92	-4,460.03	2,184.82	4,902.80	0.00	0.00	0.00
10,500.00	90.37	135.24	4,706.71	-4,815.07	2,536.86	5,395.96	0.00	0.00	0.00
11,000.00	90.37	135.24	4,703.49	-5,170.11	2,888.91	5,889.13	0.00	0.00	0.00
11,500.00	90.37	135.24	4,700.28	-5,525.14	3,240.96	6,382.29	0.00	0.00	0.00
12,000.00	90.37	135.24	4,697.07	-5,880.18	3,593.01	6,875.45	0.00	0.00	0.00
12,500.00	90.37	135.24	4,693.85	-6,235.22	3,945.06	7,368.62	0.00	0.00	0.00
13,000.00	90.37	135.24	4,690.64	-6,590.25	4,297.11	7,861.78	0.00	0.00	0.00
13,500.00	90.37	135.24	4,687.43	-6,945.29	4,649.16	8,354.94	0.00	0.00	0.00
14,000.00	90.37	135.24	4,684.22	-7,300.33	5,001.21	8,848.11	0.00	0.00	0.00
14,500.00	90.37	135.24	4,681.00	-7,655.37	5,353.25	9,341.27	0.00	0.00	0.00
14,811.52	90.37	135.24	4,679.00	-7,876.57	5,572.60	9,648.53	0.00	0.00	0.00
TD at 14811.52									

WPX
Planning Report

Database:	COMPASS	Local Co-ordinate Reference:	Well W Lybrook UT #755H (A3) - Slot A3
Company:	WPX Energy	TVD Reference:	GL @ 6719.00usft (Original Well Elev)
Project:	T23N R9W	MD Reference:	GL @ 6719.00usft (Original Well Elev)
Site:	2309-141 WLU	North Reference:	True
Well:	W Lybrook UT #755H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1 28Sept16 sam		

Design Targets									
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (bearing)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
Start 60 Tan #755H - plan hits target center - Point	0.00	0.00	4,603.30	-1,002.90	-1,243.23	1,900,065.69	523,065.07	36.222019	-107.755137
End 60 Tan #755H - plan hits target center - Point	0.00	0.00	4,653.30	-1,064.39	-1,182.25	1,900,004.25	523,126.11	36.221850	-107.754930
BHL #755H - plan hits target center - Point	0.00	0.00	4,679.00	-7,876.57	5,572.60	1,893,197.81	529,886.74	36.203134	-107.732034
POE #755H - plan hits target center - Point	0.00	0.00	4,738.58	-1,293.32	-955.24	1,899,775.51	523,353.31	36.221221	-107.754161

Casing Points					
Measured Depth (usft)	Vertical Depth (usft)	Name	Casing Diameter (in)	Hole Diameter (in)	
320.00	320.00	9 5/8"	9.625	12.250	
5,540.00	4,738.58	7"	7.000	8.750	

Plan Annotations					
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment	
		+N/-S (usft)	+E/-W (usft)		
500.00	500.00	0.00	0.00	Start Build 2.00	
1,907.53	1,851.59	-144.00	-306.76	Hold 28.15 Inclination	
4,299.34	3,960.46	-623.53	-1,328.24	Start Build DLS 9.00 TFO -121.10	
5,102.89	4,603.30	-1,002.90	-1,243.23	Hold 60.00 Inclination	
5,202.89	4,653.30	-1,064.39	-1,182.25	Start Build DLS 9.00 TFO 0.00	
5,368.36	4,716.59	-1,172.60	-1,074.95	Start DLS 9.00 TFO 0.01	
5,540.31	4,738.58	-1,293.32	-955.24	POE at 90.37 Inc 135.24 Deg	
14,811.52	4,679.00	-7,876.57	5,572.60	TD at 14811.52	

(Lat/Long) is recorded and full drill log report is completed and filed with WPX. The bed will not be energized for a minimum of 45 days.

After the completion phases and pipeline installation, portions of the project area not needed for operation will be reclaimed. When the wells are plugged, final reclamation will occur within the remainder of the project area. Reclamation is described in detail in the Surface Use Reclamation Plan (Appendix A).

7. METHODS FOR HANDLING WASTE

A. Cuttings

- 1 Drilling operations will utilize a closed-loop system. Drilling of the horizontal laterals will be accomplished with water-based mud. All cuttings will be placed in roll-off bins and hauled to a commercial disposal facility or land farm. WPX will follow Onshore Oil and Gas Order No. 1 regarding the placement, operation, and removal of closed-loop systems. No blow pit will be used.
- 2 Closed-loop tanks will be adequately sized for containment of all fluids.

B. Drilling Fluids

- 1 Drilling fluids will be stored onsite in above-ground storage tanks. Upon termination of drilling operations, the drilling fluids will be recycled and transferred to other permitted closed-loop systems or returned to the vendor for reuse, as practical. All residual fluids will be hauled to a commercial disposal facility.

C. Spills

- 1 Any spills of non-freshwater fluids will be immediately cleaned up and removed to an approved disposal site.

D. Sewage

- 1 Portable toilets will be provided and maintained during construction, as needed (see Figures 3, 4, 6 and 7 in Appendix B for the location of toilets per wellpad).

E. Garbage and other waste material


- 1 All garbage and trash will be placed in a metal trash basket. The trash and garbage will be hauled off site and dumped in an approved landfill, as needed.


F. Hazardous Waste

- 1 No chemicals subject to reporting under Superfund Amendments and Reauthorization Act Title III in an amount equal to or greater than 10,000 pounds will be used, produced, stored, transported, or disposed of annually in association with the drilling, testing, or completing of these wells.
- 2 No extremely hazardous substances, as defined in 40 CFR 355, in threshold planning quantities will be used, produced, stored, transported, or disposed of annually in association with the drilling, testing, or completing of these wells.
- 3 All fluids (i.e., scrubber cleaners) used during washing of production equipment will be properly disposed of to avoid ground contamination or hazard to livestock or wildlife.

G. Produced Water:

- 1 WPX Energy will dispose of produced water from this well at one of the following facilities:
 - Lybrook Yard WDW #1, API #30-039-27533, NMOCD permit #SWD-907, operated by Elm Ridge Resources, located in NE ¼, Section 14, Township 23 North, Range 7 West
 - Jillson Federal #1, NMOCD order #R-10168, operated by ConocoPhillips, located in NW ¼, Section 8, Township 24 North, Range 3 West
 - Basin Disposal, permit #NM-01-005, located in the NW ¼, Section 3, Township 29 North, Range 11 West
 - Sunco SWD #001, API #30-045-28653, NMOCD permit SWD-457, operated by Key Energy, located in NW ¼, Section 2, Township 29 North, Range 12 West
- 2 Water will be hauled by truck. Some produced water may also be used in drilling and completion operations as an alternative disposal method.





Directions from the Intersection of US Hwy 550 & US Hwy 64
in Bloomfield, NM to WPX Energy Production, LLC W Lybrook Unit #755H
1867' FSL & 674' FEL, Section 14, T23N, R9W, N.M.P.M., San Juan County, NM

Latitude: 36.224787°N Longitude: 107.751536°W Datum: NAD1983

From the intersection of US Hwy 550 & US Hwy 64 in Bloomfield, NM, travel Southerly on US Hwy 550 for 37.8 miles to Mile Marker 113.4:

Go Right (South-westerly) on County Road #7890 for 0.8 miles to fork in roadway:

Go Left (Southerly) remaining on County Road #7890 for 1.3 miles to begin WPX W Lybrook Unit #710H proposed access on right-hand side:

Go Right (North-westerly) along WPX W Lybrook Unit #710H proposed access for 3412.5' to fork in proposed access:

Go Left (South-westerly) continuing for 1344.8' to staked WPX W Lybrook Unit #755H location.