

State of New Mexico
Energy, Minerals and Natural Resources Department

Susana Martinez
Governor

Ken McQueen
Cabinet Secretary

Matthias Sayer
Deputy Cabinet Secretary

David R. Catanach, Division Director
Oil Conservation Division



New Mexico Oil Conservation Division approval and conditions listed below are made in accordance with OCD Rule 19.15.7.11 and are in addition to the actions approved by BLM on the following 3160-3 APD form.

Operator Signature Date: 6/29/2016

Well information;

Operator WPA, Well Name and Number Rodeo Unit #5004

API# 30-045-35796 Section 18, Township 23 N/S, Range 8 E/W

Conditions of Approval: (See the below checked and handwritten conditions)

- Notify Aztec OCD 24hrs prior to casing & cement.
- Hold C-104 for directional survey & "As Drilled" Plat
- Hold C-104 for NSL, NSP, DHC
- Spacing rule violation. Operator must follow up with change of status notification on other well to be shut in or abandoned
- Regarding the use of a pit, closed loop system or below grade tank, the operator must comply with the following as applicable:
 - A pit requires a complete C-144 be submitted and approved prior to the construction or use of the pit, pursuant to 19.15.17.8.A
 - A closed loop system requires notification prior to use, pursuant to 19.15.17.9.A
 - A below grade tank requires a registration be filed prior to the construction or use of the below grade tank, pursuant to 19.15.17.8.C
- Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
- Submit Gas Capture Plan form prior to spudding or initiating recompletion operations
- Regarding Hydraulic Fracturing, review EPA Underground Injection Control Guidance 84
- Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system.
- Well-bore communication is regulated under 19.15.29 NMAC. This requires well-bore Communication to be reported in accordance with 19.15.29.8.

Charles [Signature]
NMOCD Approved by Signature

5.26.17
Date

- APD Held for Unit approval by all agencies

Onsite 15-16
 Porter
 CK# 00011033
 TR# 3743990
 Form 3160-3
 8-25-16 (March 2012)

NOS 6-26-16
 Bond: 2100200
 Unit
 SMC/CR

ATS-FOI-16-157
 AFMSS-1040000 4803

Duga Prod Corp
 W 2NE, NW
 Requires
 1st Prod

UNITED STATES
 DEPARTMENT OF THE INTERIOR
 BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

FORM APPROVED
 OMB No. 1004-0137
 Expires October 31, 2014

5. Lease Serial No.
 NMNM136159

6. If Indian, Allottee or Tribe Name

7. If Unit or CA Agreement, Name and No.
 NMNM-136328A

8. Lease Name and Well No.
 RODEO UT 500H

9. API Well No.
 30-045-35796

10. Field and Pool, or Exploratory
 BASIN MANCOS

11. Sec., T. R. M. or Blk. and Survey or Area
 SEC 18 / T23N / R8W / NMP

12. County or Parish
 SAN JUAN

13. State
 NM

1a. Type of work: DRILL REENTER

1b. Type of Well: Oil Well Gas Well Other Single Zone Multiple Zone

2. Name of Operator
 WPX ENERGY LLC

3a. Address
 720 S MAIN AZTEC NM 87410

3b. Phone No. (include area code)
 (505)333-1822

4. Location of Well (Report location clearly and in accordance with any State requirements.)
 At surface LOT 0 / 271 FSL / 410 FEL / LAT 36.220413 / LONG -107.715566
 At proposed prod. zone LOT 0 / 718 FSL / 330 FEL / LAT 36.207071 / LONG -107.696803

14. Distance in miles and direction from nearest town or post office*

15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any)
 20 feet

16. No. of acres in lease
 400

17. Spacing Unit dedicated to this well
 640

18. Distance from proposed location* to nearest well, drilling, completed, 271 feet applied for, on this lease, ft.

19. Proposed Depth
 4941 feet / 11518 feet

20. BLM/BIA Bond No. on file
 FED: UTB000178

21. Elevations (Show whether DF, KDB, RT, GL, etc.)
 6896 feet

22. Approximate date work will start*
 10/01/2016

23. Estimated duration
 30 days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, must be attached to this form:

- Well plat certified by a registered surveyor.
- A Drilling Plan.
- A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office).
- Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
- Operator certification
- Such other site specific information and/or plans as may be required by the BLM.

25. Signature (Electronic Submission) Name (Printed/Typed) Date
 Lacey Granillo / Ph: (505)333-1816 08/29/2016

Title Permitting Tech III

Approved by (Signature) Name (Printed/Typed) Date
 AFM FARMINGTON 8/23/17

Title AFM

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

*(Instructions on page 2)

DRILLING OPERATIONS AUTHORIZED
 ARE SUBJECT TO COMPLIANCE WITH
 ATTACHED "GENERAL REQUIREMENTS"

This action is subject to
 technical and procedural review
 pursuant to 43 CFR 3165.3 and
 appeal pursuant to 43 CFR 3165.4

BLM'S APPROVAL OR ACCEPTANCE OF THIS
 ACTION DOES NOT RELIEVE THE LESSEE AND
 OPERATOR FROM OBTAINING ANY OTHER
 AUTHORIZATION REQUIRED FOR OPERATIONS
 ON FEDERAL AND INDIAN LANDS

NMOCD AV

District I
1625 N. French Drive, Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II
811 S. First Street, Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720

District III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170

District IV
1220 S. St. Francis Drive, Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department

Form C-102
Revised August 1, 2011

Submit one copy to
Appropriate District Office

OIL CONSERVATION DIVISION
1220 South St. Francis Drive
Santa Fe, NM 87505

AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

| | | | |
|-----------------------------|--|---------------------|----------------------------|
| *API Number 30-045-35796 | | *Pool Code 97232 | *Pool Name BASIN MANCOS |
| *Property Code 317507 | *Property Name RODEO UT | | *Well Number 500H |
| *OGRID No. 120782 | *Operator Name WPX ENERGY PRODUCTION, LLC | | *Elevation 6896' |

¹⁰ Surface Location


| U. or lot no. | Section | Township | Range | Lot Idn | Feet from the | North/South line | Feet from the | East/West line | County |
|---------------|---------|----------|-------|---------|---------------|------------------|---------------|----------------|----------|
| P | 18 | 23N | 8W | | 271 | SOUTH | 410 | EAST | SAN JUAN |

¹¹ Bottom Hole Location If Different From Surface

| U. or lot no. | Section | Township | Range | Lot Idn | Feet from the | North/South line | Feet from the | East/West line | County |
|---------------|---------|----------|-------|---------|---------------|------------------|---------------|----------------|----------|
| P | 20 | 23N | 8W | | 718 | SOUTH | 330 | EAST | SAN JUAN |

| | | | | |
|---|-------------------|-------------------------------|----------------------------------|-------------------------|
| ¹² Dedicated Acres 640.00 | Entire Section 20 | ¹³ Joint or Infill | ¹⁴ Consolidation Code | ¹⁵ Order No. |
|---|-------------------|-------------------------------|----------------------------------|-------------------------|

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



17 OPERATOR CERTIFICATION
I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom-hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

Lacey Granillo 3/7/17
Signature Date
Lacey Granillo
Printed Name
lacey.granillo@wpxenergy.com
E-mail Address

18 SURVEYOR CERTIFICATION
I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Date Revised: OCTOBER 6, 2016
Date of Survey: APRIL 11, 2016

Signature and Seal of Professional Surveyor

JASON C. EDWARDS
NEW MEXICO
REGISTERED PROFESSIONAL SURVEYOR
15269

JASON C. EDWARDS
Certificate Number 15269

WPXENERGY

WPX Energy

Operations Plan

(Note: This procedure will be adjusted onsite based upon actual conditions)

Date: August 22, 2016
Well Name: Rodeo UT 500H
SH Location: SESE Sec 18-23N-08W
BH Location: SESE Sec 20-23N-08W

Field: Basin Mancos
Surface: BLM
Elevation: 6896' GR
Minerals: FED

Measured Depth: 11,517.67'

I. GEOLOGY

Surface formation - NACIMIENTO

A. FORMATION TOPS: (GR)

| NAME | MD | TVD | NAME | MD | TVD |
|-----------------|----------|----------|---------------|-----------|----------|
| OJO ALAMO | 671.00 | 671.00 | POINT LOOKOUT | 3,841.00 | 3,759.00 |
| KIRTLAND | 842.00 | 842.00 | MANCOS | 4,019.00 | 3,931.00 |
| PICTURED CLIFFS | 1,304.00 | 1,303.00 | GALLUP | 4,360.00 | 4,260.00 |
| LEWIS | 1,496.00 | 1,494.00 | KICKOFF POINT | 4,604.30 | 4,495.42 |
| CHACRA | 1,721.00 | 1,713.00 | TOP TARGET | 5,197.00 | 4,941.00 |
| CLIFF HOUSE | 2,862.00 | 2,814.00 | LANDING POINT | 5,583.70 | 5,047.00 |
| MENEFEE | 2,884.00 | 2,836.00 | BASE TARGET | 5,583.70 | 5,047.00 |
| | | | TD | 11,517.67 | 4,941.00 |

B. MUD LOGGING PROGRAM:

Mudlogger on location from surface csg to TD.

C. LOGGING PROGRAM:

LWD GR from surface casing to TD.

D. NATURAL GAUGES:

Gauge any noticeable increases in gas flow. Record all gauges in Tour book and on morning reports.

II. DRILLING

A. MUD PROGRAM:

LSND mud (WBM) will be used to drill the 12-1/4" Surface hole, the 8 3/4" Directional Vertical hole, and the curve portion of the wellbore. A LSND (WBM) or (OBM) will be used to drill the lateral portion of well. Treat for lost circulation as necessary. Obtain 100% returns prior to cementing. Notify Engineering of any mud losses.

B. BOP TESTING:

While drill pipe is in use, the pipe rams and the blind rams will be function tested once each trip. The BOPE will be tested to 2,000 psi (High) for 10 minutes and the annular tested to 1,500 psi for 10 minutes. Pressure test surface casing to 1,500 psi for 30 minutes and intermediate casing to 1,500 psi for 30 minutes. Utilize a BOPE Testing Unit with a recording chart and appropriate test plug for testing. All tests and inspections will be recorded in the tour book as to time and results.

III. MATERIALS

A. CASING PROGRAM:

| CASING TYPE | OH SIZE (IN) | DEPTH (MD) | CSG SIZE | WEIGHT | GRADE | CONN |
|--------------|--------------|----------------------|----------|----------|----------------|------|
| SURFACE | 12.25" | 320.00' | 9.625" | 36 LBS | J-55 or equiv | STC |
| INTERMEDIATE | 8.75" | 5,583.70' | 7" | 23 LBS | J-55 or equiv | LTC |
| PRODUCTION | 6.125" | 5433.7' - 11,517.67' | 4.5" | 11.6 LBS | P-110 or equiv | LTC |
| TIE BACK | 6.125" | Surf. - 5433.7' | 4.5" | 11.6 LBS | P-110 or equiv | LTC |

B. FLOAT EQUIPMENT:

1. SURFACE CASING:

9-5/8" notched regular pattern guide shoe. Run (1) standard centralizer on each of the bottom (4) joints of Surface Casing.

2. INTERMEDIATE CASING:

7" cement nose guide shoe with a self-fill insert float. Place float collar one joint above the shoe. Install (1) centralizer on each of the bottom (3) joints and one standard centralizer every (3) joints to 2,500 ft. Run (1) centralizer at 2,500 ft., 2,300ft., 2,000ft., 1,500 ft., and 1,000 ft. If losses are encountered during the drilling of the intermediate section a DV tool will be utilized and a 2 stage cement job may be planned to ensure cement circ back to surface. The DV tool will be placed 100' above the top of the Chacra formation. If cement is circulated back to surface on the first stage, a cancelation device will be dropped to shift the dv tool closed and the 2nd stage cement job will be aborted at that time, if no cement is seen at surface on the 1st stage the stage tool will be open and a 2nd stage cement job will be pumped.

3. PRODUCTION LINER:

Run 4-1/2" Liner with cement nose guide Float Shoe + 2jts. of 4-1/2" casing + Landing Collar + 4-1/2" pup joint + 1 RSI (Sliding Sleeve) positioned inside the 330ft Hard line. Centralizer program will be determined by Wellbore condition and when Lateral is evaluated by Geoscientists and Reservoir Engineers. Set seals on Liner Hanger. Test TOL to 1500 psi for 15 minutes.

C. CEMENT:

(Note: Volumes may be adjusted onsite due to actual conditions)

1. Surface:

5 bbl Fresh Water Spacer, 100 sx (160 cu.ft.) of 14.5 ppg Type I-II (Neat G) + 20% Fly Ash cement w/ 7.41 gal/sack mix water ratio @ 1.61 cu ft/sx yield. Calculated @ volume + 50% excess. WOC 12 hours. Test csg to 600psi. Total Volume: (160 cu-ft/100 sx/ Bbls). TOC at Surface.

$$100 \times 1.61 = 160 \text{ cu ft}$$

2. Intermediate:

Spacer #1: 20 bbl (112 cuft) Chemwash. Lead Cement: 106 bbls, 301 sks, (593 cuft), 12.3 ppg @ 1.97 cuft/sk yield. Tail Cement: 59 bbls, 254 sks, (331 cuft), 13.5 ppg @ 1.3 cuft/sk yield. Displacement: Displace w/ +/- 220 bbl Drilling mud or water. Total Cement: 164 bbls, 555 sks, (923 cuft)

$$301 \times 1.97 = 593 \text{ cu ft}$$

$$254 \text{ sks} \times 1.3 = 330.2 \text{ cu ft}$$

$$593 + 330.2 = 923.2 \text{ cu ft}$$

3. Prod Liner:

Spacer #1: 10 bbl (56 cu-ft) Water Spacer. Spacer #2: 40 bbl 9.5 ppg (224.6 cu-ft) Tuned Spacer III. Spacer #3: 10 bbl Water Spacer. Lead Cement: Extencem™ System. Yield ~~1.36~~ cuft/sk 13.3 ppg (596 sx / 810 cuft / 144 bbls). Tail Spacer: 20 BBL of MMCR. Displacement: Displace w/ +/-151bbl Fr Water. Total Cement (596 sx / 810bbls).

$$596 \times 1.36 = \underline{\underline{810 \text{ FT}^3}}$$

D. COMPLETION:

Run CCL for perforating

A. PRESSURE TEST:

1. Pressure test 4-1/2" casing to 4500 psi max, hold at 1500 psi for 30 minutes. Increase pressure to Open RSI sleeves.

B. STIMULATION:

1. Stimulate with approximately 2,805,000# 20/40 mesh sand and 340,000# 16/30 mesh sand in 619,113 gallons water with 42,696 mscf N2 for 17 stages.
2. Isolate stages with flow through frac plug.
3. Drill out frac plugs and flowback lateral.

C. RUNNING TUBING:

1. Production Tubing: Run 2-7/8", 6.5#, J-55, EUE tubing with a SN on top of bottom joint. Land tubing near Top of Liner.

If this horizontal well is drilled past the applicable setbacks, an unorthodox location application is not required because the completed interval in this well, as defined by 19.15.16.7 B(1) NMAC, will be entirely within the applicable setbacks. This approach complies with all applicable rules, including 19.15.16.14 A(3) NMAC, 19.15.16.14 B(2) NMAC, 19.15.16.15 B(2) NMAC, and 19.15.16.15. B(4) NMAC.

NOTES:

A 4-1/2" 11.6# P-110 Liner will be run to TD and landed +/- 150 ft. into the 7" 23# J-55 Intermediate casing with a Liner Hanger and pack-off assembly then cemented to top of liner hanger.

After cementing and TOL clean up operations are complete, the TOL will be tested to 1500 psi (per BLM).

WPX Energy

**T23N R8W
2308-18P Rodeo
Rodeo UT #500H**

Wellbore #1

Plan: Design #1 26July16 sam

Standard Planning Report

28 July, 2016

WPX
Planning Report

| | | | |
|------------------|------------------------|-------------------------------------|---------------------------------------|
| Database: | COMPASS | Local Co-ordinate Reference: | Well Rodeo UT #500H |
| Company: | WPX Energy | TVD Reference: | GL @ 6896.00usft (Original Well Elev) |
| Project: | T23N R8W | MD Reference: | GL @ 6896.00usft (Original Well Elev) |
| Site: | 2308-18P Rodeo | North Reference: | True |
| Well: | Rodeo UT #500H | Survey Calculation Method: | Minimum Curvature |
| Wellbore: | Wellbore #1 | | |
| Design: | Design #1 26July16 sam | | |

| | | | |
|--------------------|--------------------------------------|----------------------|----------------|
| Project | T23N R8W | | |
| Map System: | US State Plane 1927 (Exact solution) | System Datum: | Mean Sea Level |
| Geo Datum: | NAD 1927 (NADCON CONUS) | | |
| Map Zone: | New Mexico West 3003 | | |

| | | | | | |
|------------------------------|------------------|---------------------|-------------------|--------------------------|--------|
| Site | 2308-18P Rodeo | | | | |
| Site Position: | Northing: | 1,899,488.44 usft | Latitude: | 36.220400 | |
| From: Map | Easting: | 534,918.26 usft | Longitude: | -107.714954 | |
| Position Uncertainty: | 0.00 usft | Slot Radius: | 13.200 in | Grid Convergence: | 0.07 ° |

| | | | | | | |
|-----------------------------|----------------|-----------|----------------------------|-------------------|----------------------|---------------|
| Well | Rodeo UT #500H | | | | | |
| Well Position | +N/-S | 0.00 usft | Northing: | 1,899,488.44 usft | Latitude: | 36.220400 |
| | +E/-W | 0.00 usft | Easting: | 534,918.26 usft | Longitude: | -107.714954 |
| Position Uncertainty | 0.00 usft | | Wellhead Elevation: | 0.00 usft | Ground Level: | 6,896.00 usft |

| | | | | | |
|------------------|-------------------|--------------------|--------------------|------------------|-----------------------|
| Wellbore | Wellbore #1 | | | | |
| Magnetics | Model Name | Sample Date | Declination | Dip Angle | Field Strength |
| | IGRF2015 | 7/26/2016 | (°) | (°) | (nT) |
| | | | 9.27 | 62.91 | 49,838 |

| | | | | |
|--------------------------|-------------------------|--------------|----------------------|------------------|
| Design | Design #1 26July16 sam | | | |
| Audit Notes: | | | | |
| Version: | Phase: | PLAN | Tie On Depth: | 0.00 |
| Vertical Section: | Depth From (TVD) | +N/-S | +E/-W | Direction |
| | (usft) | (usft) | (usft) | (bearing) |
| | 0.00 | 0.00 | 0.00 | 131.26 |

| Plan Sections | | | | | | | | | | |
|-----------------------|-----------------|-------------------|-----------------------|--------------|--------------|-------------------------|------------------------|-----------------------|---------|--------------------|
| Measured Depth (usft) | Inclination (°) | Azimuth (bearing) | Vertical Depth (usft) | +N/-S (usft) | +E/-W (usft) | Dogleg Rate (°/100usft) | Build Rate (°/100usft) | Turn Rate (°/100usft) | TFO (°) | Target |
| 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | |
| 1,000.00 | 0.00 | 0.00 | 1,000.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | |
| 1,761.92 | 15.24 | 99.70 | 1,752.97 | -16.97 | 99.28 | 2.00 | 2.00 | 0.00 | 99.70 | |
| 4,604.30 | 15.24 | 99.70 | 4,495.42 | -142.81 | 835.69 | 0.00 | 0.00 | 0.00 | 0.00 | |
| 5,139.00 | 60.00 | 135.28 | 4,911.81 | -330.32 | 1,082.55 | 9.00 | 8.37 | 6.65 | 42.59 | Start 60 Tan #500H |
| 5,239.00 | 60.00 | 135.28 | 4,961.81 | -391.86 | 1,143.49 | 0.00 | 0.00 | 0.00 | 0.00 | End 60 Tan #500H |
| 5,407.78 | 75.19 | 135.18 | 5,025.95 | -502.30 | 1,253.07 | 9.00 | 9.00 | -0.06 | -0.39 | |
| 5,583.70 | 91.02 | 135.48 | 5,047.00 | -626.11 | 1,375.46 | 9.00 | 9.00 | 0.17 | 1.12 | POE #500H |
| 11,517.67 | 91.02 | 135.48 | 4,941.00 | -4,856.40 | 5,535.43 | 0.00 | 0.00 | 0.00 | 0.00 | BHL #500H |

WPX
Planning Report

| | | | |
|------------------|------------------------|-------------------------------------|---------------------------------------|
| Database: | COMPASS | Local Co-ordinate Reference: | Well Rodeo UT #500H |
| Company: | WPX Energy | TVD Reference: | GL @ 6896.00usft (Original Well Elev) |
| Project: | T23N R8W | MD Reference: | GL @ 6896.00usft (Original Well Elev) |
| Site: | 2308-18P Rodeo | North Reference: | True |
| Well: | Rodeo UT #500H | Survey Calculation Method: | Minimum Curvature |
| Wellbore: | Wellbore #1 | | |
| Design: | Design #1 26July16 sam | | |

| Planned Survey | | | | | | | | | | |
|---------------------------------------|-----------------|-------------------|-----------------------|-------------|-------------|-------------------------|-------------------------|------------------------|-----------------------|------|
| Measured Depth (usft) | Inclination (°) | Azimuth (bearing) | Vertical Depth (usft) | +N-S (usft) | +E-W (usft) | Vertical Section (usft) | Dogleg Rate (°/100usft) | Bulld Rate (°/100usft) | Turn Rate (°/100usft) | |
| 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 320.00 | 0.00 | 0.00 | 320.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 9 5/8" | | | | | | | | | | |
| 500.00 | 0.00 | 0.00 | 500.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 1,000.00 | 0.00 | 0.00 | 1,000.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Start Build 2.00 | | | | | | | | | | |
| 1,500.00 | 10.00 | 99.70 | 1,497.47 | -7.33 | 42.90 | 37.08 | 2.00 | 2.00 | 0.00 | 0.00 |
| 1,761.92 | 15.24 | 99.70 | 1,752.97 | -16.97 | 99.28 | 85.82 | 2.00 | 2.00 | 0.00 | 0.00 |
| Hold 15.24 Inclination | | | | | | | | | | |
| 2,000.00 | 15.24 | 99.70 | 1,982.68 | -27.51 | 160.97 | 139.14 | 0.00 | 0.00 | 0.00 | 0.00 |
| 2,500.00 | 15.24 | 99.70 | 2,465.10 | -49.65 | 290.51 | 251.12 | 0.00 | 0.00 | 0.00 | 0.00 |
| 3,000.00 | 15.24 | 99.70 | 2,947.52 | -71.78 | 420.05 | 363.09 | 0.00 | 0.00 | 0.00 | 0.00 |
| 3,500.00 | 15.24 | 99.70 | 3,429.94 | -93.92 | 549.59 | 475.07 | 0.00 | 0.00 | 0.00 | 0.00 |
| 4,000.00 | 15.24 | 99.70 | 3,912.36 | -116.06 | 679.13 | 587.04 | 0.00 | 0.00 | 0.00 | 0.00 |
| 4,500.00 | 15.24 | 99.70 | 4,394.78 | -138.19 | 808.66 | 699.02 | 0.00 | 0.00 | 0.00 | 0.00 |
| 4,604.30 | 15.24 | 99.70 | 4,495.42 | -142.81 | 835.69 | 722.38 | 0.00 | 0.00 | 0.00 | 0.00 |
| Start Build DLS 9.00 TFO 42.59 | | | | | | | | | | |
| 5,000.00 | 47.80 | 131.84 | 4,830.05 | -252.90 | 1,001.52 | 919.64 | 9.00 | 8.23 | 8.12 | 0.00 |
| 5,139.00 | 60.00 | 135.28 | 4,911.81 | -330.32 | 1,082.55 | 1,031.61 | 9.00 | 8.78 | 2.48 | 0.00 |
| Hold 60.00 Inclination | | | | | | | | | | |
| 5,239.00 | 60.00 | 135.28 | 4,961.81 | -391.86 | 1,143.49 | 1,118.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Start Build DLS 9.00 TFO -0.39 | | | | | | | | | | |
| 5,407.78 | 75.19 | 135.18 | 5,025.95 | -502.30 | 1,253.07 | 1,273.21 | 9.00 | 9.00 | -0.06 | 0.00 |
| Start DLS 9.00 TFO 1.12 | | | | | | | | | | |
| 5,484.00 | 82.05 | 135.31 | 5,040.98 | -555.33 | 1,305.65 | 1,347.70 | 9.00 | 9.00 | 0.18 | 0.00 |
| 7" | | | | | | | | | | |
| 5,500.00 | 83.49 | 135.34 | 5,043.00 | -566.62 | 1,316.81 | 1,363.54 | 9.00 | 9.00 | 0.17 | 0.00 |
| 5,583.70 | 91.02 | 135.48 | 5,047.00 | -626.11 | 1,375.46 | 1,446.86 | 9.00 | 9.00 | 0.17 | 0.00 |
| POE at 91.02 at 135.48 | | | | | | | | | | |
| 6,000.00 | 91.02 | 135.48 | 5,039.56 | -922.89 | 1,667.30 | 1,861.97 | 0.00 | 0.00 | 0.00 | 0.00 |
| 6,500.00 | 91.02 | 135.48 | 5,030.63 | -1,279.34 | 2,017.83 | 2,360.53 | 0.00 | 0.00 | 0.00 | 0.00 |
| 7,000.00 | 91.02 | 135.48 | 5,021.70 | -1,635.78 | 2,368.35 | 2,859.10 | 0.00 | 0.00 | 0.00 | 0.00 |
| 7,500.00 | 91.02 | 135.48 | 5,012.77 | -1,992.23 | 2,718.87 | 3,357.66 | 0.00 | 0.00 | 0.00 | 0.00 |
| 8,000.00 | 91.02 | 135.48 | 5,003.84 | -2,348.68 | 3,069.39 | 3,856.23 | 0.00 | 0.00 | 0.00 | 0.00 |
| 8,500.00 | 91.02 | 135.48 | 4,994.91 | -2,705.12 | 3,419.91 | 4,354.80 | 0.00 | 0.00 | 0.00 | 0.00 |
| 9,000.00 | 91.02 | 135.48 | 4,985.97 | -3,061.57 | 3,770.44 | 4,853.36 | 0.00 | 0.00 | 0.00 | 0.00 |
| 9,500.00 | 91.02 | 135.48 | 4,977.04 | -3,418.02 | 4,120.96 | 5,351.93 | 0.00 | 0.00 | 0.00 | 0.00 |
| 10,000.00 | 91.02 | 135.48 | 4,968.11 | -3,774.46 | 4,471.48 | 5,850.49 | 0.00 | 0.00 | 0.00 | 0.00 |
| 10,500.00 | 91.02 | 135.48 | 4,959.18 | -4,130.91 | 4,822.00 | 6,349.06 | 0.00 | 0.00 | 0.00 | 0.00 |
| 11,000.00 | 91.02 | 135.48 | 4,950.25 | -4,487.36 | 5,172.53 | 6,847.62 | 0.00 | 0.00 | 0.00 | 0.00 |
| 11,500.00 | 91.02 | 135.48 | 4,941.32 | -4,843.81 | 5,523.05 | 7,346.19 | 0.00 | 0.00 | 0.00 | 0.00 |
| 11,517.67 | 91.02 | 135.48 | 4,941.00 | -4,856.40 | 5,535.43 | 7,363.81 | 0.00 | 0.00 | 0.00 | 0.00 |
| TD at 11517.67 | | | | | | | | | | |

WPX
Planning Report

| | | | |
|------------------|------------------------|-------------------------------------|---------------------------------------|
| Database: | COMPASS | Local Co-ordinate Reference: | Well Rodeo UT #500H |
| Company: | WPX Energy | TVD Reference: | GL @ 6896.00usft (Original Well Elev) |
| Project: | T23N R8W | MD Reference: | GL @ 6896.00usft (Original Well Elev) |
| Site: | 2308-18P Rodeo | North Reference: | True |
| Well: | Rodeo UT #500H | Survey Calculation Method: | Minimum Curvature |
| Wellbore: | Wellbore #1 | | |
| Design: | Design #1 26July16 sam | | |




| Design Targets | | | | | | | | | |
|--|------------------|-----------------------|---------------|-----------------|-----------------|--------------------|-------------------|-----------|-------------|
| Target Name - hit/miss target - Shape | Dip Angle (°) | Dip Dir. (bearing) | TVD (usft) | +N/-S (usft) | +E/-W (usft) | Northing (usft) | Easting (usft) | Latitude | Longitude |
| Start 60 Tan #500H - plan hits target center - Point | 0.00 | 0.00 | 4,911.81 | -330.32 | 1,082.55 | 1,899,159.44 | 536,001.21 | 36.219493 | -107.711284 |
| BHL #500H - plan hits target center - Point | 0.00 | 0.00 | 4,941.00 | -4,856.40 | 5,535.43 | 1,894,638.80 | 540,459.62 | 36.207057 | -107.696191 |
| End 60 Tan #500H - plan misses target center by 1.15usft at 5238.99usft MD (4961.81 TVD, -391.85 N, 1143.48 E) - Point | 0.00 | 0.00 | 4,961.81 | -391.04 | 1,144.30 | 1,899,098.80 | 536,063.04 | 36.219326 | -107.711075 |
| POE #500H - plan hits target center - Point | 0.00 | 0.00 | 5,047.00 | -626.11 | 1,375.46 | 1,898,864.01 | 536,294.48 | 36.218680 | -107.710291 |

| Casing Points | | | | | |
|--------------------------|--------------------------|--------|-------------------------|-----------------------|--|
| Measured Depth (usft) | Vertical Depth (usft) | Name | Casing Diameter (in) | Hole Diameter (in) | |
| 320.00 | 320.00 | 9 5/8" | 9.625 | 12.250 | |
| 5,484.00 | 5,040.98 | 7" | 7.000 | 8.750 | |


| Plan Annotations | | | | |
|--------------------------|--------------------------|-------------------|-----------------|--------------------------------|
| Measured Depth (usft) | Vertical Depth (usft) | Local Coordinates | | Comment |
| | | +N/-S (usft) | +E/-W (usft) | |
| 1,000.00 | 1,000.00 | 0.00 | 0.00 | Start Build 2.00 |
| 1,761.92 | 1,752.97 | -16.97 | 99.28 | Hold 15.24 Inclination |
| 4,604.30 | 4,495.42 | -142.81 | 835.69 | Start Build DLS 9.00 TFO 42.59 |
| 5,139.00 | 4,911.81 | -330.32 | 1,082.55 | Hold 60.00 Inclination |
| 5,239.00 | 4,961.81 | -391.86 | 1,143.49 | Start Build DLS 9.00 TFO -0.39 |
| 5,407.78 | 5,025.95 | -502.30 | 1,253.07 | Start DLS 9.00 TFO 1.12 |
| 5,583.70 | 5,047.00 | -626.11 | 1,375.46 | POE at 91.02 at 135.48 |
| 11,517.67 | 4,941.00 | -4,856.40 | 5,535.43 | TD at 11517.67 |



Well Name: Rodeo UT #500H
 Surface Location: 2308-18P Rodeo
 NAD 1927 (NADCON CONUS), US State Plane 1927 (Exact solution) New Mexico West 3003
 Ground Elevation: 6896.00
 +N/-S +E/-W Northing Easting Latitude Longitude Slot
 0.00 0.00 1899488.44 534918.26 36.220400 -107.714954
 GL @ 6896.00usft (Original Well Elev)



Project: T23N R8W
 Site: 2308-18P Rodeo
 Well: Rodeo UT #500H
 Wellbore: Wellbore #1
 Design: Design #1 26July16 sam



| SLOTS | | | |
|-----------|-------|--------|----------------------|
| Slot Name | +N/-S | +E/-W | Northing Easting |
| A1 | 0.00 | 0.00 | 1899488.44 534918.26 |
| A2 | 10.55 | -16.81 | 1899498.97 534901.44 |

| DESIGN TARGET DETAILS | | | | | | | | |
|-----------------------|---------|----------|---------|------------|-----------|-----------|-------------|-------|
| Name | TVD | +N/-S | +E/-W | Northing | Easting | Latitude | Longitude | Shape |
| Start 60 Tan #500H | 4911.81 | -330.32 | 1082.55 | 1899159.44 | 536001.21 | 36.219493 | -107.711284 | Point |
| End 60 Tan #500H | 4961.81 | -391.04 | 1144.30 | 1899098.80 | 536063.04 | 36.219326 | -107.711075 | Point |
| POE #500H | 5047.00 | -626.11 | 1375.46 | 1898864.01 | 536294.48 | 36.218680 | -107.710291 | Point |
| BHL #500H | 4941.00 | -4856.40 | 5535.43 | 1894638.80 | 540459.62 | 36.207057 | -107.696191 | Point |

| ANNOTATIONS | | | | | | | | |
|-------------|----------|-------|--------|----------|---------|---------|-----------|--------------------------------|
| TVD | MD | Inc | Azi | +N/-S | +E/-W | VSect | Departure | Annotation |
| 1000.00 | 1000.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | Start Build 2.00 |
| 1752.97 | 1761.92 | 15.24 | 99.70 | -16.97 | 99.28 | 85.82 | 100.72 | Hold 15.24 Inclination |
| 4495.42 | 4604.30 | 15.24 | 99.70 | -142.81 | 835.69 | 722.38 | 847.80 | Start Build DLS 9.00 TFO 42.59 |
| 4911.81 | 5139.00 | 60.00 | 135.28 | -330.32 | 1082.55 | 1031.61 | 1160.78 | Hold 60.00 Inclination |
| 4961.81 | 5239.00 | 60.00 | 135.28 | -391.86 | 1143.49 | 1118.00 | 1247.38 | Start Build DLS 9.00 TFO -0.39 |
| 5025.95 | 5407.78 | 75.19 | 135.18 | -502.30 | 1253.07 | 1273.21 | 1402.96 | Start DLS 9.00 TFO 1.12 |
| 5047.00 | 5583.70 | 91.02 | 135.48 | -626.11 | 1375.46 | 1446.86 | 1577.06 | POE at 91.02 at 135.48 |
| 4941.00 | 11517.67 | 91.02 | 135.48 | -4856.40 | 5535.43 | 7363.81 | 7510.08 | TD at 11517.67 |

subsoils from the Fruitland-Persayo-Sheppard complex, hilly soil map unit. A brief description of this soil can be found below.

The Fruitland-Persayo-Sheppard complex, hilly is composed of 40 percent Fruitland and similar soils, 30 percent Persayo and similar soils, and 25 percent Sheppard and similar soils. Fruitland-Persayo-Sheppard complex, hilly soils are found on alluvial fans, stream terraces, hills, ridges, breaks, and dunes ranging from 4,000 feet to 6,400 feet in elevation. Fruitland soils occur on slopes of 5 to 30 percent, are well drained, and have a high water permeability. Persayo soils occur on slopes of 5 to 30 percent, are well drained, and have low to moderately high water permeability. Sheppard soils occur on slopes of 5 to 30 percent, are excessively drained, and have high to very high water permeability. This soil complex has a low to moderate potential for water erosion and moderate to high potential for wind erosion. The Fruitland-Persayo-Sheppard complex (hilly) is generally found within sandy, shale hills, and deep sand ecological sites (USDA/NRCS 2015).

C. Badland

Within the project area, this soil map unit is distinctly recognized by the presence of contrasting black to light grey shades of clay soils with little to no vegetation cover. Excavated soils during construction of one segment of well-connect pipeline would consist of native borrow and subsoils from the badland soil map unit. A brief description of this soil can be found below.

The parent material of the Badland map unit primarily consists of shale. This soil is considered a somewhat excessively drained soil, with the depth to restrictive layer (paralithic bedrock) being zero to two inches. Available water capacity for the Badland soil unit is very low (zero inches). This soil type has a low to moderate potential for water erosion and moderate potential for wind erosion. Badland soils are typically found along the side slopes of break landforms (5- to 80-percent slopes), and are commonly used for wildlife habitat (USDA/NRCS 2015). (USDA/NRCS 2015).

7. METHODS FOR HANDLING WASTE

A. Cuttings

- 1 Drilling operations would utilize a closed-loop system. Drilling of the horizontal laterals would be accomplished with water-based mud. All cuttings would be placed in roll-off bins and hauled to a commercial disposal facility or land farm. WPX would follow Onshore Oil and Gas Order No. 1 regarding the placement, operation, and removal of closed-loop systems. No blow pit would be used.
- 2 Closed-loop tanks would be adequately sized for containment of all fluids.

B. Drilling Fluids

- 1 Drilling fluids would be stored onsite in above-ground storage tanks. Upon termination of drilling operations, the drilling fluids would be recycled and transferred to other permitted closed-loop systems or returned to the vendor for reuse, as practical. All residual fluids would be hauled to a commercial disposal facility.

C. Spills

- 1 Any spills of non-freshwater fluids would be immediately cleaned up and removed to an approved disposal site.

D. Sewage

- 1 Portable toilets would be provided and maintained as needed during construction (see Figures 3 and 4 in Appendix B for the location of toilets per project phase).

Directions from the Intersection of US Hwy 550 & US Hwy 64

in Bloomfield, NM to WPX Energy Production, LLC Rodeo UT #500H

271' FSL & 410' FEL, Section 18, T23N, R8W, N.M.P.M., San Juan County, NM

Latitude: 36.220413°N Longitude: 107.715566°W Datum: NAD1983

From the intersection of US Hwy 550 & US Hwy 64 in Bloomfield, NM, travel Southerly on US Hwy 550 for 37.8 miles to Mile Marker 113.4;

Go Right (South-westerly) on County Road #7890 for 0.7 miles to begin proposed access on left-hand side of County Road #7890 which continues for an additional 6555.1' to staked WPX Rodeo UT #500H location.