

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

## Sundry Notices and Reports on Wells

2006 MAR 27 PM 2:44

1. **Type of Well**  
GAS

2. **Name of Operator**

**BURLINGTON**

RESOURCES OIL &amp; GAS COMPANY LP

3. **Address & Phone No. of Operator**

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. **Location of Well, Footage, Sec., T, R, M**

Sec., T--N, R--W, NMPM

Unit P (SESE) 1045' FSL &amp; 740' FEL, Sec. 6, T29N R7W NMPM

5. **Lease Number**  
NMSF-078943

6. **If Indian, All. or  
Tribe Name**

7. **Unit Agreement Name**  
San Juan 29-7 Unit

8. **Well Name & Number**

9. **San Juan 29-7 Unit #46C  
API Well No.**

30-039-29730

10. **Field and Pool**

Blanco MV/ Basin DK

11. **County and State**  
Rio Arriba Co., NM

**12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA****Type of Submission****Type of Action**☐ Notice of Intent☐ Abandonment☐ Change of Plans☒ Other - 7" - 4 1/2" Casing☒ Subsequent Report☐ Recompletion☐ New Construction☐ Plugging☐ Non-Routine Fracturing☐ Casing Repair☐ Water Shut off☐ Final Abandonment☐ Altering Casing☐ Conversion to Injection**13. Describe Proposed or Completed Operations**

3/17/06 MIRU Bearcat #5. NU BOPE. PT csg to 600# for 30mins, ok. 3/18/06 RIH w/8 3/4" bit & tagged cmt @ 103'. D/O cmt & ahead to 3265'. Circulate hole. RIH w/75jts of 7" 20# J55 ST&C csg & set @3259' w/ DV tool. Circulate hole. 3/21/06 Cmt 1<sup>st</sup> stage: Pumped preflush w/10bbls gel H2O, 2bbls FW. Pump 19sxs(57cu-10bbls)prem lite w/3% CaCl2, .25pps Cell-o-Flake, 5pps LCM1, .4%FL52, .4%SMS. Lead w/33sxs(70cu-13bbls)prem lite w/3% CaCl2, .25pps Cell-o-Flake, 5pps LCM1, .4% FL52, .4% SMS. Tail w/90sxs(124cu-22bbls)Type 3 cmt w/1% CaCl2, .25pps Cell-o-flake, .2% FL52. Drop plug & displace w/40bbls FW & 91bbls mud. Bump plug to 842#. Press up to 2150#. Opened stage tool. Circulated 15bbls cmt to reserve pit. Plug down @ 1208. Circulate between stages. 2<sup>nd</sup> Stage: Pumped preflush w/10bbls FW, 10bbls mud, 10bbls FW. Pump 19sx(57cu-10bbls)prem lite w/3% CaCl2, .25pps Cell-o-Flake, 5pps LCM1, .4% FL52, .4% SMS. Lead w/315sx(671cu-120bbls)prem lite w/3% CaCl2, .25pps Cell-o-Flake, 5pps LCM1, .4% FL52, .4% SMS. Drop plug & displace w/100bbls FW. Bump plug to 1825#. Close stage collar. Circulated 20bbls cmt to reserve pit. Plug down @ 1645. ND BOP NU "B: section and BOP. PT csg to 1500# 30 mins, ok.

3/22/06 RIH 6 1/4" bit & tagged cmt. D/O cmt drlg stage collar, unload hole, drlg float collar cmt & float shoe. D/O & ahead to TD 7469'. TD reached 3/24/06. Circulated hole. RIH w/4 1/2" 13jts of 11.6# J55 LT&C & 162jts 10.5# J55 ST&C csg & set @7468'. Preflush w/10 bbls chem wash, 2bbls FW. Lead w/9sxs(28cu-5bbls)prem lite w/.3% CD32, .25pps Cell-o-flake, 6.25pps LCM1, 1% FL52. Tail 297sxs (588cu-105bbls)prem lite w/.25pps Cell-o-Flake, 6.25pps LCM1, .3% CD32, 1% FL52. Drop plug & displaced w/117bbls FW and 25# sugar in first 10bbls. Bump plug to 1600. Plug down @ 0156hrs 3/25/06. ND BOPE. RD. Rig released @ 0800 3/25/06. Will show top of cmt & csg PT on next report. PT will be conducted by completing rig.

**14. I hereby certify that the foregoing is true and correct.**Signed Amanda Sandoval Amanda Sandoval Title Regulatory Compliance Assistant III Date 3/27/06

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Date APR 07 2006

NMOCD