submitted in lieu of Form 3160-5 **UNITED STATES** DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT** Sundry Notices and Reports on Wells Lease Number NMNM-03583 Type of Well If Indian, All. or **GAS** Tribe Name 7. **Unit Agreement Name** Name of Operator BURLINGTON San Juan 28-6 Unit RESCURCES OIL & GAS COMPANY LP 8. Well Name & Number Address & Phone No. of Operator S.I 28-6 Unit #204M PO Box 4289, Farmington, NM 87499 (505) 326-9700 9. API Well No. 30-039-29767 Location of Well, Footage, Sec., T, R, M 10. Field and Pool Basin DK / Blanco MV Unit G (SWNE), 1920' FNL & 2426' FEL, Sec. 8, T27N, R6W, NMPM 11. **County and State** Rio Arriba, Co NM 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA Type of Submission Type of Action Change of Plans X Notice of Intent Abandonment X Other - casing New Construction Recompletion Non-Routine Fracturing Plugging Subsequent Report Casing Repair Water Shut off Altering Casing Conversion to Injection Final Abandonment 13. Describe Proposed or Completed Operations 3/26/06 RIH w/8-3/4" bit & tagged cement @ 175'. D/O cement & then ahead to 3445'. Circ. hole. RIH w/79 jts 7" 20#; 1-55 casing & set @ 3392' w/stage tool @ 2611'. RU to cement. 3/29/06 1st Stage - pumped 10 bbls gel water, 2 bbls FW preffush. Pumped 18 sx (54 cf -10 bbls) Class B w/3% CaCl2. .25#/sx Celloflake, 5#/sx LCM-1, .4% FL-52, .4% SMS. Lead w/170 sx. (235 cf - 42 bbls), Type III w/1% CaCl2, 25#/sx Celloflake, .20% FL-52. Dropped plug and displaced. Opened stage tool & circ. 30 bbls cmt to surface. 2<sup>nd</sup> Stage Pumped 18 sx (54 cf - 10 bbl) Class B w/same additives as 1<sup>st</sup> stage. Lead w/331 sx (705 cf - 125 bbl) Premium Lite w/3% CaCl2, .25#/sx Celloflake, 5#/sx LCM-1, .4% FL-52, .4% SML. Dropped plug and displaced. Circ. 30 bbls to surface. WOC. 3/31/06 RIH w/6-1/4" bit & D/O stage collar tool & Load hole & PT casing to 1500 #/30 min, OK, 3/31/06 With 6-1/4" & D/O shoe collar & shoe & drilled ahead to 7612' (TD). TD reached 4/1/06. Circ. hole. RIH w/4-1/2" 1-2552 casing (19 its 11.6# & 166 its 10.5#). RU to cement. Pumped preflush of 10 bbl chem. Wash, 2 bbls FW, ahead of 9 sx (27 cf 5 bbls) Premium Lite w/.25#/sx Celloflake, .3% CD-32, 6.25#/sx LCM-1, 1% FL-52. Lead – 296 sx (586 cf – 104 bbl slurry) Premium Lite w/.25#/sx Celloflake, 3% CD-32, 6.25#/sx LCM-1, & 1% FL-52. Displaced w/10 bbls sugar water & 110 bbls FW. Landed APR 2006 Plug @ 0415 hrs. Held. WOC. 4/3/06 RD & released rig 4/3/06. TOC will be shown on next report. PT will be conducted

by the completion rig and results reported on hext re	pon. 		**	CVI.	_ islor a
14. I hereby certify that the foregoing is true Signed Attle lugary	e and correct.  Patsy Clugston	Title Sr. Regulatory Specialist	of the second	1964. 3 Pate: 4/5/06	
	ruisy Stagston	The St. Meganatory Specialist	· '	CYCSCY!	ر میشوارد میشوارد
(This space for Federal or State Office use)				ATR O	7 2005
APPROVED BY	Title		Date _	<u> </u>	•

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction