Well: J. E. Decker #3-B 1,980' FNL & 660' FWL Location: Sec 17 T32N R11W NMPM

San Juan County, New Mexico 30-045-30320 API no:

prepared by L. M. Cure 26 Jan 15

NOV 1 2017

OIL CONS. DIV DIST. Gerator: Great Western Drilling Company Spud date: 12/26/2000 Elevations: KB 6.668 KB-GL 17'

GL

6.651

TOPS NOTES HOLE CASING SIZE & CEMENT 12 1/4" 9 5/8" 36# J-55 ST&C at 330" critid to GL w/ 220 sx - circ 20 bbl 330 8 3/4" 2 3/8" 4.7# J-55 EUE tubing Nacimento at 604' Ojo Alamo at 1,374' Kirtland at 1.454' DV tool at 2,426' circulated 15 bbl fromn 1st stage and then cemented 2nd stage to GL w/278 ax - circ 5 bbl Fruitland at 2.850° Pictured Cliffs at 3,296 Lewis at 3,440' 3,639 7" 20# J-55 ST&C at 3,639" cmt to 1st stg w/795 sx 6 1/4" top of cement behind 4 1/2" casing at 4,830' by CBL Cliff House at 4,830 perfs 4,972 - 5,244' acdz w/ 1k gal 15% HCi tracd w/ 113 kgal + 109 klb 20/40/sd Menafee at 5,248' perfs 5,316 - 5,889' actiz w/ 1k gal 15% HCI Point Lookout at 5,596' fracd w/ 108 kgal + 90 kib 20/40/sd EOT at 5,831' - may end with a bit or notched collar Mancos at 5,906' 4 1/2" 10.5# J-55 ST&C at 6,003" pbtd 5,926' cmtd w/ 190 sx TD at 6,018"