### DEC 0 1 2017

Form 3160-5 (June 2015)

#### **UNITED STATES**

Farmington Field Office Bureau of Land Management FORM APPROVED OMB No. 1004-0137 Expires: January 31, 2018

DEPART	MENT	OF	THE	INTE	RIOR
BUREAU	OF LA	ND	MAT	NAGE	MEN

BOILE OF EATH WITH GENERAL				5. Lease Serial No. <b>NO-G-1310-1841</b> 6. If Indian, Allottee or Tr.	ibe Name		
SUBM 1. Type of Well	IIT IN TRIPLICATE - Other instru	uctions on page 2		7. If Unit of CA/Agreement, Name and/or No. NMNM 135216A			
⊠Oil Well	Gas Well Other			8. Well Name and No. W Lybrook Unit #749H			
2. Name of Operator WPX Energy Production, L	IC.			9. API Well No. 30-045-35744			
3a. Address PO Box 640 Aztec, NI		3b. Phone No. (include area code) 505-333-1808		10. Field and Pool or Expl Lybrook Mancos W	oratory Area		
4. Location of Well (Footage, Sec SHL: 828' FSL & 480' FEL, Sec BHL: 945'FNL & 336' FEL, Sec				11. Country or Parish, Stat San Juan, NM	е		
12	. CHECK THE APPROPRIATE BO	OX(ES) TO INDICATE NATURE	OF NOTIC	CE, REPORT OR OTHER	DATA		
TYPE OF SUBMISSION		TYPE	OF ACTI	ON			
☑Notice of Intent	☐Acidize ☐Alter Casing	☐Deepen ☐Hydraulic Fracturing	□Prode	uction(Start/Resume) amation	☐Water ShutOff ☐Well Integrity		
☐ Subsequent Report ☐ Final Abandonment Notice	□Casing Repair □Change Plans □Convert to Injection	<ul><li>New Construction</li><li>□ Plug and Abandon</li><li>□ Plug Back</li></ul>		mplete porarily Abandon r Disposal	Other Flare  Extension  continued		
13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be perfonned or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has detennined that the site is ready for final inspection.)  SEE ATTACHED FOR  CONDITIONS OF APPROVAL  The Frac activity on W. Lybrook Unit 716H - 718H - 719H - 753H - 755H caused High Nitrogen and CO2 content level on							
W. Lybrook Unit 749H.	The Frac activity on W. Lybrook Unit 716H - 718H- 719H- 753H-754H- 755H caused High Nitrogen and CO2 content level on W. Lybrook Unit 749H.						

WPX Energy request to continue flaring for an additional 30 days from the current expiration date of 12/7/2017, due to the results above Williams pipeline standards, per the attached gas analysis.

DEC 07 2017

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)  Marie E. Florez	Title Permit Tech		
Signature Waldwell	Date 11/30/17		
THE SPACE FOR FEDE	RAL OR STATE O	OFICE USE	
Approved by AE E/madami	Title P E		Date 12/4/17
Conditions of approval, if any, are attached. Approval of this notice does not warrant certify that the applicant holds legal or equitable title to those rights in the subject leads which would entitle the applicant to conduct operations thereon.		FFO	7

Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.





Analysis No: WP170221 Cust No: 85500-13305

#### Well/Lease Information

Customer Name: WPX ENERGY PRODUCTION, LLC

Well Name:

716H WLU #716H;MTR

County/State:

SAN JUAN NM

Location:

Field:

Formation:

Cust. Stn. No.:

Source: Well Flowing:

METER RUN

Pressure:

Y

**132 PSIG** 

Flow Temp:

80 DEG. F

Ambient Temp:

65 DEG. F

Flow Rate:

571 MCF/D

Sample Method: Date Sampled:

Purge & Fill

Sample Time:

11/27/2017

3.10 PM

Sampled By:

JAMES MILLER

Sampled by (CO): IDEAL COMPLETIONS

Remarks:

RAN 11/28/2017

Analysis

Allalysis								
Component::	Mole%:	Unormalized %:	**GPM:	*BTU:	*SP Gravity:			
Nitrogen	32.6329	33.0607	3.6000	0.00	0.3156			
CO2	0.2506	0.2539	0.0430	0.00	0.0038			
Methane	45.6644	46.2631	7.7620	461.21	0.2529			
Ethane	8.5619	8.6742	2.2960	151.52	0.0889			
Propane	8.4230	8.5334	2.3270	211.93	0.1282			
Iso-Butane	0.9363	0.9486	0.3070	30.45	0.0188			
N-Butane	2.3346	2.3652	0.7380	76.16	0.0469			
I-Pentane	0.4122	0.4176	0.1510	16.49	0.0103			
N-Pentane	0.3818	0.3868	0.1390	15.31	0.0095			
Hexane Plus	0.4023	0.4076	0.1800	21.21	0.0133			
Total	100.0000	101.3111	17.5430	984.27	0.8882			

<sup>\* @ 14.730</sup> PSIA DRY & UNCORRECTED FOR COMPRESSIBILITY

COMPRESSIBLITY FACTOR (1/Z): 1.0029 BTU/CU.FT IDEAL: 986.6 BTU/CU.FT (DRY) CORRECTED FOR (1/Z): 989.4 BTU/CU.FT (WET) CORRECTED FOR (1/Z): 972.2 1009.2 DRY BTU @ 15.025: 0.8905 REAL SPECIFIC GRAVITY:

CYLINDER #:

CYLINDER PRESSURE:

134 PSIG

DATE RUN: ANALYSIS RUN BY: 11/27/17 12:00 AM

PATRICIA KING

GPM, BTU, and SPG calculations as shown above are based on current GPA constants.

GPA Standard: GPA-2261

GC: Danalyzer Model 500

Last Cal/Verify: 11/28/2017

<sup>\*\*@ 14.730</sup> PSIA & 60 DEG. F.



Analysis No: WP170222 Cust No: 85500-13310

#### Well/Lease Information

Customer Name: WPX ENERGY PRODUCTION, LLC

Well Name:

718H WLU #716H:MTR

County/State:

SAN JUAN NM

Location:

Field:

1

Formation:

Cust. Stn. No.:

Source:

METER RUN

Well Flowing:

Pressure:

171 PSIG

Flow Temp:

98 DEG. F

Ambient Temp:

65 DEG. F

Flow Rate:

2145 MCF/D

Sample Method: Purge & Fill

Date Sampled:

11/27/2017

Sample Time:

3.17 PM

Sampled By:

JAMES MILLER

Sampled by (CO): IDEAL COMPLETIONS

Remarks:

RAN 11/28/2017

Analysis

Analysis								
Component::	Mole%:	Unormalized %:	**GPM:	*BTU:	*SP Gravity:			
Nitrogen	77.9320	76.6238	8.5800	0.00	0.7538			
CO2	0.1359	0.1336	0.0230	0.00	0.0021			
Methane	14.3172	14.0769	2.4290	144.60	0.0793			
Ethane	2.4150	2.3745	0.6460	42.74	0.0251			
Propane	2.6793	2.6343	0.7390	67.41	0.0408			
Iso-Butane	0.3570	0.3510	0.1170	11.61	0.0072			
N-Butane	1.1266	1.1077	0.3550	36.75	0.0226			
I-Pentane	0.2821	0.2774	0.1030	11.29	0.0070			
N-Pentane	0.2986	0.2936	0.1080	11.97	0.0074			
Hexane Plus	0.4563	0.4486	0.2040	24.05	0.0151			
Total	100.0000	98.3214	13.3040	350.43	0.9603			

<sup>\* @ 14.730</sup> PSIA DRY & UNCORRECTED FOR COMPRESSIBILITY

<sup>\*\*@ 14.730</sup> PSIA & 60 DEG. F.

COMPRESSIBLITY FACTOR	(1/Z):	1.001	CYLINDER #:	5
BTU/CU.FT IDEAL:		351.2	CYLINDER PRESSURE:	162 PSIG
BTU/CU.FT (DRY) CORRECTED	FOR (1/Z):	351.6	DATE RUN:	11/27/17 3:17 PM
BTU/CU.FT (WET) CORRECTED	FOR (1/Z):	345.5	ANALYSIS RUN BY:	PATRICIA KING
DRY BTU @ 15.025:		358.6		
REAL SPECIFIC GRAVITY:		0.9609		

GPM, BTU, and SPG calculations as shown above are based on current GPA constants.

GPA Standard: GPA-2261

GC: Danalyzer Model 500

Last Cal/Verify: 11/28/2017



Analysis No: WP170223 Cust No: 85500-13315

METER RUN

#### Well/Lease Information

Customer Name: WPX ENERGY PRODUCTION, LLC

Well Name:

719H WLU # 716H:MTR

County/State:

SAN JAUN NM

Location: Field:

1

Formation: Cust. Stn. No.:

Source:

Well Flowing:

Pressure: **126 PSIG** Flow Temp: 84 DEG. F Ambient Temp: 65 DEG. F Flow Rate: 756 MCF/D Sample Method: Purge & Fill

Date Sampled: 11/27/2017 3.07 PM Sample Time: JAMES MILLER

Sampled By: Sampled by (CO): IDEAL COMPLETIONS

Remarks:

RAN 11/28/2017. SAMPLE CONTAINED SMALL AMOUNT OF CONDENSATE

Analysis

Component	Mole%:	Unarmalized 0/:	**GPM:	*BTU:	*SP Gravity:
Component::	Wole%.	Unormalized %:	GPIVI.	ъто.	SP Gravity.
Nitrogen	30.8606	31.2967	3.4050	0.00	0.2985
CO2	0.2994	0.3036	0.0510	0.00	0.0045
Methane	47.3781	48.0478	8.0540	478.52	0.2624
Ethane	8.1816	8.2972	2.1940	144.79	0.0849
Propane	8.5000	8.6201	`2.3480	213.87	0.1294
Iso-Butane	0.9992	1.0133	0.3280	32.49	0.0201
N-Butane	2.4774	2.5124	0.7830	80.82	0.0497
I-Pentane	0.4415	0.4477	0.1620	17.66	0.0110
N-Pentane	0.4054	0.4111	0.1470	16.25	0.0101
Hexane Plus	0.4568	0.4633	0.2040	24.08	0.0151
Total	100.0000	101.4132	17.6760	1008.48	0.8858

<sup>\* @ 14.730</sup> PSIA DRY & UNCORRECTED FOR COMPRESSIBILITY

COMPRESSIBLITY FACTOR (1/Z): 1.003 BTU/CU.FT IDEAL: 1010.8 BTU/CU.FT (DRY) CORRECTED FOR (1/Z): 1013.9 BTU/CU.FT (WET) CORRECTED FOR (1/Z): 996.3 DRY BTU @ 15.025: 1034.2 REAL SPECIFIC GRAVITY: 0.8881

CYLINDER #: 17

CYLINDER PRESSURE: **126 PSIG** 

DATE RUN: 11/27/17 12:00 AM

ANALYSIS RUN BY: PATRICIA KING

GPM, BTU, and SPG calculations as shown above are based on current GPA constants.

GPA Standard: GPA-2261

GC: Danalyzer Model 500

Last Cal/Verify: 11/28/2017

<sup>\*\*@ 14.730</sup> PSIA & 60 DEG. F.



Analysis No: WP170224 Cust No: 85500-13320

METER RUN

#### Well/Lease Information

Customer Name: WPX ENERGY PRODUCTION, LLC

Well Name:

753H WLU #716H;MTR

County/State:

SAN JUAN NM

Location: Field:

Formation: Cust. Stn. No.:

Flow Rate:

Source:

Well Flowing:

Pressure: 140 PSIG Flow Temp: 88 DEG. F Ambient Temp: 65 DEG. F 1201 MCF/D

Sample Method: Purge & Fill Date Sampled: 11/27/2017 Sample Time: 2.55 PM Sampled By: JAMES MILLER

Sampled by (CO): IDEAL COMPLETION

Remarks:

RAN 11/28/2017

**Analysis** 

		Allalysis			
Component::	Mole%:	Unormalized %:	**GPM:	*BTU:	*SP Gravity:
Nitrogen	36.8783	37.3011	4.0680	0.00	0.3567
CO2	0.2958	0.2992	0.0510	0.00	0.0045
Methane	41.8332	42.3129	7.1110	422.52	0.2317
Ethane	6.8800	6.9589	1.8450	121.76	0.0714
Propane	8.1432	8.2366	2.2500	204.89	0.1240
Iso-Butane	1.1115	1.1242	0.3650	36.14	0.0223
N-Butane	2.6912	2.7221	0.8510	87.80	0.0540
I-Pentane	0.5887	0.5954	0.2160	23.55	0.0147
N-Pentane	0.5688	0.5753	0.2070	22.80	0.0142
Hexane Plus	1.0093	1.0209	0.4510	53.20	0.0334
Total	100.0000	101.1466	17.4150	972.66	0.9269

<sup>\* @ 14.730</sup> PSIA DRY & UNCORRECTED FOR COMPRESSIBILITY

<sup>\*\*@ 14.730</sup> PSIA & 60 DEG. F.

COMPRESSIBLITY FACTOR BTU/CU.FT IDEAL: BTU/CU.FT (DRY) CORRECTED FOR BTU/CU.FT (WET) CORRECTED FOR BTU/CU.FT (WET) CORRECTED FOR BTU/CU.FT (WET)	, ,	1.003 974.9 977.8 960.8 997.4	CYLINDER #: CYLINDER PRESSURE: DATE RUN: ANALYSIS RUN BY:	30 77 PSIG 11/27/17 12:00 AM PATRICIA KING
DRY BTU @ 15.025: REAL SPECIFIC GRAVITY:		0.9293		

GPM, BTU, and SPG calculations as shown above are based on current GPA constants.

GPA Standard: GPA-2261

GC: Danalyzer Model 500

Last Cal/Verify: 11/28/2017



Analysis No: WP170225 Cust No: 85500-13325

METER RUN

**125 PSIG** 

92 DEG. F

#### Well/Lease Information

Customer Name: WPX ENERGY PRODUCTION, LLC

Well Name:

754H WLU #716H;MTR

County/State:

Location: Field:

ì

Formation:

Cust. Stn. No.:

SAN JUAN NM

Well Flowing: Pressure: Flow Temp: Ambient Temp:

Source:

65 DEG. F Flow Rate: 733 MCF/D Sample Method: Purge & Fill Date Sampled: 11/27/2017

2.50 PM Sample Time: Sampled By:

**WILLY JONES** 

Sampled by (CO): IDEAL CPMPLETION

Remarks:

RAN 11/28/2017

Analysis

Allalysis								
Component::	Mole%:	Unormalized %:	**GPM:	*BTU:	*SP Gravity:			
Nitrogen	57.3035	57.4908	6.3150	0.00	0.5542			
CO2	0.2938	0.2948	0.0500	0.00	0.0045			
Methane	27.5686	27.6587	4.6810	278.44	0.1527			
Ethane	4.3707	4.3850	1.1710	77.35	0.0454			
Propane	6.0132	6.0329	1.6590	151.30	0.0916			
Iso-Butane	0.8669	0.8697	0.2840	28.19	0.0174			
N-Butane	2.1179	2.1248	0.6690	69.09	0.0425			
I-Pentane	0.4597	0.4612	0.1680	18.39	0.0115			
N-Pentane	0.4257	0.4271	0.1550	17.07	0.0106			
Hexane Plus	0.5800	0.5819	0.2590	30.57	0.0192			
Total	100.0000	100.3269	15.4110	670.40	0.9495			

<sup>\* @ 14.730</sup> PSIA DRY & UNCORRECTED FOR COMPRESSIBILITY

COMPRESSIBLITY FACTOR 1.0019 (1/Z): BTU/CU.FT IDEAL: 672.0 BTU/CU.FT (DRY) CORRECTED FOR (1/Z): 673.2 661.5 BTU/CU.FT (WET) CORRECTED FOR (1/Z): DRY BTU @ 15.025: 686.7 0.9509 REAL SPECIFIC GRAVITY:

CYLINDER #: 16

CYLINDER PRESSURE: **121 PSIG** 

DATE RUN:

11/27/17 2:50 PM

ANALYSIS RUN BY:

PATRICIA KING

GPM, BTU, and SPG calculations as shown above are based on current GPA constants.

GPA Standard: GPA-2261

GC: Danalyzer Model 500

Last Cal/Verify: 11/28/2017

<sup>\*\*@ 14.730</sup> PSIA & 60 DEG. F.



Analysis No: WP170226 Cust No: 85500-13330

#### Well/Lease Information

Customer Name: WPX ENERGY PRODUCTION, LLC

Well Name:

755H WLU #716H;MTR

County/State:

SAN JUAN NM

Location:

Field:

Formation:

Cust. Stn. No.:

Source:

Well Flowing:

METER RUN

Pressure:

Flow Temp:

140 PSIG

Ambient Temp:

83 DEG. F

Flow Rate:

65 DEG. F

386 MCF/D

Sample Method: Date Sampled:

Purge & Fill

11/27/2017

Sample Time:

2.49 PM

Sampled By:

JAMES MILLER

Sampled by (CO):

Remarks:

RAN 11/28/2017. SAMPLE CONTAINED A SMALL AMOUNT OF CONDENSATE,

Analysis

Allalysis								
Component::	Mole%:	Unormalized %:	**GPM:	*BTU:	*SP Gravity:			
Nitrogen	22.3117	22.5449	2.4630	0.00	0.2158			
CO2	0.3261	0.3295	0.0560	0.00	0.0050			
Methane	54.2193	54.7860	9.2220	547.61	0.3003			
Ethane	8.7012	8.7921	2.3350	153.99	0.0903			
Propane	9.3301	9.4276	2.5790	234.75	0.1421			
Iso-Butane	1.1306	1.1424	0.3710	36.77	0.0227			
N-Butane	2.5244	2.5508	0.7980	82.35	0.0507			
I-Pentane	0.4474	0.4521	0.1640	17.90	0.0111			
N-Pentane	0.3987	0.4029	0.1450	15.98	0.0099			
Hexane Plus	0.6105	0.6169	0.2730	32.18	0.0202			
Total	100.0000	101.0452	18.4060	1121.54	0.8681			

<sup>\* @ 14.730</sup> PSIA DRY & UNCORRECTED FOR COMPRESSIBILITY

<sup>\*\*@ 14.730</sup> PSIA & 60 DEG. F.

GPM, BTU, and SPG calculations as shown above are based on current GPA constants.

GPA Standard: GPA-2261

GC: Danalyzer Model 500

Last Cal/Verify: 11/28/2017



# United States Department of the Interior

#### **BUREAU OF LAND MANAGEMENT**

Farmington District Office 6251 College Blvd. - Suite A Farmington, New Mexico 87402 www.blm.gov/nm



In Reply refer To:

## **Conditions of Approval**

- Flaring is authorized pursuant to 43 CFR 3170, Subpart 3179.102.
- 43 CFR 3179.9 (a) The operator must estimate or measure all volumes of gas vented or flared from wells, facilities and equipment on a lease, unit PA, or communitized area and report those volumes under applicable ONRR reporting requirements.
- Flaring will be authorized until January 7, 2018 if additional time is required, please contact this office accordingly.
- Please take appropriate and necessary safety precautions at this well site during the flaring period.