

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

- | | |
|--|---|
| <p>1. Type of Well
GAS</p> <p>2. Name of Operator
CDX RIO, LLC</p> <p>3. Address & Phone No. of Operator
2010 Afton Place, Farmington, New Mexico 87401 (505) 326-3003</p> <p>4. Location of Well, Footage, Sec., T, R, M
2335'FNL, 1300'FEL, Sec.3, T-26-N, R-5-W, NMPM</p> | <p>5. Lease Number
Jicarilla Contract 151</p> <p>6. If Indian, All. or Tribe Name
Jicarilla Apache</p> <p>7. Unit Agreement Name</p> <p>8. Well Name & Number
Jicarilla 151 #8F</p> <p>9. API Well No.
30-039-29204</p> <p>10. Field and Pool
WC Basin Mancos/Basin DK</p> <p>11. County and State
Rio Arriba Co, NM</p> |
|--|---|

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
☐ Notice of Intent	☐ Abandonment ☐ Change of Plans
☒ Subsequent Report	☐ Recompletion ☐ New Construction
☐ Final Abandonment	☐ Plugging ☐ Non-Routine Fracturing
	☐ Casing Repair ☐ Water Shut off
	☐ Altering Casing ☐ Conversion to Injection
	☒ Other

13. Describe Proposed or Completed Operations

- 2-20-06 MIRU. NU BOP. TIH w/3 7/8" bit. SDON.
- 2-21-06 TIH, tag up @ 8335'. Drill out soft cmt from 8335' to PBTD @ 8353'. Circ hole clean w/230 bbl 2% KCL wtr. TOO H w/bit. ND BOP. Pump 14 bbl 2% KCL wtr to load up csg. NU WH. RD. Rig released.
- 3-9-06 (Verbal approval to proceed with squeeze if necessary from Jim Lovato, BLM). MIRU. ND WH. NU BOP. TIH, tag up @ 8348'. Circ hole clean. TOO H. TIH w/4 1/2" CIBP, set @ 6375'. Circ hole clean. PT CIBP to 2000 psi/15 min, OK. TOO H. SDON.
- 3-10-06 TIH, perf 2 sqz holes @ 5950'. TOO H. Establish injection w/10 bbl wtr. TIH w/4 1/2" cmt retainer. SD for weather.
- 3-11-06 Set cmt retainer @ 5910'. Establish injection w/10 bbl wtr. Pump 250 sx 50/50 poz w/3% gel, 0.1% CFR-3 0.4% Halad-9 (363 cu.ft.). Tail w/25 sx Class "B" cmt w/0.4% Halad-9 (30 cu.ft.). Displace w/23 bbl wtr to cmt retainer. Circ 0.5 bbl cmt to surface. TOO H. WOC. SD for Sunday.
- 3-13-06 TIH, ran CBL @ 3930-5902', TOC @ 5450'. Good bond @ 5450-5902'. Cmt stringers @ 4200-5450'. TIH, tag TOC @ 5902'. Circ hole clean. PT 4 1/2" lnr to 2000 psi/15 min, OK. Drill cmt retainer @ 5910'.
- 3-14-06 Drill out cmt retainer @ 5910'. PT lnr to 2000 psi/15 min, OK. Drill cmt @ 5910-5980'. Circ hole clean. PT sqz holes to 2000 psi/15 min, OK. TOO H.
- 3-15-06 TIH to CIBP @ 6375'. Circ hole clean. Drill out CIBP @ 6375'. TIH, tag up @ PBTD @ 8353'.

14. I hereby certify that the foregoing is true and correct.

Signed Nancy Altmanna Title Agent Date 3/23/06

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

APR 14 2006

NMOC