

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or reenter an abandoned well. Use Form 3160-3 (APD) for such proposals.

FORM APPROVED
OMB No. 1004-0135
Expires July 31, 1996

RECEIVED

5. Lease Serial No.
1420-603-1228

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

NM
Central Bisti Unit

8. Well Name and No.

Central Bisti Unit #72

9. API Well No.

30-045-22945

10. Field and Pool, or Exploratory Area

Bisti Lower Gallup

11. County or Parish, State

San Juan, New Mexico

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

Elm Ridge Resources, Inc.

3a. Address

PO Box 189 Farmington, NM 87499

3b. Phone No. (include area code)

505-632-3476

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 2080' FEL


Sec. 9-T25N-R12W

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize <input type="checkbox"/> Deepen <input type="checkbox"/> Production (Start/Resume) <input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing <input type="checkbox"/> Fracture Treat <input type="checkbox"/> Reclamation <input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair <input type="checkbox"/> New Construction <input type="checkbox"/> Recomplete <input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans <input checked="" type="checkbox"/> Plug and Abandon <input type="checkbox"/> Temporarily Abandon
	<input type="checkbox"/> Convert to Injection <input type="checkbox"/> Plug Back <input type="checkbox"/> Water Disposal

13. Describe Proposed or Completed Operations (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once Testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

Elm Ridge Resources, Inc. plugged and abandoned the CBU #72 on May 27, 2003 as follows:
SEE ATTACHED SHEET FOR DETAILS



Certified Return Receipt #

14. I hereby certify that the foregoing is true and correct

Name (Printed/Typed)

Trudy Grubelnik

Title

Production Technician

Signature

Date

May 30, 2003

THIS SPACE FOR FEDERAL OR STATE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on reverse)

NMOCD

ACCEPTED FOR RECORD

JUN 16 2003

FARMINGTON FIELD OFFICE

**Elm Ridge Resources Inc.
Plug Abandon Report**

Operator: **Elm Ridge Resources, Inc.**
Date: June 9, 2003
Field: Bisti Lower Gallup
Contractor: Triple P

Well Name: **CBU #72**
Report No.: 1 and 2
Location: Sec. 9, T25N, R12W
Supervisor: Terry Lindeman

Work Summary:

Tuesday, May 27, 2003: MIRU Triple P Rig #8. Plug #1 - Set cement retainer @ 3295'. Pump 120 sx (141.6') Class "B" below retainer and 13 sx (15.34') on top from 4854' to 3145'. Plug #2 - Shoot and squeeze holes @ 1890. Set retainer @ 1827'. Pump 53 sx (62.54') Class "B" from 1890' to 1790' inside and outside casing. Plug #3 - shoot squeeze holes to 1142'. Set retainer @ 1085'. Pump 65 sx (76.7') from 1142' to 1042' inside and outside casing. Plug #4 - shoot squeeze holes to 842'. Set cement retainer @ 792' Pump 53 sx (62.54) Class "B" from 842' to 742' inside and outside casing. SDON

Wednesday, May 28, 2003: Plug #5 - shoot squeeze hole @ 284'. Break circulation. Pump 150 sx (177') Class "B" cement. Circulate cement to surface. Plugging complete.