

Well Name: SAN JUAN 27-5 UNIT #40N

API / UWI 3003929557	Surface Legal Location 016-027N-005W-F	Field Name BLANCO MESAVERDE (PRORATED GAS)	License No.	State/Province NEW MEXICO	Well Configuration Type VERTICAL
Ground Elevation (ft) 6,596.00	Original KB/RT Elevation (ft) 6,608.00	KB-Ground Distance (ft) 12.00	KB-Casing Flange Distance (ft)	KB-Tubing Hanger Distance (ft)	

VERTICAL, Original Hole, 2/27/2018 2:39:23 PM

Vertical schematic (actual)

MD (ftKB) | **TVD (ftKB)**

11.8 | 11.8 | Tubing Hanger; 7 1/16 in; 50.00 lb/ft; J-55; 12.0 ftKB; 13.0 ftKB

12.1 | 12.1 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 13.0 ftKB; 44.3 ftKB

13.1 | 13.1 | Tubing Pup Joint; 2 3/8 in; 4.70 lb/ft; J-55; 44.3 ftKB; 52.4 ftKB

157.5 | 157.5 | OJO ALAMO (final)

158.1 | 158.1 | KIRTLAND (final)

162.1 | 162.1 | FRUITLAND (final)

2,798.9 | 2,797.6 | PICTURED CLIFFS (final)

2,875.0 | 2,873.7 | LEWIS (final)

2,877.0 | 2,875.6 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 52.4 ftKB; 7,694.9 ftKB

2,877.3 | 2,876.0 | HUERFANITO BENTONITE (final)

2,908.1 | 2,906.8 | CHACRA (final)

3,080.1 | 3,078.6 | CLIFFHOUSE (final)

3,199.1 | 3,197.6 | MENEFEE (final)

3,392.1 | 3,390.4 | POINT LOOKOUT (final)

3,515.1 | 3,513.4 | MANCOS (final)

3,556.4 | 3,554.7 | GALLUP (final)

3,556.8 | 3,555.0 | GREENHORN (final)

3,599.7 | 3,598.0 | GRANEROS (final)

3,600.4 | 3,598.6 | DAKOTA (final)

3,605.0 | 3,603.2 | Tubing Pup Joint; 2 3/8 in; 4.70 lb/ft; J-55; 7,694.9 ftKB; 7,697.0 ftKB

3,888.8 | 3,886.9 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,697.0 ftKB; 7,728.4 ftKB

3,901.6 | 3,899.7 | Pump Seating Nipple; 2 3/8 in; 6.00 lb/ft; J-55; 7,728.4 ftKB; 7,729.5 ftKB

3,909.1 | 3,907.3 | Mule Shoe; 2 3/8 in; 6.00 lb/ft; J-55; 7,729.5 ftKB; 7,730.4 ftKB

4,358.9 | 4,357.0 | PBTD; 7,832.0

4,725.1 | 4,723.0 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

5,048.9 | 5,046.8 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

5,206.0 | 5,203.9 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

5,340.9 | 5,338.7 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

5,416.0 | 5,413.8 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

5,573.2 | 5,570.9 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

5,745.1 | 5,742.8 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

6,065.9 | 6,063.6 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

6,744.1 | 6,741.6 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

7,373.4 | 7,370.7 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

7,385.8 | 7,383.2 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

7,509.8 | 7,507.1 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

7,567.9 | 7,565.2 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

7,592.8 | 7,590.1 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

7,596.1 | 7,593.4 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

7,636.2 | 7,633.4 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

7,694.9 | 7,692.1 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

7,697.2 | 7,694.4 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

7,702.1 | 7,699.3 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

7,728.3 | 7,725.6 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

7,729.7 | 7,726.9 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

7,730.3 | 7,727.6 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

7,806.1 | 7,803.3 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

7,832.0 | 7,829.2 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

7,832.3 | 7,829.6 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

7,833.0 | 7,830.2 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB

7,834.0 | 7,831.2 | Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 7,730.4 ftKB