Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB NO. 1004-0137
Expires March 31, 2007

5. Lease Serial No.

abandoned well. Use Form 3160-3 (APD) for such proposals. SUBMIT IN TRIPLICATE - Other instructions on reverse side 7. If Unit or CA/.	# 3S pol, or Exploratory Area cland Coal Parish, State NM ER DATA Water Shut-Off Well Integrity X Other Ser Coard approximate duration thereof. pertinent markers and zones. shall be filed within 30 days m 3160-4 shall be filed once
Type of Well Gil Well Gother	dd No. # 3S Sol, or Exploratory Area Cland Coal Parish, State NM ER DATA Water Shut-Off Well Integrity X Other Ser Coal Approximate duration thereof. pertinent markers and zones. shall be filed within 30 days m 3160-4 shall be filed once
Oil Well X Gas Well Other S.	# 3S pol, or Exploratory Area cland Coal Parish, State NM ER DATA Water Shut-Off Well Integrity X Other Ser Coard approximate duration thereof. pertinent markers and zones. shall be filed within 30 days m 3160-4 shall be filed once
Name of Operator	# 3S pol, or Exploratory Area cland Coal Parish, State NM ER DATA Water Shut-Off Well Integrity X Other Ser Coard approximate duration thereof. pertinent markers and zones. shall be filed within 30 days m 3160-4 shall be filed once
Energen Resources Corporation 3a. Address 2198 Bloomfield Highway, Farmington, NM 87401 4. Location of Well (Footage, Sec. T., R. M., or Survey Description) Sec. 25, T3ON, R1OW 760' FSL, 670' FEL NMPM 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER TYPE OF SUBMISSION TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Acidize Casing Repair After Casing Fracture Treat Recomplete Casing Repair New Construction Recomplete Convert to Injection Plug Back Water Disposal 3. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and are if the Bond under which the work will be performed or provide the Bond No. on file with BLMRAR Acquired subsequent reports following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a For testing has been completed. Final Abandonment Notices shall be filed only after all requirements, incling reclamation, have been completed. Final Abandonment Notices shall be filed only after all requirements, incling reclamation, have been completed. Final Abandonment Notices shall be filed only after all requirements, incling reclamation, have been completed. Final Abandonment Notices shall be filed only after all requirements, incling reclamation, have been completed. Final Abandonment Notices shall be filed only after all requirements, incling reclamation, have been completed. Final Abandonment Notices shall be filed only after all requirements, incling reclamation, have been completed. Final Abandonment Notices shall be filed only after all requirements, incling reclamation, have been completed. Final Abandonment Notices shall be filed only after all requirements, incling reclamation, have been completed. Final Abandonment Notices shall be filed only after all requirements, incling reclamation, have been completed. Final Abandonment Notices shall be filed only after all requirements, incling reclam	ool, or Exploratory Area cland Coal Parish, State NM ER DATA Water Shut-Off Well Integrity X Other Ser Coard pertinent markers and zones, shall be filed within 30 days m 3160-4 shall be filed once
38. Address 2198 Bloomfield Hichway, Farmington, NM 87401 4. Location of Well (Footage, Sec., T., R. M., or Survey Description) 58cc, 25, T30N, R10W 760' FSL, 670' FEL NMPM 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHE TYPE OF SUBMISSION 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHE TYPE OF SUBMISSION 13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and are if the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all p Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports following completion of the involved operations. If the operation results in a multiple completion completed of the involved operations. If the operation results in a multiple completion or completed of final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed. Plug down 04/08/06 TD:2730' PBTD:2668' Drill 7.875" hole to 2730'. Run 61 jts. 5.50" 15.5# J-5 set § 2715'. RU Halliburton. Cement first stage with 100 sks Class B, 5#/sk gilsonite, 1 (124 cu.ft.). Plug down 04/08/06. Circulate 22 bbls cement to surface. Circulate 22 bbls cement to surface. Circulate 22 bbls cement to surface. ND BOP. Release rig on 04/09/06. Will test completion.	ool, or Exploratory Area cland Coal Parish, State NM ER DATA Water Shut-Off Well Integrity X Other Ser Coard pertinent markers and zones, shall be filed within 30 days m 3160-4 shall be filed once
2198 Bloomfield Highway, Farmington, NM 87401 (505) 325-6800 10 Field and Polar Control (Floring Research Control (Floring	Parish, State Parish, State NM ER DATA Water Shut-Off Well Integrity X Other Ser Corresponding to the read of pertinent markers and zones, shall be filed once
Basin Fruitd Sec. 25, T30N, R10W 760' FSL, 670' FEL NMPM 11. Country or Pr. San Juan 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHE TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent	Parish, State NM ER DATA Water Shut-Off Well Integrity X Other Ser Corr pproximate duration thereof. pertinent markers and zones. shall be filed once markers and days m 3160-4 shall be filed once
Sec. 25, T30N, R10W 760' FSL, 670' FEL NMPM 11. County or Pr. San Juan 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHE TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent	Parish, State NM ER DATA Water Shut-Off Well Integrity X Other Ser Correspondent and zones, shall be filed within 30 days m 3160-4 shall be filed once
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHE TYPE OF SUBMISSION Notice of Intent	Water Shut-Off Well Integrity Wother Ser Corr Other Deproximate duration thereof. pertinent markers and zones. shall be filed within 30 days m 3160-4 shall be filed once
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHE TYPE OF SUBMISSION Notice of Intent	Water Shut-Off Well Integrity Other Ser Csriv Other Ser Csriv Approximate duration thereof. pertinent markers and zones. shall be filed within 30 days m 3160-4 shall be filed once
TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent	Water Shut-Off Well Integrity X Other Ser Corr pproximate duration thereof. pertinent markers and zones. shall be filed within 30 days m 3160-4 shall be filed once
Notice of Intent Acidize	Well Integrity Ser Control Other Ser Control pproximate duration thereof. pertinent markers and zones. shall be filed within 30 days m 3160-4 shall be filed once
Alter Casing Fracture Treat Reclamation Alter Casing Fracture Treat Reclamation Recomplete Subscription R	Well Integrity Ser Control Other Ser Control pproximate duration thereof. pertinent markers and zones. shall be filed within 30 days m 3160-4 shall be filed once
Casing Repair New Construction Recomplete 2 2 2 2 2 2 2 2 2	pproximate duration thereof. pertinent markers and zones. shall be filed within 30 days m 3160-4 shall be filed once
Casing Repair New Construction Recomplete 2	pproximate duration thereof. pertinent markers and zones. shall be filed within 30 days m 3160-4 shall be filed once
3. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and are If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all proposal is to deepen directionally or recomplete the Bond No. on file with BLM/BIA. Required subsequent reports following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Fort testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completering that the final site is ready for final inspection.) 04/08/06 TD:2730' PBTD:2668' Drill 7.875" hole to 2730'. Run 61 jts. 5.50" 15.5# J-5 set @ 2715'. RU Halliburton. Cement first stage with 100 sks Class B, 5#/sk gilsonite, 1 (124 cu.ft.). Plug down @ 10:00 pm on 04/07/06. Circulate 2 bbls cement to surface. Cir stages. Cement second stage with 410 sks 65/35 Class B poz, 6% gel, 2% Cacl2, 10#/sk gils flocele tailed by 50 sks Class B, 5#/sk gilsonite, 1/4#/sk flocele (989 cu.ft.). Plug down 04/08/06. Circulate 22 bbls cement to surface. ND BOP. Release rig on 04/09/06. Will test completion.	pproximate duration thereof, pertinent markers and zones, shall be filed within 30 days m 3160-4 shall be filed once
Convert to Injection Plug Back Water Disposal Convert to Injection Injectio	pertinent markers and zones. shall be filed within 30 days m 3160-4 shall be filed once
Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and are lift the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all particular the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports: following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed that the final site is ready for final inspection.) 04/08/06 TD:2730' PBTD:2668' Drill 7.875" hole to 2730'. Run 61 jts. 5.50" 15.5# J-5 set @ 2715'. RU Halliburton. Cement first stage with 100 sks Class B, 5#/sk gilsonite, 1 (124 cu.ft.). Plug down @ 10:00 pm on 04/07/06. Circulate 2 bbls cement to surface. Cir stages. Cement second stage with 410 sks 65/35 Class B poz, 6% gel, 2% Cacl2, 10#/sk gils flocele tailed by 50 sks Class B, 5#/sk gilsonite, 1/4#/sk flocele (989 cu.ft.). Plug down 04/08/06. Circulate 22 bbls cement to surface. ND BOP. Release rig on 04/09/06. Will test completion.	pertinent markers and zones. shall be filed within 30 days m 3160-4 shall be filed once
If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all p Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports of following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Forresting has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been complete determined that the final site is ready for final inspection.) 04/08/06 TD:2730' PBTD:2668' Drill 7.875" hole to 2730'. Run 61 jts. 5.50" 15.5# J-5 set @ 2715'. RU Halliburton. Cement first stage with 100 sks Class B, 5#/sk gilsonite, 1 (124 cu.ft.). Plug down @ 10:00 pm on 04/07/06. Circulate 2 bbls cement to surface. Cir stages. Cement second stage with 410 sks 65/35 Class B poz, 6% gel, 2% Cacl2, 10#/sk gils flocele tailed by 50 sks Class B, 5#/sk gilsonite, 1/4#/sk flocele (989 cu.ft.). Plug dow 04/08/06. Circulate 22 bbls cement to surface. ND BOP. Release rig on 04/09/06. Will tes completion.	pertinent markers and zones. shall be filed within 30 days m 3160-4 shall be filed once
(124 cu.ft.). Plug down @ 10:00 pm on 04/07/06. Circulate 2 bbls cement to surface. Circulate 2 cement second stage with 410 sks 65/35 Class B poz, 6% gel, 2% CaCl2, 10#/sk gils flocele tailed by 50 sks Class B, 5#/sk gilsonite, 1/4#/sk flocele (989 cu.ft.). Plug dow 04/08/06. Circulate 22 bbls cement to surface. ND BOP. Release rig on 04/09/06. Will tes completion.	55 LT&C casing,
stages. Cement second stage with 410 sks 65/35 Class B poz, 6% gel, 2% CaCl2, 10#/sk gils flocele tailed by 50 sks Class B, 5#/sk gilsonite, 1/4#/sk flocele (989 cu.ft.). Plug dow 04/08/06. Circulate 22 bbls cement to surface. ND BOP. Release rig on 04/09/06. Will tes completion. APR 2006	
flocele tailed by 50 sks Class B, 5#/sk gilsonite, 1/4#/sk flocele (989 cu.ft.). Plug dow 04/08/06. Circulate 22 bbls cement to surface. ND BOP. Release rig on 04/09/06. Will tes completion. APR 2006	
04/08/06. Circulate 22 bbls cement to surface. ND BOP. Release rig on 04/09/06. Will tes completion. APR 2006	
APR 2006	-
APR 2006	st casing during
Old Tage	2006 0
Old Tage	
DIV. J	<u> </u>
	R 2
	20 PF RECEIVE
	PM
	PA TOTAL
14. I hereby certify that the foregoing is true and correct Name (Printed Typed) Title	
Name (Printed/Typed) Yicki Donaghey Regulatory Analyst	<u> </u>
	TEPTED TEPTED
THE SPACE FOR FEDERAL OR STATE OFFICE USE	THE PROPERTY AND ASSESSMENT OF THE PARTY OF
Approved by Title Date	
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.