UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT  SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals)  1. Oil Well [] Gas Well [] Other []		5. Lease  NMNM-03551  6. If Indian, Allottee or Tribe Name  7. Unit Agreement Name  8. Well Name and No.
GAS WELL		BREECH "E" 79
2. Name of Operator:  Caulkins Oil Company		9. API Well No. 30-039-29419-00S1
3. Address of Operator: (505) 334-4323		10. Field and Pool, Exploratory Area
1409 W. Aztec Blvd. Ste B7, Aztec, NM 87410 4. Location of Well (Footage, Sec., Twp., Rge.)		BASIN DAKOTA  11. Country or Parish, State
2595' F/N 1975' F/E SEC. 1-26N-6W		Rio Arriba Co., New Mexico
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF N		
TYPE OF SUBMISSION	TYPE OF ACTION	OTICE, REPORT, OR OTHER DATA
Notice of Intent	[ ] Abandonment	[ ] Change of Plans
[X] Subsequent Report	[ ]Recompletion [ ] Plugging Back [ ] Casing Repair	[ ] New Construction [ ] Non-Routine Fracturing [X] Water Shut-Off
[ ] Final Abandonment Notice	[ ] Altering Casing	[ ] Conversion to Injection
17. Describe Proposed or Completed Operations:	[ ] Other	[ ] Dispose Water
11-10-05 Rigged up.  T. I. H. with 4 3/4" bit on 2 3/8" tubing.		
Tagged cement at 3970'.  Drilled out stage tool at 4014'.  Continued in hole, tagged cement at 5995'.  Drilled out stage tool at 6089". LeD3 2'  Continued in hole, tagged cement at 7698'.  Drilled out cement to TD at 8019'.  11-15-05  Rolled hole with KCL water.  Pressure tested casing to 4000#, held OK.  T. O. H. sanding back 2 3/8" tubing.		27 PM 12 RECEIVED ARMINGTON
(continued on page 2)  NOTE: The format is issued in lieu of U.S. BLM Form 3160-5		
18. I HEREBY CERTIFY THE FOREGOING IS TRUE AND CORRECT		
SIGNED: Rolert 1 Vergue TITLE: Superintendent DATE: December FOR RECORD		
APPROVED BY:	TITI D.	DEC 2 9 2005
CONDITIONS OF APPROVAL, IF ANY	TITLE:	FARMING I UM FIELD OFFICE BY

Z

Caulkins Oil Company BLM Sundry Notice Breech "E" 79 December 21, 2005 Page 2

11-16-05 Rigged up Bluejet.
Ran CBL, TD to surface.
Bond log shows cement from TD to 5806' and 4048' to 3405'.
Ran GSL, TD to 4000'
Perforated Dakota zone with 30 select fire holes, 7785' – 7988'.

11-17-05 T. I. H. with 2 3/8" tubing.
T. O. H. laying down tubing.

11-29-05 Flowed well back through 3/4" choke for 4 hours.
T. I. H. with new 2 3/8" tubing.

11-30-05 Tagged sand at 7965'.

Landed tubing on doughnut at 7947'.

Rigged down.