Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
OM B No. 1004-0137
Expires: March 31, 2007

5. Lease Serial No.	
---------------------	--

Bonesto of Bitties with a top side	5. Lease Serial No.		
SUNDRY NOTICES AND REPORTS	ON WELLS SF 079042		
Do not use this form for proposals to drill on abandoned well. Use Form 3160-3 (APD) for			
SUBMIT IN TRIPLICATE- Other instructions	on reverse side. 7. If Unit or CAVA greening, Name, and/or No.		
I. Type of Well Gas Well Other	7 O Northeast Blanco Unit 8. Well Name and No.		
2. Name of Operator Devon Energy Production Company, L.P.	NEBU 461A 9. API Well No.		
	No. (include area code) 30-045-32374 APR 2008		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	Basin Fruitland Coal OF CONS. DIV.		
710' FNL & 1,130' FEL, NE NE, Unit A, Sec. 12, T30N- R8W	11. County or Parish, State 38		
12. CHECK APPROPRIATE BOX(ES) TO INDICAT	E NATURE OF NOTICE, REPORT, OR OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION		
☐ Acidize ☐ Deepen ☐ Notice of Intent ☐ Alter Casing ☐ Fracture ☐ Subsequent Report ☐ Casing Repair ☐ New Co	Treat Reclamation Well Integrity onstruction Recomplete Other Casing & Cement d Abandon Temporarily Abandon		
testing has been completed. Final Abandonment Notices shall be filed only afted determined that the site is ready for final inspection.) Drilled 12 1/4" hole to 290' on 2/14/06, set 8 jts of 9 5/8", H-40, ST8 CaC1 and 1/4# PSX Floseal. Circulated 18 bbls of cement to surfact Drilled 8 3/4" hole to 3,690' on 2/20/06, set 83 jts of 7", J-55 LT&C, Gel, 5# Gilsonite, 1/4# Flocele, 1/10% CFR 3, 4/10% Halad 344 and surface. Tested casing to 1500 psi. Drilled 6 1/4" hole to 4,117' TVD on 3/8/06. Underreamed hole to 1 near wellbore material. On 3/22/06, set 12 jts 5 1/2" 15.5, J-55 liner phasing, 4 SPF, total of 352 holes from 3,691' to 3,983'. Landed 2 3	23# casing at 3,663!. Cemented lead w/625 sx (160 bbls) 50/50 POZ w/3% tail w/75 sx (16 bbls) STD, 4/10% Halad 344. Circulated 40 bbls of cement to 11" from 3,690' to 4,117'. Utilized natural and air assisted surges to remove at 4,117' with liner top at 3,618'. Perforated liner with size 0.51" holes, 120°		
14. Thereby certify that the foregoing is true and correct Name (Printed/Typed)			
Melisa Zimmerman	Title Senior Operations Technician		
Signature M.S.Z.	Date 4-17-06		
HIS SPACE FOR FEDERAL OR STATE OFFICE USE			
Approved by Conditions of approval, if any, are attached. Approval of this notice does not was certify that the applicant holds legal or equitable title to those rights in the subject which would entitle the applicant to conduct operations thereon.	lease Office		
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for a States any false, fictitious or fraudulent statements or representations as to anyma	ny person knowingly and willfully to make to any department or a company the line of the l		

(Instructions on page 2)

MMOCD

APR 2 5 2006

FARMINGTON FELDOFFICE