Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0137 Expires: July 31, 2010

5. Lease Serial No.

NMSF079049

Farmingto
SUNDRY NOTICES AND REPORTS ON WELLSureau of La
Do not use this form for proposals to drill or to re-enter an
abandoned well. Use Form 3160-3 (APD) for such proposals.

	Farming	ton Field	NMSF079049	
SUNDRY NOTICES AND REPORTS	ON WELLSureau of	6. If Indian, Allottee or Tr	ibe Name	
Do not use this form for proposals to drill				
abandoned well. Use Form 3160-3 (APD) fo	or such proposals.			
SUBMIT IN TRIPLICATE - Other instructions	on page 2.	7. If Unit of CA/Agreemen	nt, Name and/or No.	
I. Type of Well				
Oil Well X Gas Well Other		8. Well Name and No.		
2. Name of Operator		9. API Well No.	San Juan 28-6 Unit 205E	
Hilcorp Energy Company			80-039-30120	
Ba. Address 3b. Phone No. (include area cod		10. Field and Pool or Exploratory Area		
382 Road 3100, Aztec, NM 87410	505-599-3400	Blanco M	esaverde/Basin Dakota	
Location of Well (Footage, Sec., T.,R.,M., or Survey Description)		11. Country or Parish, Star		
Surface Unit A (NENE) 20'FNL & 370' FEL, Sec.	9, 127N, R06W	Rio Arriba	, New Mexico	
40. OUEQUETHE ADDRODDIATE DOV(50) TO INI	DIGATE NATURE OF A	HOTIOF DEPORT OF O	THE DATA	
12. CHECK THE APPROPRIATE BOX(ES) TO INI	JICATE NATURE OF I	NOTICE, REPORT OR O	THER DATA	
TYPE OF SUBMISSION	TYPE OF A	ACTION		
Notice of Intent Acidize Dec	epen	Production (Start/Resume)	Water Shut-Off	
Alter Casing Fra	cture Treat	Reclamation	Well Integrity	
X Subsequent Report Casing Repair Ne	w Construction X	Recomplete	Other	
Change Plans Plu	g and Abandon	Temporarily Abandon		
Final Abandonment Notice Convert to Injection Plu	g Back	Water Disposal		
following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once Testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.) 10/8/18 MIRU. ND WH. NU BOP. PT BOP, test good. Pull tbg hanger & TOOH w/2-3/8" tbg. SDON. 10/9/18 TIH w/4.5" csg scraper to 5760'. TOOH w/csg scraper. TIH w/4.5" CIBP set @ 5650'. Clean & load well. PT 4.5" csg & CIBP to 2000#/30 mins, test good. TOOH. ND BOP. Top off csg & PT to 4000#/30 mins, test good. NU WH. RD. Rig released. 10/31/18 Remove tree & master valve. Install 7" 5K frac stack. Load csg & frac stack. PT csg & frac stack to 4000#, test good. 11/6/18 RU W/L. Perf PT Lookout & Lower Menefee @ 5270', 5269', 5268', 5262', 5261', 5260', 5245', 5244', 5237', 5236', 5224', 5211', 5200', 5196', 5191', 5173', 5172', 5168', 5161', 5156', 5152', 5142', 5138', 5136', 5128', 5120', 5097', 5089', 5084', 5075', 5054', 5051', 5038', 5037', 5017', 5016', 4997', 4996', 4995', 4981' (1 SPF) for a total of 42, 0.34" dia holes. CONTINUED on Page 2 BY:				
14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)				
Tammy Jones Title Operations/Regulatory Technician - Sr.				
Signature Jammy Jones	Date 11/13/2	2018	NMOCD	
THIS SPACE FOR FEDERAL OR STATE OFFICE USE NOV 3 0 2018				
Approved by				
	Title		DISTRICT III	
Conditions of approval, if any, are attached. Approval of this notice does not warrant of that the applicant holds legal or equitable title to those rights in the subject lease which partitle the applicant to conduct expertions thereon.				

entitle the applicant to conduct operations thereon.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

11/7/18 Broke down well with water & 500 gal 15% HCL. Foam FRAC'D PT Lookout & Lower Menefee w/ 150,200# 40/70 sand & 52,337 gal slickwater & 1.56 million SCF N2 70 quality. avg rate = 55 BPM, avg PSI = 2008. Dropped 13 bio-balls with 1/2 of sand pumped. TIH & set frac plug @ 4750'. PT plug to 2900#, ok.

11/8/18 Perf Cliffhouse @ 4737', 4722', 4716', 4715', 4707', 4706', 4698', 4693', 4686', 4675', 4674', 4655', 4649', 4636', 4631', 4622', 4598', 4593', 4584', 4583' (1 SPF) for a total of 20, 0.34" dia holes. Broke down well with water & 500 gal 15% HCL. Foam FRAC'D Cliffhouse w/ 150,800# 40/70 sand & 46,847 gal slickwater & 1.42 million SCF N2 70 quality. avg rate = 50 BPM, avg PSI = 2205. TIH & set isolation plug @ 4430'. RD W/L.

11/9/18 MIRU. ND frac stack. NU BOP & PT, test good. TIH w/3-3/4" bit tag plug @ 4430'. Est. circ & D/O isolation plug @ 4430'. C/O fill. D/O frac plug @ 4750'. PUH & flow back well.

11/10/18 TIH & tag @ 5230'. Swivel up & D/O CIBP @ 5650'. TIH tag PBTD @ 7390'. PUH w/bit. Flow back well to tank.

11/11/18 TOOH w/3-3/4" bit. TIH w/BHA to 7380', unload well. PUH & Land 231 jts 2-3/8" 4.7# J-55 EUE T&C upset tubing @ 7291', SN @ 7289'. ND BOP. NU WH. RD. Rig released.

Well is now producing as Blanco Mesaverde/Basin Dakota commingle under DHC4029AZ.