This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator Hilco	rp Energy	y Company	L	ease Name	e HELE	N JACKSON		Well No. 2A
Location of We	II: Unit L	etter O	Sec 33	Twp	029N	Rge	009W API	# 30-045-23294
	Name of Reservoir or Pool			Type of Prod			Method of Prod	Prod Medium
Upper Completion	MV			Gas			ial Lift	Tubing
Lower Completion	DK			Gas			ial Lift	Tubing
			Pre-FI	ow Shut-In	Pressu	ire Data		
Upper Completion	Hour, Date, Shut-In 5/7/2019			Length of Time Shut-In			ss. PSIG 251	Stabilized?(Yes or No) Yes
Lower Completion	Hour, Date, Shut-In 5/7/2019						ss. PSIG 240	Stabilized?(Yes or No) Yes
				Flow Tes	t No. 1			
Commenced a	at:	5/13/2019		2	Zone Pro	oducing (Upper	r or Lower): UF	PPER
Time Lapsed Time		Lapsed Time	F	PRESSURE		Prod Zone		
(date/time	9)	Since*	Upper z	one Lowe	er zone	Temperature	Remarks	
5/13/2019 11:30 AM		11	240		251		Started the flow test on the lower DK zone down the meter at 11:30 AM.	
5/13/2019 11:42 AM		11	240		190		Reached the 20% crossover in 22 minutes.	
5/14/2019 11:30 PM		47	240		86		24 hour flow readings.	
Production rate	during te	est						
Dil: BPOD Based on: Bb			Bbls. Ir	ls. In Hrs.			Grav.	GOR
Gas		MCFPD; Test	thru (Orifice	or Meter)				
			Mid-T	est Shut-In	Pressu	ıre Data		
Upper Completion	Hour, Date, Shut-In Hour, Date, Shut-In			d-Test Shut-In Pressure Dat Length of Time Shut-In			ss. PSIG	Stabilized?(Yes or No)
Lower Completion							ss. PSIG	Stabilized?(Yes or No)

(Continue on reverse side)



Northwest New Mexico Packer-Leakage Test

Flow Test No. 2

Commenced at:		Zone Producing (Upper or Lower)							
Time	Lapsed Time	PRES	SURE	Prod Zone					
(date/time)	Since*	Upper zone	Lower zone	Temperature		Remarks			
-									
		•							
			1	<u> </u>	<u>l</u>				
.									
Production rate duri	ng test								
Oil:BP0	DD Based on:	Bbls. In	Hrs.		Grav.	GOR			
	MCFPD; Test ti								
						·			
Remarks:									
Well reached 20% c	rossover in 22minutes.			• • • • • • • • • • • • • • • • • • • •					
		٨							
I hereby certify that t	the information herein o	contained is true	and complete	to the best of	mv knowledo	ıe			
	- 4 . 4								
Approved: 21	- / / /	20 /9	Operat	or: Hilcorp	Energy Comp	any			
New Mexico Oil Conservation Division				Brad Griswo	old				
By: MA	1 them		Title:	Multi-Skilled	Operator				
Daniel	ty Oil & Gas Inspe	ector,							
Title: Depu	District #3		Date: _	Monday, Ma	y 20, 2019				

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual
 completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion.
 Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or
 chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or
 the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when
 requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).