

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator

**BURLINGTON  
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

835' FSL, 1110' FWL, Sec. 15, T-27-N, R-9-W, NMPM

5. Lease Number  
NMNM011808A

6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name

8. Well Name & Number

Skelly Govt 2

9. API Well No.

30-045-06454

10. Field and Pool

Basin Dakota

11. County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

05/28/03 MIRU. Spot rig and equip. SDFN.

05/29/03 RU. Blow tbg & csg down. Kill tbg w/20 bbls wtr. NU WH, NU BOP. Work tbg from 35K to 60K. Freeport 2 3/8" tbg @ 6281'. Run in with cutter cut off @ 6281'. TOOH w/tbg.

05/30/03 TIH w/csg scraper 2 3/8" tbg, CO csg. Blow Well. Braden Head leaking. 6" nipple rotted. Change nipple in BH. Blow Well. TIH to 3500', could not blow well around. TOOH. TIH W/tbg to 6580'. TOOH w/2 3/8" tbg. SDFN.

06/02/03 TIH, Set plug @ 6543'. Test plug @ 900 psi, OK. TOOH to 4616', set pkr. Test to 750 PSI, failed. TIH to 5246', test to 750', failed. TIH to 5875', set pkr, test to 750 PSI, OK. TOOH to 5559', Test failed. TIH to 5813' test failed, Test @ 5844', Test. Test isolated hole between 5844' to 5875'. Test to 750'. TOOH to 1905', set pkr, test down casing fluid. TOOH to 960', test down casing. TOOH. RU Wireline. Run CBL log from 6543 to surface. RD WL. SDFN

06/03/03 Dig out from around WH. Hole in csg 2' below WH. Run Pkr in hole 15'. Test tbg head seals to 750 PSI, OK. TIH w/RBP & Pkr, 2 3/8" tbg set RBP @ 5817'. Test RBP to 750 PSI, OK. TOOH, Test csg from 5817' to 4363'. Isolate hole from 4363' to 3230', 1133' of holes. From 3230' to 2195', good csg. From 2195' to 202' 1993' of holes in csg. From 202' to surface test good. SDFN.

14. I hereby certify that the foregoing is true and correct.

Signed Reggie Allen Title Regulatory Supervisor Date 07/15/03  
fsb

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

JUL 15 2003

NMOCD

ADMINISTRATIVE OFFICE

06/04/03 Verbal approval from Steve Mason, BLM to P & A Well. TIH to 6543' w/2 3/8" open ended. Spot 10 SK 2.4 BBL cmt plug 6543' to 6385 158' plug. Pull up to 5743' Spot 12 sk 3 bbl cmt plug 5743' to 5555' 188' plug. Pull up to 3700'. SDFN.

06/05/03 Verbal approval from Steve Mason, BLM to change plug #3. Pull to 4017', spot 46 sks 11.5 bbls cmt from 4017' to 3296' 721' plug pull to 2200'. WOC. TIH to 4040' no cmt plug, pull to 3860', Spot 38 sks 9.5 BBL cmt, Plug 3860' to 3265', pull to 2200'. WOC. TIH, tag @ 3223'. TOOH w/tbg. SDFN

06/06/03 RU WL. Tag cmt @ 3273' pull to 3262 shot 1 squeeze hole, pull out of hole. TIH W/CR & tbg retainer set @ 2081'. Verbal approval from Wayne Townsend, BLM to pump cmt @ 2081'. Pump 45 bbls cmt below retainer sting out pump 8.5 bbls cmt on top retainer cmt Chacra & PC & Fruitland. TOOH W/tbg. WOC. Run tag w WL cmt top @ 1549'. TIH w/tbg to 1470'. Spot 28 bbls cmt over Kirtland & Ojo Alamo. TOH W/tbg. WOC. TIH, tag @ 405' LD tbg. Pump 28 bbls cmt from surface circulated out Bradenhead 2 bbls. ND. ND BOP.  
Rig Down, Clean Rig Pit. Move off location.