

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0135
Expires November 30, 2000

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an
abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1. Type of Well

☒ Oil Well ☐ Gas Well ☒ Other water source well

2. Name of Operator

HART OIL & GAS INC

3a. Address

P.O. Box 385 Rongdy CO 81648

3b. Phone No. (include area code)

(970) 629-1116

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

652' FSL + 3250' FWC
2050
Sec 14 T32N R18W

5. Lease Serial No.

14-20-603-584

6. If Indian, Allottee or Tribe Name

Navajo

7. If Unit or CA/Agreement, Name and/or No.

RECEIVED

8. Well Name and No.

C-18

9. API Well No.

30-045-28520

10. Field and Pool, or Exploratory Area

Mesa Gallup

11. County or Parish, State

N.M.
Son Juan County N.M.

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

This well will be plugged by 12-31-06.
All plugs set will be in compliance of All
regulations.

14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

Andrew B. Saied

Title President

Signature

Andrew B. Saied

Date 5-29-06

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Original Signed: Stephen Mason

Title

Date

JUN 01 2006

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC

8

Plug and Abandonment of Navajo C #18
14-32N-18W API#3004528520

Lease # 14-20-603-584

- 1) Set a BP @ 3000' cap with 100' of cement to isolate the Entrada Perfs.
- 2) Place a cement plug from 2052' to 1952' to cover the Morrison top.
- 3) Place a cement plug from 1846' to 1746' to cover the Dakota top.
- 4) Place a cement plug from 1095' to 995' to cover the Gallup top.
- 5) Set a cement plug from 100' to surface to cover the 9 5/8" casing shoe to surface.