Form 3160-5 (August 1999)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

	Budget Bureau No. 1004-0135 Expires: November 30, 2000
5.	Lease Serial No.
1	NMNM - 112957
6.	If Indian Allottee or Tribe Name

FORM APPROVED

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an
abandoned well. Use Form 3160-3 (APD) for such proposals

States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

abandoned well. Use Form 316		ıls.	o. If fiduli, Another of Tribe Palife		
	7. If Unit or CA/Agreement, Name and/or No.				
SUBMIT IN TRIPLICATE - Other instructions on reverse side					
1. Type of Well	8. Well Name and No.				
☐ Oil Well ☑ Gas Well ☐	TSAH TAH 33 #1				
2. Name of Operator ROSETTA RESOURCES	9. API Well No. 30-045-33608				
3a. Address c/o Walsh Engingeeirng & Production Corp	10. Field and Pool, or Exploratory Area				
7415 East Main St. Farmington, NM 87402	BASIN FRUITLAND COAL				
4. Location of Well (Footage, Sec., T., R., M., or Survey D	11. County or Parish, State				
1378' FNL & 1620' FEL SEC 33 T25N R10W	San Juan, New Mexico				
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA					
TYPE OF SUBMISSION	TYPE	OF ACTION			
☐ Notice of Intent ☐ Acidize ☐ Alter Casing	☐ Deepen ☐ Fracture Treat	Production (S	art/Resume)		
✓ Subsequent Report			Other CASING/CEMENT		
Change Plans			<del></del>		
☐ Final Abandonment Notice ☐ Convert to In	jection Plug Back	☐ Water Dispose	al		
and the operator has determined that the site is ready for final inspection.)  05/16/06 spud 8-3/4" surface hole. Drilled to 125'KB. Ran 3 jts (115.28') of 7", 17#, J-55, ST&C new LS casing and set casing at 121'KB. Cemented with 60sx (71 cu. ft.) of Cl "B", 3% CaCl <sub>2</sub> and 1/4 #/sk celloflake. Circulated 5 bbls of good cement to surface.  05/17/06 Nippled up the BOP and pressure tested the casing and BOP to 1500 psi.  05/14/06 TD 6-1/4" hole at 1905' . 05/15/06 Ran 46 jts (1893.72') of 41/2", 11.6#, L/S R-3, LT&C production casing and landed at 1899.47' KB. Insert float is at 1878'KB. Cemented with 150 sx (309cu.ft.) of Type 5, 2% sodium metasillicate, 1/4#/sk celloflake, followed by 75 sx (89 cu. ft.) of Type 5, with 1/4# celloflake. Bumped plug to 1100 psi. Circulated 20 bbls of cement to the surface.					
14. Thereby certify that the foregoing is true and correct					
Name (Printed/Typed)		_1.	4 <i>ij</i> : 5: 0		
Paul C. Thompson, P.E.	Title	49	= /		
Signature Paul C. Thurst	Date	and the second and			
THIS SPACE FOR FEDERAL OR STATE OFFICE USE					
			MAY 2 5 2006		
Approved by	Title		Date Date		
Conditions of approval, if any, are attached. Approval of this notice certify that the applicant holds legal or equitable title to those rights which would entitle the applicant to conduct operation thereon		ce	FARMATON FX DOFFICE		
which would entitle the applicant to conduct operation thereon.  Title 18 U.C.S. Section 1001 and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make any department or agency of the United					

