District I 1625 N. French Dr., Hobbs, NM 88240 District II
1301 W. Grand Avenue, Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe

Form C-144

June 1, 2004

Oil Conservation Division

Pit or Below-Grade Tank Registration or Closure

1220 South St. Francis Dr. office Santa Fe, NM 87505

Is pit or below-grade tank covered by a "general plan"? Yes 🔀 No 🗌 Type of action: Registration of a pit or below-grade tank 🔲 Closure of a pit or below-grade tank 🔀								
	ne: <u>(505)326-9200</u> e-mail address:							
	Longitude							
Surface Owner: Federal 🗌 State 🗎 Private 🗀 Indian 🗀		(A)						
Pit Type: Drilling Production Disposal Workover Emergency Lined Unlined Liner type: Synthetic Thicknessmil Clay	Below-grade tank Volume:bbl Type of fluid: Construction material: Double-walled, with leak detection? Yes If not	explain why not. RECEIVED						
Pit Volumebbl Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet 50 feet or more, but less than 100 feet	(20 points) (292 SZ VZ VZ SZ VZ						
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes No	(0 points) (20 points) (0 points)						
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more	(20 points) (10 points) (0 points)						
	Ranking Score (Total Points)							
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's your are burying in place) onsite offsite from If offsite, name of facility emediation start date and end date. (4) Groundwater encountered: No 5) Attach soil sample results and a diagram of sample locations and excaval Additional Comments:	(3) Attach a general d	escription of remedial action taken including						
See Attached Documentation	Historia							
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline	of my knowledge and belief. I further certify that t is 🏿 , a general permit 🗀 , or an (attached) alterna	he above-described pit or below-grade tank tive OCD-approved plan .						
Date:	ureC _ Slegg not relieve the operator of liability should the contents the operator of its responsibility for compliance with a	of the pit or tank contaminate ground water or ny other federal, state, or local laws and/or						
Approval: Printed Name/Title Printed Name/Title Signature Symmetry Sell Date: JAN 0 9 2006								

client: BP	BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413			413	LOCATION NO: 80769			
	(505) 632-1199					COCR NO:		
FIELD REPORT	: PIT CL	OSURE	VERIF	ICATIO	ON	PAGE No:	of/_	
LOCATION: NAME: LUOWIA						DATE STARTED: _		
QUAD/UNIT: K SEC: 29						DATE FINISHED:		
QTR/FOOTAGE: 1460 5 /16	00'W 1	VE/SW CONTI	RACTOR: 51 ER	RA (CALVIN	<u> </u>	ENVIRONMENTAL SPECIALIST:	~V	
EXCAVATION APPROX. <u>NA</u> FT. x <u>NA</u> FT. x <u>NA</u> FT. DEEP. CUBIC YARDAGE: <u>NA</u>								
DISPOSAL FACILITY: ON-SITE REMEDIATION METHOD: COSE AS IS								
LAND USE: RANGE-								
FIELD NOTES & REMAR	KS: PIT LOC	ATED APPROX	CIMATELY 2	9 FT.	N70	FROM	WELLHEAD.	
DEPTH TO GROUNDWATER: NEAREST WATER SOURCE: >1000' NEAREST SURFACE WATER: >1000'								
NMOCD RANKING SCORE: NMOCD TPH CLOSURE STD: 5000 PPM								
					= 53.7 ppm CHECK $= 100 ppm RF = 0.52$			
				TIME:	. GAS - 2 <u>≤</u> a	m/pm DATE: _	213/04	
SOIL TYPE: SAND SILTY SAN	D / SILT / SILTY	CLAY / CLAY /	GRAYEL / OTH					
SOIL COLOR: DR. YELL COHESION (ALL OTHERS): NON CO	HESIVE/ SLIGHTLY	COHESIVE / CO	PW/V HESIVE / HIGHLY	COHESIVE				
COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIVE CONSISTENCY (NON COHESIVE SOILS): OOSD (FIRM) DENSE / VERY DENSE								
PLASTICITY (GLAYS): NON PLASTIC				/ HIGHLY PLAST	ric .			
MOISTURE: DRY / CLATS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD CLOSED								
DISCOLORATION/STAINING OBSERV	/ED: YES/NO EXF						(2034)	
HC ODOR DETECTED: YES (NO EX								
SAMPLE TYPE: GRAB COMPOSITE - # OF PTS								
<u>co~1</u>	oucted.							
FIELD 418.1 CALCULATIONS								
SCALE SAMP. TIM	E SAMP. ID	LAB NO.	WEIGHT (g)	mL FREON	DILUT	TION READING	CALC. (ppm)	
0 FT								
PIT PERIMET		٦ _			Pi	T PROFIL	.E	
	T.H.,		VM DING					
- 1	/8.T.B.	SAMPLE	FIELD HEADSPACE	-				
201	7/6	1@ 8	(ppm)					
	7	2 @ 3 @		_				
	7) T	4@						
		5@		-	AJA3	- APPLIC	AD 1 55	
\oplus	201			_	,-0,		75 GC	
WELL ' (D)	1 1			-				
HEAD /				7				
	<u> </u>	LAB SA	AMPLES					
P.D.	\ 	SAMPLE AN	ALYSIS TIME	_1				
~5 T	ovenier steel		_ /3/3		•			
	B. ~ 5′8.6.			-				
P.D. = PIT DEPRESSION; B.G. = BELOW T.H. = TEST HOLE; ~ = APPROX.; T.B. =								
TRAVEL NOTES: CALLOUT: 2/3/04- MORN. ONSITE: 2/3/04-AFTER.								