DISTRICT 1 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410

State of New Mexico **Energy Minerals and Natural Resources**

Oil Conservation Division

For drilling and production facilities, submit to appropriate NMOCD District Office.

For downstream facilities, submit to Santa Fe office

Form C-144 June 1, 2004

District IV 1220 S. St. Francis Dr., Santa Fe. NM 87505

1220 South St. Francis Dr. Santa Fe, NM 87505 Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tan Type of action: Registration of a pit o	k covered by a "general plan"? Yes ⊠ No or below-grade tank □ Closure of a pit or below-gra	∐ ade tank ⊠	
Operator: BP AMERICA PROD. CO. Address: 200 ENERGY COURT, FARMINGTON.	Telephone: (505)-326-9200 e-ma NM 87410 API#: 30-045- 23173 U/L or Qtt/0	oil address:QtrH _ Sec4	
Pit Type: Drilling Production Disposal ABANDON Workover Emergency Lined Unlined Liner type: Synthetic Thickness mil Clay Pit Volume bbl	Below-grade tank Volume:bbl_Type of fluid: / Construction materia: Double-walled, with leak detection? Yes lf	- <u>st.</u> explain why not.	
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet 50 feet or more, but less than 100 feet 100 feet or more	(20 points) (10 points) (0 points)	0
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes No	(20 points)	0
Distance to surface water: (horizontal distance to all wetlands, playas, gation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more	(20 points) (10 points) (0 points)	0
If this is a pit closure: (1) attach a diagram of the facility showing the pit's your are burying in place) onsite offsite offsite, name of facility remediation start date and end date. (4) Groundwater encountered: No offsite sample results and a diagram of sample locations and excavation	. (3) Attach a general Yes If yes, show depth below ground surface	description of remedial	action taken including
Additional Comments: PIT LOCATED APPROXIMATELY PIT EXCAVATION: WIDTH N/Aft., LENGTH PIT REMEDIATION: CLOSE AS IS: ⊠, LANDFARM: □, C	y 78 ft. N2W from we N/Aft., depth N/Aft		EB 2006
Cubic yards: N/A BEDROCK BOTTOM			CONS. DIV.
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline Date:	Signature	s of the pit or tank conta	aminate ground water or
proval: Printed Name/Title CR & GAS INSPECTOR, DIST. SI	gnature Derry Ret	Date: FF	B 2 1 2006_

26.168177 101.10116 **BLAGG ENGINEERING, INC.** LOCATION NO: B1550 P.O. BOX 87, BLOOMFIELD, NM 87413 COCR NO: (505) 632-1199 FIELD REPORT: PIT CLOSURE VERIFICATION PAGE No: TYPE: ABANDIN DATE STARTED: 6/17/05 LS WELL #: 16 LOCATION: NAME: NEIL DATE FINISHED: 6/17/05 4 TWP: 31N RNG: 11W PM: NM CNTY: SJ ST: NM QUAD/UNIT: H SEC: 890 FEL SEINE CONTRACTOR: Prs (Allon ENVIRONMENTAL 1814 FNLY SPECIALIST: EXCAVATION APPROX. <u>NA</u> FT. x <u>NA</u> FT. x <u>NA</u> FT. DEEP. CUBIC YARDAGE: NA CLUSE AS IS __ REMEDIATION METHOD: **DISPOSAL FACILITY:** - BLM 5F-079051 LAND USE: LEASE: PIT LOCATED APPROXIMATELY 78 FT. NZW FROM WELLHEAD. FIELD NOTES & REMARKS: DEPTH TO GROUNDWATER: >/00 NEAREST WATER SOURCE: >/000 NEAREST SURFACE WATER: >/000 NMOCD TPH CLOSURE STD: 5000 PPM NMOCD RANKING SCORE: OVM CALIB. READ. = 52.5 ppm SOIL AND EXCAVATION DESCRIPTION: OVM CALIB. GAS = 100 ppm RF = 0.520730 /am/pm DATE: SOIL TYPE SAND SILTY SAND / SILT / SILTY CLAY / CLAY / GRAVEL / OTHER Life ton COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIVE CONSISTENCY (NON COHESIVE SOILS) LOOSE FIRM / DENSE / VERY DENSE PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD CLOSED MOISTURE: DRY SLIGHTLY MOIST MOIST WET / SATURATED / SUPER SATURATED DISCOLORATION/STAINING OBSERVED: YES NO EXPLANATION - V. Moral Odio SAMPLE TYPE: GRAB COMPOSITE - # OF PTS. 12 x12 x4 Deps Coutlan ADDITIONAL COMMENTS: Use Buther to dill test trouch. Borrom Firm bedrock SS @ FIELD 418.1 CALCULATIONS SCALE WEIGHT (g) | mL FREON | DILUTION READING | CALC. (ppm) SAMP. TIME SAMP, ID LAB NO. FT PIT PROFILE PIT PERIMETER OVM **READING** SAMPLE FIELD HEADSPACE 12 1@ 6 111 2@ 3@ 4@ 5@ 1 12 6 LAB SAMPLES ANALYSIS TIME A Rodvock S.S. P.D. = PIT DEPRESSION; B.G. = BELOW GRADE; B = BELOW T.H. = TEST HOLE; ~ = APPROX.; T.B. = TANK BOTTOM TRAVEL NOTES: CALLOUT: ONSITE:



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 6'	Date Reported:	06-21-05
Laboratory Number:	33373	Date Sampled:	06-17-05
Chain of Custody No:	13890	Date Received:	06-17-05
Sample Matrix:	Soil	Date Extracted:	06-20-05
Preservative:	Cool	Date Analyzed:	06-21-05
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	14.0	0.2
Diesel Range (C10 - C28)	39.8	0.1
Total Petroleum Hydrocarbons	53.8	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Neil LS 16 Abandon Pit.

Analyst C. Oglucu

Mistine M Walten
Review



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 6'	Date Reported:	06-21-05
Laboratory Number:	33373	Date Sampled:	06-17 - 05
Chain of Custody:	13890	Date Received:	06-17-05
Sample Matrix:	Soil	Date Analyzed:	06-21-05
Preservative:	Cool	Date Extracted:	06-20-05
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)	
Benzene	4.0	2.1	
Toluene	216	1.8	
Ethylbenzene	124	1.7	
p,m-Xylene	1,510	1.5	
o-Xylene	381	2.2	
Total BTEX	2,240		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	98.0 %
	1,4-difluorobenzene	98.0 %
	Bromochlorobenzene	98.0 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Neil LS 16 Abandon Pit.

Analyst C. Carrier

Arview Maeters