District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tan Type of action: Registration of a pit o	k covered by a "general plan"? Yes 🔀 No or below-grade tank 🗌 Closure of a pit or below-gr	o 🔲 rade tank 🕱
Operator: BP America Production Company Telephor  Address: 200 Energy Ct, Farmington, NM 87401  Facility or well name: UPPRED LS # LAITH API #: 5  County: San Juan Latitude  Surface Owner: Federal State Private Indian		Sec 13 T 28N R 9W
Pit  Type: Drilling Production Disposal Workover Emergency Lined Unlined Liner type: Synthetic Thickness mil Clay  Pit Volume bbl	Below-grade tank  Volume:bbl Type of fluid:  Construction material:  Double-walled, with leak detection? Yes	 ot, explain why not.
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet 50 feet or more, but less than 100 feet 100 feet or more	(20 points) (10 points) ( 0 points)
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes No	(20 points) ( 0 points)
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more	(20 points) (10 points) ( 0 points)
If this is a pit closure: (1) Attach a diagram of the facility showing the pit' your are burying in place) onsite  offsite  If offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No     (5) Attach soil sample results and a diagram of sample locations and excava   Additional Comments:  See Attached Documentation	Yes I If yes, show depth below ground surface	description of remedial action taken including
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline.  Date:	ture	ts of the pit or tank contaminate ground water or
Approval:  Printed Name/Title  Approval:  Only G. B. GAS WSFCTOR, DIST. 61	Signature Deny	DEC 1 6 2005
	3 of 3	

RP.			NEERING	•	LO	CATION NO:	80005
CLIENT:	P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199				CR NO:	11426	
FIELD REPORT	: PIT CL	OSURE	VERIF	CATIO	N PAG	SE No:	of
LOCATION: NAME: WARE	REN LS	WELL#:	A TYPE	: BLOI			10-9-03
QUAD/UNIT: J SEC: 13	TWP: ZEN RNG	6: 9W PM:	NM CNTY: S.	J ST: N/	<u> </u>		10-9-03
QTR/FOOTAGE: 18505					SPE		IB
EXCAVATION APPROX		<u>//A</u> FT.	x <u> </u>	. DEEP. CU	JBIC YAR	DAGE: _	$\mathcal{O}$
DISPOSAL FACILITY:	<u> </u>		REMEDIA				ASIS
	- Bum						VV V
FIELD NOTES & REMAR			CIMATELY 14	•			
DEPTH TO GROUNDWATER: $\geq u$	<del></del>		>1000		URFACE WA	TER:	000
NMOCD RANKING SCORE:C	2 NMOCD TPH	CLOSURE STD:	5000 PI	<del></del>			
SOIL AND EXCAVATION	N DESCRIPT	<u> 10N:</u>		OVM CALIB.			<u>RF = 0.52</u>
				TIME:	am/p	m DATE: _	
SOIL TYPE: SAND, SILTY SAN SOIL COLOR: Lellow		CLAY / CLAY /	GRAVEL (OTH	EB) /30cl	wik	55	
COHESION (ALL OTHERS): NON C		COHESIVE / CO	HESIVE / HIGHLY	COHESIVE			
CONSISTENCY (NON COHESIVE SO							
PLASTICITY (CLAYS): NON PLASTI DENSITY (COHESIVE <u>CLAYS &amp; S</u> ILT				/ HIGHLY PLAST	IC		
MOISTURE: DRY (SLIGHTLY MOIST	MOIST WET / SAT	URATED / SUPE	R SATURATED			(CL	Q38 Q
DISCOLORATION/STAINING OBSER HC ODOR DETECTED: YES NO E							
SAMPLE TYPE GRABI COMPOSITI	* # OF PTS					<del></del>	
DDITIONAL COMMENTS:	X12 X 5						
	Steel tark rple From	Bodevik	BASE M	INOR HES	TAIN	on BA	SE
			LD 418.1 CALC				
SCALE SAMP. TI	ME SAMP. ID	LAB NO.	WEIGHT (g)	mL FREON	DILUTIO	NREADING	CALC. (ppm)
Og FT							
N PIT PERIMET	ED				DIT	 PROFIL	F
		1 0	VM		FII	FROFIL	· <b>L</b>
Tr. 36	7	REA	DING				
	well	SAMPLE ID	FIELD HEADSPACE (ppm)				
	- 60	1@ 6	266	-			
1	586	3@					
	86	4 @ 5 @		$\dashv$			
12-1 1 0 1	1			ر ر	OT AF	'PU <pb< td=""><td>UT.</td></pb<>	UT.
						, •	
	TANK FOUT Pant			]			
	Pant						
15		SAMPLE	AMPLES	<u>.  </u> =			
	(	D ID AI	NALYSIS TIME				
	`		PASSED)	4		•	
.D. = PIT DEPRESSION; B.G. = BELOW	/ GRADE: B = BELOW			_			
.H. = TEST HOLE; ~ = APPROX.; T.B. =				1		7 -	
TRAVEL NOTES: CALLOUT		<del></del>	_ ONSITE: _	10/9/03	0	235	



## EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Blow 1 @ 6'	Date Reported:	10-14-03
Laboratory Number:	26818	Date Sampled:	10-09-03
Chain of Custody No:	11426	Date Received:	10-09-03
Sample Matrix:	Soil	Date Extracted:	10-10-03
Preservative:	Cool	Date Analyzed:	10-13-03
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Warren LS 1A.

Mistine of Walters

Review



## EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Olionate	Diame / DD	Decided #	04024 040
Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Blow 1 @ 6'	Date Reported:	10-13-03
Laboratory Number:	26818	Date Sampled:	10-09-03
Chain of Custody:	11426	Date Received:	10-09-03
Sample Matrix:	Soil	Date Analyzed:	10-13-03
Preservative:	Cool	Date Extracted:	10-10-03
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	ND	1.8
Toluene	45.1	1.7
Ethylbenzene	106	1.5
p,m-Xylene	113	2.2
o-Xylene	106	1.0
Total BTEX	370	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	99 %
	1,4-difluorobenzene	99 %
	Bromochlorobenzene	99 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Warren LS 1A.

Analyst Malter

Review KOS