District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Pit or Below-Grade Tank Registration or Closure

	or below-grade tank Closure of a pit or below-gra		
Operator: BP America Production Company Telephor	ne: (505)326-9200 e-mail address:		
Address: 200 Energy Ct, Farmington, NM 87401			
Facility or well name: Tapp # 2 API #:	30045 238/4 U/L or Qtr/Qtr 1	Sec <u>16T_28N_R_8W</u>	
		NAD: 1927 🗌 1983 🔲	
Surface Owner: Federal State Private Indian			
<u>Pit</u>	Below-grade tank	•	
Type: Drilling Production Disposal	e: Drilling Production Disposal Volume:bbl Type of fluid:		
Workover Emergency	Construction material:	_	
Lined 🗌 Unlined 🔲	Double-walled, with leak detection? Yes 🔲 If no	on? Yes 🔲 If not, explain why not.	
Liner type: Synthetic Thicknessmil Clay			
Pit Volumebbl			
Darah sa arang dan sa d	Less than 50 feet	(20 points)	
Depth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less than 100 feet	(10 points)	
high water elevation of ground water.)	100 feet or more	(0 points)	
	Yes	(20 points)	
Wellhead protection area: (Less than 200 feet from a private domestic	No	(0 points)	
water source, or less than 1000 feet from all other water sources.)			
Distance to surface water: (horizontal distance to all wetlands, playas,	Less than 200 feet	(20 points)	
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)	
	1000 feet or more	(0 points)	
	Ranking Score (Total Points)		
If this is a pit closure: (1) Attach a diagram of the facility showing the pit your are burying in place) onsite offsite for If offsite, name of facility remediation start date and end date. (4) Groundwater encountered: No 4.5) Attach soil sample results and a diagram of sample locations and excavated Additional Comments:	Yes I f yes, show depth below ground surface	description of remedial action taken including	
See Attached Documentation			
SW Attached Documentation			
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline	of my knowledge and belief. I further certify that tes \mathbf{X} , a general permit \square , or an (attached) alterna	the above-described pit or below-grade tank ative OCD-approved plan .	
Date: 11/01/2005	1.		
Printed Name/Title Jeffrey C. Blagg, Agent Signal	ture Jeffy C. Sligg		
Your certification and NMOCD approval of this application/closure does otherwise endanger public health or the environment. Nor does it relieve regulations.	not relieve the operator of liability should the contents	s of the pit or tank contaminate ground water or any other federal, state, or local laws and/or	
Approval: CEPUTY OR & GAS INSPECTOR, DIST. (3) Printed Name/Title	Signature B.M. E.M.	Date: <u>DEC 1 4 2005</u>	

	BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199	C.D.C. ND: <u>80901</u>				
	FIELD REPORT: CLOSURE VERIFICATION LOCATION: NAME: TAPP WELL #: Z PIT: SEP	PAGE No: of				
	QUAD/UNIT: L SEC: 16 TWP: 28N RNG: 8W PM: NM CNTY: SS ST: NM QTR/FOOTAGE: 1710'S 975' NW/SWCONTRACTOR: FLINT	DATE FINISHED: 10-5-01 ENVIRONMENTAL SPECIALIST:				
	DISPOSAL FACILITY: NA REMEDIATION METHOL LEASE: NASE 078499 FOR	D: CLOSE AS IS				
	FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 102 FT. A DEPTH TO GROUNDWATER: >100 NEAREST SURFACE DEPTH TO GROUNDWATER: >100 NEAREST SURFACE NEAREST SURF	170°W FROM WELLHEAD.				
	NMOCD RANKING SCORE: 0 NMOCD TPH CLOSURE STD. 5000 PPM	CHECK ONE:				
	DESCRIPTION: SULTYPE: SAND / SILTY SAND / SILTY SAND / SILTY CLAY / CLAY / GRAVEL / DTHER SULL COLOR: TIME: 1600 am/pm DATE: 10-5-01 SULTYPE: SAND / SILTY SAND / SILTY CLAY / CLAY / GRAVEL / DTHER SULL COLOR:	FIBERGLASS TANK INSTALLED				
	COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY COHESIVE / COHESIVE / HIGHL CONSISTENCY (NON COHESIVE SOILS): LODSE / FIRM / DENSE / VERY DENSE PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLAS DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD	TIC / HIGHLY PLASTIC				
<i>;</i>)	MOISTURE: (DRY) / SLIGHTLY MOIST / MOIST / VET / SATURATED / SUPER SATURATED DISCOLORATION/STAINING OBSERVED: YES / NO EXPLANATION - HC ODOR DETECTED YES / NO EXPLANATION - SAMPLE TYPE: GRAB / COMPOSITE - # OF PTS. ADDITIONAL COMMENTS: PIT W/ 95 5/62 Sec. 1 TANK Revised to the					
	ADDITIONAL COMMENTS: PIT W/ 95 BBC STEEL ANT. COM DIED ON THE SOURCE OF					
	SCALE SAMP. TIME SAMPLE I.D. LAB No: WEIGHT (g) ml. FREON DILL OF FT	ITION READING CALC. ppm				
	PIT PERIMETER OVM RESULTS	PROFILE				
	SAMPLE FIELD HEADSPACE PID (ppm) 1 @ 44 0 0 0	_15'->				
47m	3 @					
	C104 714 1555	EDRUKT				
)	TRAVEL NOTES: (2) (2) (4) (5)	157.0				
	TRAVEL NOTES: CALLOUT: 10-5-01 1400 ONSITE: 10-5-01	1530				



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Sep C @ 4'	Date Reported:	10-10-01
Laboratory Number:	21199	Date Sampled:	10-05-01
Chain of Custody No:	8777	Date Received:	10-08-01
Sample Matrix:	Soil	Date Extracted:	10-09-01
Preservative:	Cool	Date Analyzed:	10-10-01
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Tapp #2.

Analyst C. Offeren

(Nistri m Walters Review