## **UNITED STATES** DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

**AMENDED 6/6/06** replaces sundry dated 2/9/06

Share and the special resolution of the special specia

·	
Sundry Notices and Reports on Wells 3 9	
Type of Well GAS SUN S AND S 54	5. Lease Number NMSF-079049B 6. If Indian, All. or Tribe Name
Name of Operator	7. Unit Agreement Name
BURLINGTON RESCURCES OIL & GAS COMPANY LP	San Juan 28-6 Unit
Address & Phone No. of Operator	- 8. Well Name & Number
PO Box 4289, Farmington, NM 87499 (505) 326-9700	San Juan 28-6 Unit #130N 9. API Well No.
Location of Well, Footage, Sec., T, R, M Sec., TN, RW, NMPM	30-039-27865 10. Field and Pool
Unit G (SWNE), 2535' FNL & 2505' FEL, Sec. 32, T28N, R6W NMPM	Blanco MV/ Basin DK 11. County and State Rio Arriba, NM
13. Describe Proposed or Completed Operations:	☑ Other: 7" csg & 4-1/2" prod.
☐ Altering Casing ☐ Conversion to Injection ☐	2/3/06 Drill to intermediate TD @ 3464'. 2/5/06 <b>Stage 1</b> : Cmtd w/: 32, 6.25 pps LCM-1, 1% fluid loss (5 pps LCM-1, 1% fluid loss (186 cu ff 6.25 pps LCM-1, 1% fluid loss (57 c) CM-1, 1% fluid loss (720 cu ff). 1500 psi/30 mins. OK. Drilling csg. (total jts 179) & set @ 7691'. C w/9 sxs (28 cf- 5 bbls) Scavenger ed w/ 299 sxs (592 cf- 105 bbls) % FL-52. Dropped plug, displaced
13. Describe Proposed or Completed Operations:  1/31/06 MIRU. NU BOP. PT BOP & csg to 600 psi/30 min. OK. Drilling ahead. 2 3470' Circ hole clean. TOOH. 2/4/06 TIH w/80 jts 7" 20# J-55 ST&C csg set 6 sxs Scavenger cmt w/3% calcium chloride, .05 pps D-29 cellophane, 0.3% CD-3 cu ft). Tail w/135 sxs Premium Lite cmt w/0.3% CD-32, .25 pps cello-flake, 6.25 Circulated 10 bbls of cmnt to surface. (AMENDED) 6/6/06 Stage 2: Tail w/19 sxs Scavenger cmt w/.3% CD-32, .05 pps D-29 cellophane, 6 ft). Tail w/338 sxs Premium Lite cmt w/.3% CD-32, .25 pps celloflake, 6.25 pps L Displace w/20 bbls wtr. Circ 50 bbls of cmt to surface. 2/5/06 PT BOP & csg to ahead. 2/6/06 Drill to TD @ 7691'. Circ hole clean. TOOH. 2/7/06 TIH w/161 jts 4 ½" 10.5# J-55 ST&C csg. & 18 jts of 11.6# J-55 LT&C of to bottom, ran pre-flush of 10 bbls of chemical wash, 2 bbls of H2O then cmntd Class B cmt w/.25% Cello-Flake, .3% CD-32, 6.25 pps LCM-1, 1% FL-52. Taile Premium Lite HS FMI cmt w/.25 pps celloflake, 6.25 pps LCM-1, 0.3% CD-32, 1 H2O, bumped plug, plugged down @ 19:13 hrs on 2/7/06. ND BOP, RD & release be conducted by completion rig. Will show TOC & PT on next report.	2/3/06 Drill to intermediate TD @ 3464'. 2/5/06 Stage 1: Cmtd w//32, 6.25 pps LCM-1, 1% fluid loss (186 cu ff 6.25 pps LCM-1, 1% fluid loss (57 cl. CM-1, 1% fluid loss (57 cl. CM-1, 1% fluid loss (720 cu ft). 1500 psi/30 mins. OK. Drilling csg. (total jts 179) & set @ 7691'. Cl. cm/9 sxs (28 cf- 5 bbls) Scavenger ed w/ 299 sxs (592 cf- 105 bbls) % FL-52. Dropped plug, displaced ased @ 06:00 hrs on 2/8/06. PT will complete the complete compl
13. Describe Proposed or Completed Operations:  1/31/06 MIRU. NU BOP. PT BOP & csg to 600 psi/30 min. OK. Drilling ahead. 2 3470' Circ hole clean. TOOH. 2/4/06 TIH w/80 jts 7" 20# J-55 ST&C csg set 6 sxs Scavenger cmt w/3% calcium chloride, .05 pps D-29 cellophane, 0.3% CD-3 cu ft). Tail w/135 sxs Premium Lite cmt w/0.3% CD-32, .25 pps cello-flake, 6.25 Circulated 10 bbls of cmnt to surface. (AMENDED) 6/6/06 Stage 2: Tail w/19 sxs Scavenger cmt w/.3% CD-32, .05 pps D-29 cellophane, 6 ft). Tail w/338 sxs Premium Lite cmt w/.3% CD-32, .25 pps celloflake, 6.25 pps L Displace w/20 bbls wtr. Circ 50 bbls of cmt to surface. 2/5/06 PT BOP & csg to ahead. 2/6/06 Drill to TD @ 7691'. Circ hole clean. TOOH. 2/7/06 TIH w/161 jts 4 ½" 10.5# J-55 ST&C csg. & 18 jts of 11.6# J-55 LT&C of to bottom, ran pre-flush of 10 bbls of chemical wash, 2 bbls of H2O then cmntd Class B cmt w/.25% Cello-Flake, .3% CD-32, 6.25 pps LCM-1, 1% FL-52. Taile Premium Lite HS FMI cmt w/.25 pps celloflake, 6.25 pps LCM-1, 0.3% CD-32, 1 H2O, bumped plug, plugged down @ 19:13 hrs on 2/7/06. ND BOP, RD & release be conducted by completion rig. Will show TOC & PT on next report.	2/3/06 Drill to intermediate TD @ 3464'. 2/5/06 <b>Stage 1</b> : Cmtd w/: 32, 6.25 pps LCM-1, 1% fluid loss (186 cu ff) pps LCM-1, 1% fluid loss (186 cu ff) 6.25 pps LCM-1, 1% fluid loss (57 c) CM-1, 1% fluid loss (720 cu ft). 1500 psi/30 mins. OK. Drilling csg. (total jts 179) & set @ 7691'. C w/9 sxs (28 cf- 5 bbls) Scavenger ed w/ 299 sxs (592 cf- 105 bbls) % FL-52. Dropped plug, displaced ased @ 06:00 hrs on 2/8/06. PT will