UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

PORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

5.	Lease Serial No.	
-	NMMM03187	

Do not use thi abandoned wei	6. If Indian, Allotte	6. If Indian, Allottee or Tribe Name				
SUBMIT IN TRI	PLICATE - Other instruc	tions on reverse side.	7. If Unit or CA/Ag	reement, Name and/or No.		
1. Type of Well		8. Well Name and N LAMBE 1B	8. Well Name and No.			
Oil Well Gas Well Oth		DECCY COLE	9. API Well No.			
Name of Operator BURLINGTON RESOURCES		PEGGY COLE E-Mail: pcole@br-inc.com	30-045-30744	30-045-30744-00-X1		
3a. Address 3401 EAST 30TH FARMINGTON, NM 87499		FX. 303.320.97q1=	AY 2003 MESAVERDE	10: Field and Pool, or Exploratory MESAVERDE POINT LOOKOUT		
4. Location of Well (Footage, Sec., 1	., R., M., or Survey Description		11. County or Paris	h, and State		
Sec 21 T31N R10W NENW 1	235FNL 1890FWL		SAN JUAN C	OUNTY, NM		
12. CHECK APPI	ROPRIATE BOX(ES) TO	INDICATE NATURE OF	NOTICE, RÉPORT, OR OTH	ER DATA		
TYPE OF SUBMISSION		ТҮРЕ (OF ACTION			
	☐ Acidize	Deepen	Production (Start/Resume)	☐ Water Shut-Off		
□ Notice of Intent	Alter Casing	Fracture Treat	Reclamation	☐ Well Integrity		
Subsequent Report	☐ Casing Repair	☐ New Construction	Recomplete	_		
Final Abandonment Notice	Change Plans	Plug and Abandon	☐ Temporarily Abandon	Other Well Spud		
J	Convert to Injection	Plug Back	☐ Water Disposal			
determined that the site is ready for for (5/7/03) MIRU. Spud well @ 932.3# H-40 ST&C csg, set @ surface. WOC. (5/8/03) NU BOP. PT BOP & (5/10/03) Drill to intermediate (5/11/03) TiH w/72 jts 7" 20# w/42 sxs Premium Lite FM w/ (89 cu. ft.). Tail w/90 sxs Type loss (124 cu. ft.). Displace w/3 Premium Lite w/3% calcium c (639 cu. ft.). Displace w/97 bb mins, OK. Drilling ahead.	2:00 pm 5/7/03. Drill to 19:187'. Cmtd w/140 sxs Clacsg to 600 psi/15 mins, O TD @ 3103'. Circ hole cled J-55 ST&C csg, set @ 30 3% calcium chloride, 0.25 e III cmt w/1% calcium chloride, 0.25 pps celloflak hloride, 0.25 pps celloflak	ass B neat (197 cu. ft.). Circ K. Drilling ahead. ean. TOOH. 93'. Stage tool set @ 2405'. is pps celloflake, 5 pps LCM- oride, 0.25 pps celloflake, 0 s cmt to surface. Cmtd 2nd stee. 0.5 pps LCM-1. 0.4% flui	11 bbls cmt to Cmtd 1st stage 1, 0.4% fluid loss .2% fluid stage w/300 sxs d loss. 0.4% SMS			
14. Thereby certify that the foregoing is	Electronic Submission # For BURLINGTON RE	21811 verified by the BLM W SOURCES O&G CO LP, sen essing by Adrienne Garcia or	t to the Farmington			
Name (Printed/Typed) PEGGY C	OLE	Title REGU	ILATORY ADMINISTRATOR			
Signature (Electronic S	Submission)	Date 05/14/	/2003			
•	THIS SPACE FO	OR FEDERAL OR STATE	OFFICE USE			
Approved By ADRIENNE GARCIA	Α	TitlePFTROL	EUM ENGINEER	Date 05/14/2003		
Conditions of approval, if any, are attached certify that the applicant holds legal or equivalent would entitle the applicant to conditions.	ed. Approval of this notice does	not warrant or				
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U.S.C. Section 1212, make it a statements or representations as	crime for any person knowingly a to any matter within its jurisdiction	and willfully to make to any department	t or agency of the United		

,Additional data for EC transaction #21811 that would not fit on the form

32. Additional remarks, continued

APD ROW Related