

(October 1990)

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

SUBMIT IN DUPLICATE*

(See other instructions on reverse side)

FOR APPROVED

OMB NO. 1004-0137

Expires: December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other _____				5. LEASE DESIGNATION AND SERIAL NO. NMSF-078410	
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☐ Other _____				6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
2. NAME OF OPERATOR CONOCOPHILLIPS COMPANY				7. UNIT AGREEMENT NAME San Juan 29-5 Unit	
3. ADDRESS AND TELEPHONE NO. PO BOX 4289, Farmington, NM 87499 (505) 326-9700				8. FARM OR LEASE NAME, WELL NO. San Juan 29-5 Unit #4C	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements) At surface Unit F (SENW), 2435' FNL & 2315' FWL, At top prod. interval reported below Same as above At total depth Same as above				9. API WELL NO. 30-039-29351	
10. FIELD AND POOL, OR WILDCAT Blanco Mesaverde				11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA Sec. 6, T29N, R5W, NMPM	
14. PERMIT NO.		DATE ISSUED		12. COUNTY OR PARISH Rio Arriba	
				13. STATE New Mexico	
15. DATE SPUDDED 5/17/06	16. DATE T.D. REACHED 5/25/06	17. DATE COMPL. (Ready to prod.) 6/23/06	18. ELEVATIONS (DF, RKB, RT, BR, ETC.)* GL - 6661'		19. ELEV. CASINGHEAD
20. TOTAL DEPTH, MD & TVD 6210'	21. PLUG, BACK T.D., MD & TVD 6178'	22. IF MULTIPLE COMPL., HOW MANY* 1	23. INTERVALS DRILLED BY	ROTARY TOOLS	CABLE TOOLS
24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)* Blanco Mesaverde - 4385' - 5956'				25. WAS DIRECTIONAL SURVEY MADE No	
26. TYPE ELECTRIC AND OTHER LOGS RUN GR/CBL				27. WAS WELL CORED No	
28. CASING RECORD (Report all strings set in well)					
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
9-5/8"	32.3# H-40	235'	12-1/4"	Surface: 155 sx (183 cf)	7 bbls
7"	20#, J-55	3950'	8-3/4"	TOC - 1520': 670 sx (1451 cf)	0
4-1/2"	11.6#, N-80	6201'	6-1/4"	TOC @ 3145': 260 sx (377 cf)	
29. LINER RECORD					
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	
30. TUBING RECORD					
SIZE	DEPTH SET (MD)	PACKER SET (MD)			
2-3/8"	5818'				
4.7#					
31. PERFORATION RECORD (Interval, size and number)			32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.		
MV perforations			DEPTH INTERVAL (MD)		
LMF - 5722' - 5749' - 5 holes			AMOUNT AND KIND OF MATERIAL USED		
PLO - 5810' - 5956' - 25 holes			5722' - 5956'		
CH - 5217' - 5604' - 27 holes			420 gal 15% HCL, 1256 bbls 60 Q slickfoam w/100,360#		
LEWIS - 43'96" - 4919' 25 holes			20/40 Brady sand & 1,295,600 scf N2		
is -			5217'-5604'		
			420 gal 15% HCL, 1244 bbls 60 Q slickfoam w/100,210#		
			20/40 Brady sand & 1,272,100 scf N2		
			4396' - 4919'		
			420 gal 15% HCL; 670 bbls 75 Q 20# Linear gel w/		
			191,200# 20/40 Brady sand & 1,330,600 scf N2		
33. PRODUCTION			34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)		
DATE FIRST PRODUCTION			TEST WITNESSED BY		
SI			To be sold		
35. LIST OF ATTACHMENTS					
This will be a single zones Mesaverde well.					
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records					
SIGNED		TITLE		DATE	
		Sr. Regulatory Specialist		6/28/06	

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department of agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries);

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	GEOLOGIC MARKERS		
				NAME	MEAS. DEPTH	TRUE VERT. DEPTH
Ojo Alamo	2670'	2911'	White, cr-gr ss.	Ojo Alamo	2670'	
Kirtland	2911'	3195'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	2911'	
Fruitland	3195'	3548'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Fruitland	3195'	
Pictured Cliffs	3548'	4364'	Bn-Gry, fine grn, tight ss.	Pic.Cliffs	3548'	
Lewis / Navajo City	4364'	4635'	Shale w/siltstone stringers	Lewis	4364'	
Huerfanito Bentonite			White, waxy chalky bentonite	Huerfanito Bent.		
Chacra	4635'	5196'	Gry fn grn silty, glauconitic sd stone w/drk gry shale	Chacra	4635'	
Mesa Verde	5196'	5527'	Light gry, med-fine gr ss, carb sh & coal	Mesa Verde	5196'	
Menefee	5527'	5805'	Med-dark gry, fine gr ss, carb sh & coal	Menefee	5527'	
Point Lookout	5805'		Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation	Point Lookout	5805'	