

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

1. **Type of Well**
GAS

2. **Name of Operator**
CONOCOPHILLIPS

3. **Address & Phone No. of Operator**

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. **Location of Well, Footage, Sec., T, R, M**

Unit K, 1470' FSL & 1600' FWL, Sec. 30, T26N, R3W, NMPM

2006 JUN 27 6:59

RECEIVED
070 FARMINGTON NM

42 **Lease Number**
JIC 100
If Indian, All. or
Tribe Name

7. **Unit Agreement Name**

8. **Well Name & Number**


Jicarilla D #5
API Well No.

30-039-06273

10. **Field and Pool**

Tapacito Pictured Cliffs

11. **County and State**
Rio Arriba Co., NM



12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action	
<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Plugging	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
		<input type="checkbox"/> Other

13. Describe Proposed or Completed Operations

6/7/06 MIRU. Kill well w/30 bbls. ND WH, NU BOP. Remove hanger. POH w/121 juts tbg. PU casing scraper. TIH to 3826'. TOH & LD scraper. PU cement retainer & set @ 3806'. Load casing & attempt to PT casing to 500#. Failed. Couldn't establish Inj rate. Pumped Plug #1 w/40 sx Type III cement. Plug from 3806 - 3228'. POH. RU WL & perf'd 217k4' w/3 1/3" HSC. POOH & RD WL. PU cement retainer & set @ 2114'. Pumped #2 plug w/46 sx Type III cement - 2174' - 2074'. Est TOC w/required excess @ 2103'.. Pumped 35 sx outside csg, 4 sx below cement ret. & 7 sx on top. LD. RU WL & perf @ 247' w/3-3-1/8 HS. POOH. RD WL. Pumped plug #3 Surface plg w/90 sx Type III cement from 247 - surf. Circ. Good cement out of BH. SIW. 6/14/03 Open up Well. Cement down 6'. ND BOP, RD pump truck. Dug out & cut off WH. Cement in annulus full. Installed dry hole marker w/20 sx Type III cement. RD rig. Cut off anchors. MOL.

Well now P&A'd. Will submit sundry when pad has been cleaned and reclaimed.

14. I hereby certify that the foregoing is true and correct.

Signed Patsy Clugston Patsy Clugston Title Sr. Regulatory Specialist Date 6/23/06

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

ACCEPTED FOR RECORD

JUN 29 2006

NHOC
8

FARMINGTON FIELD OFFICE
JL sm