

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

2006 JUN 27 PM 9 46

1. **Type of Well**
GAS

2. **Name of Operator**
CONOCOPHILLIPS

3. **Address & Phone No. of Operator**

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. **Location of Well, Footage, Sec., T, R, M**

Unit F (SENW), 1800' FNL & 1460' FWL, Section 20, T29N, R5W, NMPM

5. **Lease Number**
NMSF-078281
6. **If Indian, Ail. or
Tribe Name**

7. **Unit Agreement Name**

8. **San Juan 29-5 Unit
Well Name & Number**

9. **SJ 29-5 Unit #67F
API Well No.**

30-039-29740

10. **Field and Pool**

Basin DK / Blanco MV

11. **County and State**
Rio Arriba Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action	
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection

☒ Other casing report

13. Describe Proposed or Completed Operations

6/10/06 MIRU PT casing to 1000 psi/30 min. Good test. RIH w/8-3/4" bit & tagged cement @ 169'. D/O cement and then ahead to 3840'. Circ. Hole. RIH w/7" 20#, J-55 casing and got casing stuck @ 3770'. Attempt to backoff of casing. Able to PUH w/casing. RIH w/mill & washed & reamed 3840'. Drilled to 3862'. Circ. Hole. 6/15/06 RIH w/90 jts 7", 20#, J-55 casing & set @ 3848'. RU to cement. Pumped 20 bbls gel water preflush. Lead w/425 sx (199 bbl slurry) Class G cement w/3% D079, .2% D045, 1#/bbl cement. Tailed w/240 sx (55 bbl slurry) 50/50 POZ Class G w/2% D20, .2% D46, 2% S-001, 5#/sx D24, 0.15% D64, 1#/bbl cement. Dropped plug and displaced w/154 bbls FW. Bumped plug w/1550 psi. Plug down @ 1350 hrs. 90 bbls cement circulated to surface. RD cement. WOC. 6/17/06 PT casing to 1800#/30 min. OK.

6/17/06 RIH w/6-1/4" bit & tagged cement @ 3800'. Hammer drill w/air from 3880' to 8040' (TD). TD reached 6/19/06. Blow-hole. RIH w/194 jts 4-1/2" 11.6# N-80 casing and set @ 8036'. RU Schlumberger. Pumped 10/10/10 preflush. Pumped 470 sx (10.5 bbl slurry) 50/50 POZ Class G cement w/.25#/sx D029, 3.0% D029, 1#/sx D024, .25% D167, .15% D065, .10% D80, .10% D045. Dropped plug & displaced w/124.5 bbls. Bumped plug @ 11200 hrs 6/20/06 w/1500#. RD cement. ND BOP, set slips And cut off casing. Installed Trash cap. RD & released rig @ 1800 hrs 6/20/06. The casing PT & TOC will be reported on the next report. The completion rig will conduct the PT.

14. I hereby certify that the foregoing is true and correct.

Signed Patsy Clugston Patsy Clugston Title Sr. Regulatory Specialist Date 6/23/06

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

ACCEPTED FOR RECORD
Date

JUN 28 2006

NMOC

FARMINGTON FIELD OFFICE