District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410

State of New Mexico Energy Minerals and Natural Resources

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144 June 1, 2004

<u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505 Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

	de Tank Registration or Closi		
Is pit or below-grade tan Type of action: Registration of a pit of	k covered by a "general plan"? Yes 🔯 Nor below-grade tank 🔲 Closure of a pit or below-gr	O∐ rade tank ⊠	
WEG ENERGY DIG	Telephone: (505)-324-1090 e-m UITE 1. FARMINGTON. NM 874 API#: 30-045- 24880 U/L or Qtr	nail address:	
Pit Type: Drilling Production Disposal BLOW Workover Emergency Lined Unlined Liner type: Synthetic Thicknessmil Clay Pit Volumebbl	Below-grade tank Volume:bbl_Type of fluid: Construction materia: Double-walled, withteak actection? Yes If j		
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet 50 feet or more, but less than 100 feet 100 feet or more	(20 points) (10 points) (0 points)	0
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes No	(20 points) (0 points)	0
Distance to surface water: (horizontal distance to all wetlands, playas, igation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more	(20 points) (10 points) (0 points)	0
	Ranking Score (Total Points)		0
If this is a pit closure: (1) attach a diagram of the facility showing the pit's your are burying in place) onsite offsite for offsite, name of facility remediation start date and end date. (4) Groundwater encountered: No Attach soil sample results and a diagram of sample locations and excavation Additional Comments: PIT LOCATED APPROXIMATELY PIT EXCAVATION: WIDTH NA ft., LENGTH	Yes If yes, show depth below ground surface	description of remedial a ft. and attach	action taken including
PIT REMEDIATION: CLOSE AS IS: ☑, LANDFARM: ☐, C	COMPOST: [], STOCKPILE: [], OTHER [] ((co	ECHWED W
Cubic yards: NA BEDROCK BOTTOM		OM.	CONS. DIM
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline Date:	es 🗵, a general permit 🗌, or an alternative OCI Signature Signature should the content of liability should the content of t	t the above-described dis- approved plan .	- minate ground water or
proval: Printed Name/Title	motion Deny to	y Date: N	1AR 2 7 2006

0f2



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / XTO	Project #:	94034-010
Sample ID:	2 @ 9'	Date Reported:	11-23-04
Laboratory Number:	31292	Date Sampled:	11-19-04
Chain of Custody No:	13306	Date Received:	11-22-04
Sample Matrix:	Soil	Date Extracted:	11-22-04
Preservative:	Cool	Date Analyzed:	11-23-04
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	411	0.2
Diesel Range (C10 - C28)	480	0.1
Total Petroleum Hydrocarbons	891	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Martin GC B #1E Blow.

Ahalyst

(Mustine m Walters



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / XTO	Project #:	94034-010
Sample ID:	2 @ 9'	Date Reported:	11-23-04
Laboratory Number:	31292	Date Sampled:	11-19-04
Chain of Custody:	13306	Date Received:	11-22-04
Sample Matrix:	Soil	Date Analyzed:	11-23-04
Preservative:	Cool	Date Extracted:	11-22-04
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)	
Benzene	1,160	1.8	
Toluene	1,780	1.7	
Ethylbenzene	358	1.5	
p,m-Xylene	1,540	2.2	
o-Xylene	722	1.0	
Total BTEX	5,560		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	96 %
	1,4-difluorobenzene	96 %
	Bromochlorobenzene	96 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Martin GC B #1E Blow.

Analyst C. Oy

Mistine m Walter
Review

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410

State of New Mexico Energy Minerals and Natural Resources

n r. For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144 June 1, 2004

District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Santa Fe, NM 87505

For downstream facilities, submit to Sa

Is pit or below-grade tar	ade Tank Registration or Closh covered by a "general plan"? Yes \(\subseteq \) or below-grade tank \(\subseteq \) Closure of a pit or below-	No 🔲	
Operator: XTO ENERGY INC. Address: 2700 FARMINGTON AVE BLDG. K. S. Facility or well name: MARTIN GC B #1E County: SAN JUAN Latitude 36.61465 Longitude 10	SUITE 1. FARMINGTON. NM 87 API#: 30-045- 24880 U/L or Q	otr/Qtr P Sec 31	
Pit Type: Drilling Production Disposal SEPARATOR Workover Emergency Lined Unlined Liner type: Synthetic Thicknessmil Clay Pit Volumebbl	Below-grade tank Volume:bbl_Type of fluid: Construction material Double-walled, with leak of tection? YesIf Less than 50 feet	explain why not.	
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	50 feet or more, but less than 100 feet 100 feet or more	(10 points) (0 points)	0
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes No	(20 points) (0 points)	0
Distance to surface water: (horizontal distance to all wetlands, playas, igation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more	(20 points) (10 points) (0 points)	0
If this is a pit closure: (1) attach a diagram of the facility showing the pit?			
your are burying in place) onsite \square offsite \square If offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No \square Attach soil sample results and a diagram of sample locations and excavation	Yes If yes, show depth below ground surface _	ft. and attach	
Additional Comments: PIT LOCATED APPROXIMATEL PIT EXCAVATION: WIDTH NA ft., LENGTH	NA ft., DEPTH NA ft	25	MAR 2008
Additional Comments: PIT LOCATED APPROXIMATEL PIT EXCAVATION: WIDTH NA ft., LENGTH PIT REMEDIATION: CLOSE AS IS: ☑, LANDFARM: ☐, C Cubic yards: NA	NA ft., DEPTH NA ft	25	MAR 2006 COLVED
Additional Comments: PIT LOCATED APPROXIMATEL PIT EXCAVATION: WIDTH NA ft., LENGTH PIT REMEDIATION: CLOSE AS IS: ⋈, LANDFARM: □, O	NA ft., DEPTH NA ft COMPOST:, STOCKPILE:, OTHER t of my knowledge and belief. I further certify th	(explain) (© O)	
Additional Comments: PIT LOCATED APPROXIMATEL PIT EXCAVATION: WIDTH NA ft., LENGTH PIT REMEDIATION: CLOSE AS IS: M, LANDFARM: M, C Cubic yards: NA BEDROCK BOTTOM I hereby certify that the information above is true and complete to the best	NA ft., DEPTH NA ft COMPOST:, STOCKPILE:, OTHER t of my knowledge and belief. I further certify the es \boxed{\omega}, a general permit, or an alternative OC Signature	(explain) at the above-described pit (D-approved plan (S)).	below grade tank

2 of 2

	1		NEERING	•	LOC	ATION NO:	CTIZZ
CLIENT: XTO	P.O. BOX	87, BLO 505) 632		, NM 874		R NO:	13306
FIELD REPORT	: PIT CL	OSURE	VERIF	ICATIO	N PAGI	E No:1	of
LOCATION: NAME: MAR	TIN GC !	S WELL#: 1	E TYPE	SEP		STARTED:	
QUAD/UNIT: P SEC: 31	TWP: 28 N RNG	: 10W PM: /	NA CNTY: 5	ST: NM			-19 - 04
QTR/FOOTAGE: 1120 FSL	XIIZUFEL S	ELSE CONTR	RACTOR: KELCO	(MIKE)	ENVIR SPECI	ONMENTAL ALIST:	IB
EXCAVATION APPROX							0
DISPOSAL FACILITY:	NA		REMEDIA	TION METHO	D:	cuse.	As 15
LAND USE: RANG							PC
FIELD NOTES & REMAR							NELLHEAD.
DEPTH TO GROUNDWATER: >10	O' NEAREST WA	TER SOURCE:	>10001	_ NEAREST SU	IRFACE WAT	ER: >/8	000′
NMOCD RANKING SCORE:	NMOCD TPH	CLOSURE STD:	5000 PF	PM			!
SOIL AND EXCAVATION				OVM CALIB.	READ. = 5	ېرې ppm	
SOIL AND EXCAVATION	DESCRIPT	IOIN.		OVM CALIB.			$\frac{RF = 0.52}{11.69}$
SOIL TYPE: SAND SILTY SAI	ND / SILT / SILTY (CLAY / CLAY /	GRAVEL / OTH	TIME: <u>08</u> 5			0 10' BU
SOIL COLOR:	ow TAN						
COHESION (ALL OTHERS): NON C CONSISTENCY (NON COHESIVE S				COHESIVE			
PLASTICITY (CLAYS): NON PLAST				/ HIGHLY PLAST	IC		
DENSITY (COHESIVE CLAYS & SILT						CCI	(Q3EC
MOISTURE: DRY SLIGHTLY MOIS DISCOLORATION/STAINING OBSER				7′			
HC ODOR DETECTED YES NO E	XPLANATION -	MoDerato	, , , , , , , , , , , , , , , , , , ,				
SAMPLE TYPE: GRAB COMPOSIT	E - # OF PTS	- 24	X 15 X4	Deex Fo	Man	A.X. C	Ko
BEDROCK BA	ektiviz to	Dig tost	- Trendy,	FIRM	Bedice	k @ 16	U' B6
ROHOM							
SCALE SAMP. TI	ME SAMP. ID	LAB NO.	ELD 418.1 CALC		DUUTION	DE A DING	CAT C (===)
SAMP. 11	ME SAMP. ID	LAB NO.	WEIGHT (g)	IL FREON	DILUTION	READING	CALC. (ppm)
O a FT							
√ PIT PERIMET	ER						
					PITF	ROFIL	<u>E</u>
	ر. ال		VM		PITF	ROFIL	E
1 Put	ell	REA	DING		PITF	ROFIL	<u>E</u>
	ell	REA SAMPLE			PIT	ROFIL	E
	.PD	REA SAMPLE ID 1@ 10 2@	FIELD HEADSPACE		PIT P	ROFIL	<u>E</u>
	PD	REA SAMPLE ID 1 @ 10 2 @ 3 @	FIELD HEADSPACE	A	PIT P	ROFIL	<u>E</u>
	PD PD	REA SAMPLE ID 1@ 10 2@	FIELD HEADSPACE	A	PIT P	ROFIL	E A
1 Tu	PD	REA SAMPLE ID 1 @ 10 2 @ 3 @ 4 @	FIELD HEADSPACE	A	PIT	ROFIL	<u>A</u>
	PD (15' A'	REA SAMPLE ID 1 @ 10 2 @ 3 @ 4 @	FIELD HEADSPACE		PIT F	ROFIL	E
1 Tu	PD	REA SAMPLE ID 1 @ 10 2 @ 3 @ 4 @	FIELD HEADSPACE	STAN	PIT P	ROFIL	<u>A</u>
A O	PD	REA SAMPLE ID 1@ ID 2@ 3@ 4@ 5@	ADING FIELD HEADSPACE (ppm) 244		PIT	ROFIL	<u>A</u>
1 Tu	PD	REA SAMPLE ID 2 @ 3 @ 4 @ 5 @ LAB S.	ADING FIELD HEADSPACE (ppm) 244 AMPLES NALYSIS TIME	STAN	**************************************		<u>A</u>
A O	PD	REASON SAMPLE AND SAMP	ADING FIELD HEADSPACE (ppm) 244 AMPLES	STAN	**************************************	ROFIL	<u>A</u>
A O	PD	REA SAMPLE ID 2 @ 3 @ 4 @ 5 @ LAB S.	ADING FIELD HEADSPACE (ppm) 244 AMPLES NALYSIS TIME	STAN	**************************************		<u>A</u>
P.D. = PIT DEPRESSION; B.G. = BELO	N GRADE; B = BELOW	REA SAMPLE ID 2 @ 3 @ 4 @ 5 @ LAB S.	ADING FIELD HEADSPACE (ppm) 244 AMPLES NALYSIS TIME	STAN	**************************************		<u>A</u>
A O	W GRADE; B = BELOW = TANK BOTTOM	REA SAMPLE ID 2 @ 3 @ 4 @ 5 @ 10 10 10 10 10 10 10 10	ADING FIELD HEADSPACE (ppm) 244 AMPLES NALYSIS TIME	STAIN BEDRON	**************************************		<u>A</u>



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / XTO	Project #:	94034-010
Sample ID:	1 @ 10'	Date Reported:	11-23-04
Laboratory Number:	31293	Date Sampled:	11-19-04
Chain of Custody No:	13306	Date Received:	11-22-04
Sample Matrix:	Soil	Date Extracted:	11-22-04
Preservative:	Cool	Date Analyzed:	11-23-04
Condition:	Cool and intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	157	0.2
Diesel Range (C10 - C28)	249	0.1
Total Petroleum Hydrocarbons	406	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Martin GC B #1E Separator.

Analyst C. O

Review Museters



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / XTO	Project #:	94034-010
Sample ID:	1 @ 10'	Date Reported:	11-23-04
Laboratory Number:	31293	Date Sampled:	11-19-04
Chain of Custody:	13306	Date Received:	11-22-04
Sample Matrix:	Soil	Date Analyzed:	11-23-04
Preservative:	Cool	Date Extracted:	11-22-04
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)	
Benzene	212	1.8	
Toluene	502	1.7	
Ethylbenzene	42.5	1.5	
p,m-Xylene	312	2.2	
o-Xylene	143	1.0	
Total BTEX	1,210		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	96 %
	1,4-difluorobenzene	96 %
	Bromochlorobenzene	96 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Martin GC B #1E Separator.

Analyst C. Cym.

Mustine of Walters
Review