Form 3160-5 (February 2005)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0137 Expires: March 31, 2007

UNDRY	NOTIC	ES AN	DAREPORT	ſ\$∩ONΩWEĻ	LS 27

5. Lease Serial No.

	ITO IOCO AITMAIACA	(以外 (お) () N/ VK E.L.L	. 3 ^ 7	NMSF 0/8		
SUNDRY NOTICES AND REPORTS ON WELLS 7 Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160 - 3 (APD) for such proposals.					6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE- Other instructions on reverse side.					7. If Unit or CA/Agreement, Name and/or No. Canyon Largo Unit 8. Well Name and No.	
1. Type of Well						
Name of Operator Huntington E	Cnergy, L.L.C.		Canyon Largo Unit 477 9. API Well No.			
Address	3b. Phone No. (include at	rea code)	30-039-29715 10. Field and Pool, or Exploratory Area Basin Dakota			
6301 Waterford Blvd., Suite 400 Location of Well (Footage, Sec., 7	405-840-9876					
NENE Lot A, 1060' FNL & 86	-			11. County or	Parish, State	
Sec 27, T24N-R6W NMPM				Rio Arriba County, NM		
12. CHECK AP	PPROPRIATE BOX(ES) TO	INDICATE NATURE	OF NOTICE.	REPORT, OR		
TYPE OF SUBMISSION		TYPE	OF ACTION		7	
	Acidize	Deepen	Deepen Production (Water Shut-Off	
Notice of Intent	Alter Casing	Fracture Treat	Reclamation	Į	Well Integrity ✓ Other Production Casing	
✓ Subsequent Report	Casing Repair Change Plans	New Construction Plug and Abandon	Recomplete Temporarily	Ahandon	V 10ther 110ddenon casing	
Final Abandonment Notice	Convert to Injection	Plug Back	Water Dispos			
following completion of the intesting has been completed. Fit determined that the site is ready Production Casing Detail:	inal Abandonment Notices must b ly for final inspection.)	n results in a multiple comple	ction or recompletion	on in a new interval,	ports must be filed within 30 days a Form 3160-4 must be filed once completed, and the operator has	
testing has been completed. Fi determined that the site is ready Production Casing Detail: 6/2/06: 7 7/8" hole, 4 1/2" Cementing detail: Cemer	inal Abandonment Notices must by for final inspection.) : " N-80 11.6# LT&C Casing. S	n results in a multiple complete filed only after all requirements Set at 7041' KB. 30 bbls chem wash; Leac	etion or recompletion nents, including recl tents 700 sx (230	on in a new interval, lamation, have been been been been been been been be	a Form 3160-4 must be filed once	
testing has been completed. Fi determined that the site is ready Production Casing Detail: 6/2/06: 7 7/8" hole, 4 1/2" Cementing detail: Cemer	inal Abandonment Notices must be by for final inspection.) " N-80 11.6# LT&C Casing. So nt 10 bbls fresh water spacer water. Circ pressure 1900 psi	n results in a multiple complete filed only after all requirements Set at 7041' KB. 30 bbls chem wash; Leac	etion or recompletion nents, including recl l cmt 700 sx (230 bbls cmt to surfa	bbis) 65/35 poz.	a Form 3160-4 must be filed once completed, and the operator has Tail cmt 900 sx (235 bbls) 50/50	
testing has been completed. Findetermined that the site is ready Production Casing Detail: 6/2/06: 7 7/8" hole, 4 1/2" Cementing detail: Cemer poz. Displace w/108 bbls w/6/23/06: Pressure test csg	inal Abandonment Notices must be by for final inspection.) I: " N-80 11.6# LT&C Casing. Sont 10 bbls fresh water spacer water. Circ pressure 1900 psi 6000 psi. OK.	n results in a multiple complete filed only after all requirements Set at 7041' KB. 30 bbls chem wash; Leac	etion or recompletion nents, including recl l cmt 700 sx (230 bbls cmt to surfa	bbis) 65/35 poz.	a Form 3160-4 must be filed once completed, and the operator has Tail cmt 900 sx (235 bbls) 50/50	
testing has been completed. Fi determined that the site is ready Production Casing Detail: 6/2/06: 7 7/8" hole, 4 1/2" Cementing detail: Cemer poz. Displace w/108 bbls w 6/23/06: Pressure test csg	inal Abandonment Notices must be by for final inspection.) I: " N-80 11.6# LT&C Casing. Some 10 bbls fresh water spacer water. Circ pressure 1900 psi 6000 psi. OK.	n results in a multiple complete filed only after all requirements of the filed only after all requirements at 7041' KB. 30 bbls chem wash; Lead, burn plug 2500 psi. 80 leads of the filed psi.	etion or recompletion in the second section of recompletion including recommendations and second section in the section i	bbis) 65/35 poz.	a Form 3160-4 must be filed once completed, and the operator has Tail cmt 900 sx (235 bbls) 50/50	
testing has been completed. Findetermined that the site is ready Production Casing Detail: 6/2/06: 7 7/8" hole, 4 1/2" Cementing detail: Cemer poz. Displace w/108 bbls w/6/23/06: Pressure test csg	inal Abandonment Notices must be by for final inspection.) I: " N-80 11.6# LT&C Casing. Some 10 bbls fresh water spacer water. Circ pressure 1900 psi 6000 psi. OK.	n results in a multiple complete filed only after all requirements of the filed only after all requirements at 7041' KB. 30 bbls chem wash; Lead, burn plug 2500 psi. 80 leads of the filed psi.	etion or recompletion nents, including recl l cmt 700 sx (230 bbls cmt to surfa	bbis) 65/35 poz.	a Form 3160-4 must be filed once completed, and the operator has Tail cmt 900 sx (235 bbls) 50/50	
testing has been completed. Fi determined that the site is ready Production Casing Detail: 6/2/06: 7 7/8" hole, 4 1/2" Cementing detail: Cemer poz. Displace w/108 bbls w 6/23/06: Pressure test csg 14. I hereby certify that the for Name (Printed/Typed) Catherine Smit	inal Abandonment Notices must be by for final inspection.) I: "N-80 11.6# LT&C Casing. Some struct 10 bbls fresh water spacer water. Circ pressure 1900 psi geometric comments of the commen	n results in a multiple complete filed only after all requirements of the control	etion or recompletion that is, including reclaiments, including reclaiments, including reclaiments at 1230 bills cmt to surface the surface of the surface o	bbis) 65/35 poz.ce	a Form 3160-4 must be filed once completed, and the operator has Tail cmt 900 sx (235 bbls) 50/50	
testing has been completed. Fi determined that the site is ready Production Casing Detail: 6/2/06: 7 7/8" hole, 4 1/2" Cementing detail: Cemer poz. Displace w/108 bbls w/6/23/06: Pressure test csg 14. I hereby certify that the for Name (Printed/Typed) Catherine Smit	inal Abandonment Notices must be by for final inspection.) I: "N-80 11.6# LT&C Casing. Some struct 10 bbls fresh water spacer water. Circ pressure 1900 psi geometric comments of the commen	results in a multiple complete filed only after all requirements of the desired only after all requirements of	etion or recompletion on recompletion or recompletion on recompletion on the recompletion of the recomplet	bbis) 65/35 poz. ce 06/27/2006 CE USE	a Form 3160-4 must be filed once completed, and the operator has Tail cmt 900 sx (235 bbls) 50/50	
testing has been completed. Fi determined that the site is ready Production Casing Detail: 6/2/06: 7 7/8" hole, 4 1/2" Cementing detail: Cemer poz. Displace w/108 bbls w 6/23/06: Pressure test csg 14. I hereby certify that the for Name (Printed/Typed) Catherine Smit	inal Abandonment Notices must be by for final inspection.) I: " N-80 11.6# LT&C Casing. Some 10 bbls fresh water spacer water. Circ pressure 1900 psi 6000 psi. OK. THIS SPACE FOI The attached. Approval of this notingal or equitable title to those right	results in a multiple complete filed only after all requirements of the desired only after all requirements. Set at 7041' KB. 30 bbls chem wash; Lead, bum plug 2500 psi. 80 lines of the desired of the	etion or recompletion that is, including reclaiments, including reclaiments, including reclaiments at 1230 bills cmt to surface the surface of the surface o	bbis) 65/35 poz. ce 06/27/2006 CE USE	a Form 3160-4 must be filed once completed, and the operator has Tail cmt 900 sx (235 bbls) 50/50	

(Instructions on page 2)

JUL 0 7 2006

NMOCD