submitted in lieu of Form 3160-5 $^{\circ}$

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

CAC 20 0	27 F(\$-9 ECEIVI S D RMINGTON	Legse Number NMSF-078119 If Indian, All. or Tribe Name
2. Name of Operator CONOCOPHILLIPS	7.	Unit Agreement Name
3. Address & Phone No. of Operator	8.	Well Name & Number
PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	Suter #1B API Well No.
4. Location of Well, Footage, Sec., T, R, M		30-045-30617
. Location of Well, Poolage, Sec., 1, 10, 101	10.	Field and Pool
Unit E (SWNW), 1800' FNL & 1135' FWL, Sec. 13, T32N, R11W, NMPM		Blanco Mesaverde
	11.	County and State San Juan -Co., NM
13. Describe Proposed or Completed Operations 4/24/06 MIRU Key #30. ND WH, NU BOP. PT-OK. Kill well. Pull tbg hanger. TOH w/casing to 700#30 min. PT up to 2250#/15 min. OK. RD test unit. TIH & tagged sand plug		
5/19/06 RU WH. Perf'd Lewis @ 417/2-4183'; 4243' - 4279'; 4295' - 4299'; 4324' - 43 holes. RU BJ. Frac'd w/173,960# 16/30 Brady w/395# Flex sand. 1,836,228 scf N2 & 1.6/6/06 MIRU Key #15. Kill well. ND frac valve. NU BOP. OK. Removed tbg hanger. Tw/air-mist. C/O fill. Flowed back. POOH. RIH w/mill. D/O CBP @ 4545'. C/O. TOH & set @ 5293' w/FN @ 5292'. ND BOP, NU WH. Removed BPV. RD & released rig 6	587 bbls 20# I TH w/2-3/8", [. RIH w/179	363'; 4446' - 4452' = 48 Linear gel. RD BJ 5/19/00 tbg. & tagged fill. Circ.
5/19/06 RU WH. Perf'd Lewis @ 417/2-4183'; 4243' - 4279'; 4295' - 4299'; 4324' - 43 holes. RU BJ. Frac'd w/173,960# 16/30 Brady w/395# Flex sand. 1,836,228 scf N2 & 1.6/6/06 MIRU Key #15. Kill well. ND frac valve. NU BOP. OK. Removed tbg hanger. Tw/air-mist. C/O fill. Flowed back. POOH. RIH w/mill. D/O CBP @ 4545'. C/O. TOH	587 bbls 20# I TH w/2-3/8", I. RIH w/179 /13/06.	363'; 4446' - 4452' = 48 inear gel. RD BJ 5/19/0 tbg. & tagged fill. Circ. its 2-3/8", 4.7# J-55 tbg
5/19/06 RU WH. Perf'd Lewis @ 417/-4183'; 4243' - 4279'; 4295' - 4299'; 4324' - 43 holes. RU BJ. Frac'd w/173,960# 16/30 Brady w/395# Flex sand. 1,836,228 scf N2 & 1.6/6/06 MIRU Key #15. Kill well. ND frac valve. NU BOP. OK. Removed tbg hanger. Tw/air-mist. C/O fill. Flowed back. POOH. RIH w/mill. D/O CBP @ 4545'. C/O. TOH & set @ 5293' w/FN @ 5292'. ND BOP, NU WH. Removed BPV. RD & released rig 6 14. I hereby certify that the foregoing is true and correct. Signed Patsy Clugston Title Sr. Regulation of Federal or State Office use)	587 bbls 20# I TH w/2-3/8", I. RIH w/179 /13/06.	363'; 4446' – 4452' = 48 Linear gel. RD BJ 5/19/0 tbg. & tagged fill. Circ. tjts 2-3/8", 4.7# J-55 tbg

NMOCD

PARLINGTON SAME