Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
OM B No. 1004-0137
Expires: March 31, 200

BUREAU OF LAND MANAGEMENT					5. Lease Serial No.			
SUNDRY NOTICES AND REPORTS ON WELLS 14 Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.						SF 078970 6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE- Other instructions on reverse side.						7. If Unit or CA/Agreement, Name and/or No.		
1. Type of Well Oil Well	Type of Well Gas Well Other					Northeast Blanco Unit		
2. Name of Operator Devon Energy Production Company, L.P.						8. Well Name and No. NEBU 240		
3a Address 3b. Phone No. (include area code)						9. API Well No. 30-045-33495		
PO Box 6459, Navajo Dam, NM 87419 405-552-7917					10. Field and Pool, or Exploratory Area			
 Location of Well (Footage, Sec., T., R., M., or Survey Description) SL: 1,160' FNL & 1,315' FWL, NW NW, Unit D, Sec. 18, T31N-R6W 					Rosa Picture Cliffs 11. County or Parish, State			
	WL, NW NW, Unit D, Sec. 18		1		San Juan	, NM		
12. CHECK A	PPROPRIATE BOX(ES) TO	INDICATE	NATURE	OF NOTICE, R	EPORT, OR O	OTHER DATA		
TYPE OF SUBMISSION			TYPE	OF ACTION				
Notice of Intent	Acidize Alter Casing	Deepen		Production (St	art/Resume)	Water Shut-Off		
	Casing Repair	Fracture Tr		Reclamation Recomplete	[Well Integrity Other Casing & Cement		
Subsequent Report	Change Plans	Plug and A		Temporarily A	_	design change		
Final Abandonment Notice	Convert to Injection	Plug Back		Water Disposal				
7", K-55, 23#, LT&C Cas Intermediate String: Cen Lead: 500 sx 50/50 Poz, Diacel Lwl. Tail: 75 sx 50/50 Poz, Yd * Minor variations possi If hole conditions dictate Lead: 575 sx 50/50 Poz v Flocele. Density: 13.0 lb/s	n Company, L.P. gives notificating will be run to a TVD of 3,0 nent will be circulated to surfa Yd-1.45, Water Gal/sk 6.8, Mil-1.45, Water Gal/sk 6.8, Addible due to existing conditions, an alternate, cement design with 50% Class B Cement, 50% gal; Yield: 1.46 cuft/sx; Water h 94#/sx Standard Cement, 0.3	183' the cement ce. xed @ 13ppg tives 2% Gel, vill be used: 6 San Juan Pole: 6 6.42 gal/sx	it program Foamed W 0.2% Vers	is as follows: // N2 Down To 9.0 saset, 0.1% Diacel lad-344, .1% CFR	# Additives 2% Lwl. -3, 3% Bentonit	te, 5#/sx Gilsonite, .25#/sx		
gal/sx		9% Hajad-344	, .25 #/SX P	locele. Density: 1	5.6 ib/gai; Yieid	1: 1.18 cuit/sx; water: 5.23		
* Minor variations possible due to existing conditions ** 4 1/2" casing will be set & cemented as originally proposed. **								
14. I hereby certify that the fore Name (Printed/Typed)	egoing is true and correct					JUL 2008 RELIEVE		
Melisa Zimmeri	man		Title Ser	ior Operations Te	chnician	C OIL CONS. E		
Signature 11/5			Date (6-27-	06	DIST. 3		
	THIS SPACE FOR	FEDERAL	OR ST	ATE OFFICE	USE	El 120202121		
Approved by Origin	al Signed: Stephen Mas	ion	Tit	le	Da	JUL 0 7 2006		
Conditions of approval, if any, are certify that the applicant holds legs which would entitle the applicant t	al or equitable title to those rights i			īce				
	le 43 U.S.C. Section 1212, make it a	a crime for any as to any matte	person kno r within its	wingly and willfully jurisdiction.	to make to any o	department or agency of the United		

(Instructions on page 2)