

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN
DUPLICATE

(See other instructions on
reverse side)

FORM APPROVED
OMB NO. 1004-0137
Expires: February 28, 1995

5. LEASE DESIGNATION AND LEASE NO.
SF-078769

6. IF INDIAN ALLOTTEE OR

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME, WELL NO.
ROSA UNIT #153B

9. API WELL NO.
30-039-27603

10. FIELD AND POOL OR WILDCAT
BLANCO MESAVERDE

11. SEC., T.R.M. OR BLOCK AND
SURVEY OR AREA
NE/4 SE/4 SEC 17-31N-5W

12. COUNTY OR
RIO ARriba

13. STATE
NEW MEXICO

19. ELEVATION CASINGHEAD

14. PERMIT NO.

DATE ISSUED

18. ELEVATIONS (DK. RKB, R.POR, ETC.)
6323' GR

15. DATE
SPUDDED
10/21/2004

16. DATE T.D.
REACHED 12/1/04
11/12/04

17. DATE COMPLETED (READY TO PRODUCE)
12/20/2004

20. TOTAL DEPTH, MD & TVD
8150' MD

21. PLUG BACK T.D., MD & TVD
8132' MD

22. IF MULTICOMP.,
HOW MANY

23. INTERVALS
DRILLED BY

ROTARY TOOLS
x

CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION - TOP, BOTTOM, NAME (MD AND TVD)*
BLANCO MESAVERDE 4796' - 5936'

25. WAS DIRECTIONAL SURVEY MADE
YES

26. TYPE ELECTRIC AND OTHER LOGS RUN
TMDL, GR, CCL & CBL

27. WAS WELL CORED
NO

3 1/2" 9.3" 8/49' 4 3/4" 50 SXS LT TOC
7883' 2683'

28. CASING REPORT (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB/FT	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
10 3/4", K-55	40.5#	343'	14 3/4"	355 SX - SURFACE	
7 7/8", K-55	26.4#	3642'	9 7/8"	720 SX - SURFACE	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
5 1/2", 17#, N-80	0'	7814'	275 SX		2-1/16", J-55, 3.25#	5932'	6032'

31. PERFORATION RECORD (Interval, size, and number)

CH/MEN: 0000', 0000', 13', 44', 53', 63', 87', 96', 8024', 28', 32', 36', 40',
44', 50', 76' & 80'. Total of 32, 0.34" holes
P.L.O.: 0000', 0000', 13', 44', 53', 63', 87', 96', 8024', 28', 32', 36', 40', 44',
50', 76' & 80'. Total of 36, 0.34" holes
See Sundry Notice

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL
(MD)

AMOUNT AND KIND OF MATERIAL USED

4796' - 5615'

Faced w/ 9300# 14/30 LiteProp 125 & 5000# 20/40 brown sand
carried in slick water.

5654' - 5936'

Faced w/ 9300# 14/30 LiteProp 125 & 8100# 20/40 brown sand
carried in slick water.

33. PRODUCTION

DATE OF FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping-size and type of pump)				WELL STATUS (PRODUCING OR SI)	
		Flowing				Producing	
DATE OF TEST	TESTED	CHOKE SIZE	PROD'N FOR TEST PERIOD	OIL - BBL.	GAS - MCF	WATER - BBL.	GAS-OIL RATIO
01/15/05		2"	3 hrs		198		
FLOW TBG PRESS	CASING PRESSURE	CALCULATED 24-HOUR RATE		OIL - BBL.	GAS - MCF	WATER - BBL.	OIL GRAVITY-API (CORR.)
115	750						

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.): TO BE SOLD

TEST WITNESSED BY: Larry Higgins

35. LIST OF ATTACHMENTS: SUMMARY OF POROUS ZONES, WELLBORE DIAGRAM

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED: Tracy Ross TITLE: Sr. Production Analyst DATE: July 10, 2006

ACCEPTED FOR RECORD

JUL 17 2006

NMOC

FARMINGTON FIELD OFFICE

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals, and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries);					38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP		TRUE VERTICAL DEPTH
					NAME	MEASURED DEPTH	
PICTURED CLIFFS	2637						
LEWIS	3167						
CLIFFHOUSE	5387						
MENEFE	5432						
POINT LOOKOUT	5642						
MANCOS	5992						
DAKOTA	7887						