District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144 June 1, 2004

Pit or Below-Grade Tank Registration or Closure

Type of action: Registration of a pit or below-grade tank \(\sum \) Closure of a pit or below-grade tank \(\sum \)				
Operator: BP America Production Company Telephone: (505)326-9200 e-mail address:				
Address: 200 Energy Ct, Farmington, NM 87401				
Facility or well name: Storey ALS#1 API#: 30045 11/79 U/L or Qtr/Qtr A Sec 35 T32N R 11W				
	Longitude			
Surface Owner: Federal State Private Indian	200			
Pit	Below-grade tank			
Type: Drilling Production Disposal	Volume:bbl Type of fluid:	18 19 20		
Workover ☐ Emergency ☐	Construction material:	/ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\		
Lined Unlined				
Liner type: Synthetic Thickness mil Clay		t, explain why not. DEC 2005		
Pit Volumebbl		OIL COMS. DIM.		
	Less than 50 feet	(20 points) UIST 3		
Depth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less than 100 feet	(10 points)		
high water elevation of ground water.)	100 feet or more	(0 points)		
	V			
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)		
water source, or less than 1000 feet from all other water sources.)	No	(0 points)		
Distance to surface water. (harizontal distance to all water de player	Less than 200 feet	(20 points)		
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)		
irrigation canais, ditches, and pereninal and epitemetal watercourses.)	1000 feet or more	(0 points)		
	Ranking Score (Total Points)			
If this is a pit closure: (1) Attach a diagram of the facility showing the pit?	1	ate disposal location: (check the opsite how if		
your are burying in place) onsite offsite If offsite, name of facility				
·				
remediation start date and end date. (4) Groundwater encountered: No 🔲		it. and attach sample results.		
(5) Attach soil sample results and a diagram of sample locations and excava	tions.			
Additional Comments:				
See Attached Documentation				
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit , or an (attached) alternative OCD-approved plan .				
Date: 11/01/2005				
Printed Name/Title Jeffrey C. Blagg, Agent Signature				
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.				
Approval:	, 1/	ስፖሊ 4 4		
Printed Name/Title ON A GAS INSPECTOR, DIST.	Signature BA Sell	Date: UEL 1 9 2005		

CLIENT: BP	P.O. BOX	37, BLO	NEERING, OMFIELD, 332-1199			ATION NO: :	
FIELD REPO	RT: PIT CL	OSURE	VERIFI	CATION	PAG	E No: _/_	of
LOCATION: NAME: STO		WELL #: / RNG: いい		compr. TY: 5J ST: N	DATE	STARTED: 8	
QTR/FOOTAGE: 990 N	1990 E NELSE	CONTRACTO	R: HIGH DESER	r (HEBER)	SPEC	RONMENTAL IALIST:	<u>~~</u>
EXCAVATION APPROX.	NA FT. x NA	FT. x	<u>NA</u> FT.	DEEP. CU	BIC YAF	RDAGE:	NA
DISPOSAL FACILITY:	04-5176		REMEDIA	TION MET	HOD: _	close As	15
LAND USE: RANGE	- Bum	LEASE:	NM 0732	-61	FORMAT	10N:	1V
FIELD NOTES & REM							
DEPTH TO GROUNDWATER: 2					REACE WAT	TER: >100	<u>>0 '</u>
NMOCD RANKING SCORE:					DE 1. T.	F	
SOIL AND EXCAVA	rion =	<u>.</u> ლა. 6382	.	DVM CALIB		100 ppm	RF = 052
DESCRIPTION:						DATE 81	
SOIL TYPE: SAND / SIL	TY SAND / SILT /	SILTY CLAY	/ CLAY / GR	AVEL / OTHE	R BEOR	PCK (SANO	ا عاده ا
SDIL COLOR: MO COHESION (ALL DTHERS):							
CONSISTENCY (NON COHES							
PLASTICITY (CLAYS): NO						HIGHLY PLA	ASTIC N
MOISTURE: DRY / CSLIGH					- '	<u> </u>	
DISCOLORATION/STAINING							<i>surfact</i>
HC ODOR DETECTED: YES			A PIT AIRES	4 oum 3	AMPLE.		
ADDITIONAL COMMENTS: L	nstructed opera	STOR TO P	_	RED FOIL W	NO HTIC	ON IMPRET	3012
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	- PLACE BACK IN TEEL TANK REMO			HOLE ADVA	VŒMENT	·.	
			ELD 418.1 CA				
SCALE SAMP.	TIME SAMPLE I.D.	LAB No:	WEIGHT (g)	mL. FREON	DILUTION	READING CA	ALC. ppm
O FT							
	Organia A	L			ות דו		
PII PER	METER 42	0	VM	P	<u> 11 Pr</u>	ROFILE	
Com	TO WELL HEAD		ULTS				
mp R	WELL	SAMPLE 1D	FIELD HEADSPACE PID (ppm)	7			
14'	HEAD	109	648	7			
BERY	~	2 @ 3 @		-			
	4 <u>e</u> 5 <u>e</u>						
13' \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \							
NOT APPLICABLE							
	B.7.0			_			
				-			
P.D. FOR	mer Loc.		AMPLES]			
	KOTI	10 ~~	1(8015B) 1156	-			
λ	7' 8.6.		× (80218) 11	7			
P.D. = PIT DEPRESSION; B	C = REIOW CDADE	BOTH	PMSSED)	1			
$T.H. = TEST HOLE; \sim = A$	PPROX.; B = BELOW			1			
TRAVEL NOTES: CALL	OUT: 8/20/02-	- MORN.	_ ONSITE:	8/20/02 -	morn.		
l .							

revised: 02/27/02



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

•			
Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 9'	Date Reported:	08-26-02
Laboratory Number:	23618	Date Sampled:	08-20-02
Chain of Custody No:	10086	Date Received:	08-20-02
Sample Matrix:	Soil	Date Extracted:	08-21-02
Preservative:	Cool	Date Analyzed:	08-25-02
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	5.1	0.2
Diesel Range (C10 - C28)	200	0.1
Total Petroleum Hydrocarbons	205	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Storey A LS #1 Compressor Pit.

Mistre m Walter

Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 9'	Date Reported:	08-26-02
Laboratory Number:	23618	Date Sampled:	08-20-02
Chain of Custody:	10086	Date Received:	08-20-02
Sample Matrix:	Soil	Date Analyzed:	08-23-02
Preservative:	Cool	Date Extracted:	08-21-02
Condition:	Cool & Intact	Analysis Requested:	BTEX

		Det.
	Concentration	Limit
Parameter	(ug/Kg)	(ug/Kg)
Benzene	151	1.8
Toluene	99.9	1.7
Ethylbenzene	973	1.5
p,m-Xylene	251	2.2
o-Xylene	294	1.0
Total BTEX	1,770	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	99 %
	1,4-difluorobenzene	99 %
	Bromochlorobenzene	99 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Storey A LS #1 Compressor Pit.

Mister m Welter