District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes 🔀 No 🗌 Type of action: Registration of a pit or below-grade tank 🔲 Closure of a pit or below-grade tank 🔀					
Operator: BP America Production Company Telephon Address: 200 Energy Ct. Farmington, NM 87401 Facility or well name: 444 API #: 5	ne:(505)326-9200	Sec 21 T 29N RBW			
Pit Type: Drilling Production Disposal Workover Emergency Lined Unlined Liner type: Synthetic Thicknessmil Clay Pit Volumebbl	Below-grade tank Volume:bbl Type of fluid: Construction material: Double-walled, with leak detection? Yes If no				
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet 50 feet or more, but less than 100 feet 100 feet or more	(20 points) (10 points) (0 points)			
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes No	(20 points) (0 points)			
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more	(20 points) (10 points) (0 points)			
	Ranking Score (Total Points)				
If this is a pit closure: (1) Attach a diagram of the facility showing the pit' your are burying in place) onsite offsite If offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No (5) Attach soil sample results and a diagram of sample locations and excavate	Yes If yes, show depth below ground surface	description of remedial action taken including			
Additional Comments: See Attached Documentation	DEC 2005 PECEIVED PECINED DIST. 3	A STATE OF THE STA			
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit , or an (attached) alternative OCD-approved plan . Date:					
otherwise endanger public health or the environment. Nor does it relieve t regulations. Approval: Printed Name/Title GEFUTY OIL & GAS INSPECTOR, DIST.	he oper#for of its responsibility for compliance with a	Date: DEC 1 9 2005			

170			NEERING	•	LO	CATION NO:	B1098
CLIENT: BP	P.O. BOX	87, BLO 505) 632		, NM 874	13	CR NO:	10429
FIELD REPO	FIELD REPORT: PIT CLOSURE VERIFICATION PAGE No: of						of\
LOCATION: NAME: +	TUCHES B	WELL#:	<u>6</u> туре	DEHL			11-15-02
	21 TWP: 29 N RNG					RONMENTAL	11-13 00
	2/1725/2 5) SPE	CIALIST:	JCB_
EXCAVATION APP						DAGE:	
disposal facility: land use:Rang	NA NA					CLOSE A	<u> </u>
FIELD NOTES & RE							\ <u>\</u>
DEPTH TO GROUNDWATER:						•	WELLHEAD. >(のひノ
NMOCD RANKING SCORE:			5000 pp		ORFACE WA		
SOIL AND EXCAV	ATION DESCRIPT	ION:		OVM CALIB.			
<u> </u>	711OH BEGGH	1011.		OVM CALIB.			RF = 0.52
SOIL TYPE: SAND / SILT	Y SAND / SILT / SILTY C	CLAY CLAY /	GRAVEL / OTH				
SOIL COLOR: GRAY: COHESION (ALL OTHERS): N	SH BROWN	COHESIVE CO	HESIVE)/ HIGHLY	COHESIVE			
CONSISTENCY (NON COHES				001120172			
PLASTICITY (CLAYS): NON P				HIGHLY PLAST	IC		
DENSITY (COHESIVE CLAYS MOISTURE: DRY (SLIGHTLY						CLOS	ED
DISCOLORATION/STAINING			CONTOUNTED				
HC ODOR DETECTED: YES /(
SAMPLE TYPE: GRAB) COM ADDITIONAL COMMENTS: _	POSITE - # OF PTS. PIT	w/ 95 B	BL STEEL 7	ANK. USE	D BACK	WE 70 /	REMOVE
-	TANK Y DIG T	EST TRENS					
<u> </u>	CONTAMINATION						
SCALE 5.12	(D. 770 (D. 77	1	LD 418.1 CALC				love ()
SAM	IP. TIME SAMP. ID	LAB NO.	WEIGHT (g)	mL FREON	DILUTIO	NREADING	CALC. (ppm)
O _A FT							
N PIT PERI	METER				PIT	PROFIL	Ē
	SAMPLE		VM				
14 -		SAMPLE	DING FIELD HEADSPACE				
TEST		1@8	(ppm) Oe 3				
HOLE	`\\\\\	2@	<i>Oa</i> 5				
8'86		3@					
1: 0	14	4 @ 5 @		-	**		
,					T AP	PLICABL	Æ.
				\dashv			
7	TANK			_			
	fuet for	DANES E	AMPLES	_			
PD	10 PRINT	COP TO	NALYSIS TIME	-			
6'BG	J well	Ox	ಬಾಕು)				
BD - BE DEDBESSION S.C.	V						
P.D. = PIT DEPRESSION; B.G. = BELOW GRADE; B = BELOW T.H. = TEST HOLE; ~ = APPROX.; T.B. = TANK BOTTOM							
TRAVEL NOTES: CALLOUT: 11-15-02 0945 ONSITE: 11-15-02 1100							



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Dehy C @ 8'	Date Reported:	11-19-02
Laboratory Number:	24265	Date Sampled:	11-15-02
Chain of Custody No:	10429	Date Received:	11-18-02
Sample Matrix:	Soil	Date Extracted:	11-18-02
Preservative:	Cool	Date Analyzed:	11-19-02
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)	
Gasoline Range (C5 - C10)	ND	0.2	
Diesel Range (C10 - C28)	55.2	0.1	
Total Petroleum Hydrocarbons	55.2	0.2	

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Hughes B #6.

Analyst C. Og

Mister of Walters
Review