District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

June 1, 2004 drilling and production facilities, submit to

Form C-144

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Pit or Below-Grade Tank Registration or Closure Is nit or below-grade tank covered by a "general plan"? Yes 🔀 No

Type of action: Registration of a pit of	or below-grade tank \(\text{ Closure of a pit or below-grade} \)	nde tank 🔀	
Onesster: DR America Production Company Telephon	ne: (505)326-0200 e-mail address:		
Operator: BP America Production Company Telephone: (505)326-9200 e-mail address: Address: 200 Energy Ct, Farmington, NM 87401			
Facility or well name: Harton Com L5#9 API#:	30045 10170 W. or Otr/Otr B	Sec. 32 T3/N R 117/	
County: San Juan Latitude			
Surface Owner: Federal State Private Indian			
Pit	Below-grade tank		
Type: Drilling Production Disposal	Volume:bbl Type of fluid:		
Workover Emergency	Construction material:		
Lined Unlined	Double-walled, with leak detection? Yes If not, explain why not.		
Liner type: Synthetic Thicknessmil Clay _			
Pit Volumebbl			
	Less than 50 feet	(20 points)	
Depth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less than 100 feet	(10 points)	
high water elevation of ground water.)	100 feet or more	(0 points)	
	Voc	(20 mainta)	
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)	
water source, or less than 1000 feet from all other water sources.)	140	(o points)	
Distance to surface water: (horizontal distance to all wetlands, playas,	Less than 200 feet	(20 points)	
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)	
inigation canality, diversely, and performant and optionional water-contribution	1000 feet or more	(0 points)	
	Ranking Score (Total Points)		
If this is a pit closure: (1) Attach a diagram of the facility showing the pit	's relationship to other equipment and tanks (2) India	rate disposal location: (check the onsite box if	
your are burying in place) onsite of offsite. If offsite, name of facility			
remediation start date and end date. (4) Groundwater encountered: No			
		it. and attach sample results.	
(5) Attach soil sample results and a diagram of sample locations and excava	nons.		
Additional Comments:			
See Attached Documentation			
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit , or an (attached) alternative OCD-approved plan .			
Date: 11/01/2005			
Date: 11/01/2005 Printed Name/Title Jeffrey C. Blagg, Agent Signature L. Signature			
Your certification and NMOCD approval of this application/closure does	- J-/	s of the nit or tank contaminate ground water or	
otherwise endanger public health or the environment. Nor does it relieve t regulations.			
Approval: Signature Signature Date: DEC 1 9 2005			

	CLIENT: BP BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199 C.O.C. ND: 10031
	FIELD REPORT: PIT CLOSURE VERIFICATION PAGE No: 1 of 1
Į	LOCATION: NAME: HEATON COM WELL #: 9 TYPE: DEHY DATE STARTED: 6-25-02
	QUAD/UNIT: SEC: 34 TWP: 31N RNG: 11W PM: NM CNTY: 33 ST: MM
-	OTR/FOOTAGE: 990 W/1495 NUME CONTRACTOR: HIGH DESERT (HEBER) SPECIALIST:
	EXCAVATION APPROX. 12 FT. x 12 FT. x 3 FT. DEEP. CUBIC YARDAGE: O
	LAND USE: RANGE -BLM LEASE: MANN 073545 FORMATION: MV/PC
}	LAND USE: RANGE -BOM LEASE: MANN 073545 FORMATION: MV/PC FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 93 FT. S12°W FROM WELLHEAD.
+	DEPTH TO GROUNDWATER: >/W NEAREST WATER SOURCE: >/WW NEAREST SURFACE WATER: >/WW
	NMOCD RANKING SCORE: O NMOCD TPH CLOSURE STD: 5000 PPM
İ	SOIL AND EVENUATION DVM CALIB. READ. 129.7 ppm
	DESCRIPTION: OVM CALIB. GAS = 250 ppm RF = 0.52 TIME: 1330 am/pm DATE: 6-25 - 0.2
	SDIL TYPE: SAND (SILTY SAND) SILT / SILTY CLAY / CLAY / GRAVEL / OTHER BENRUCK @ 6
	SOIL COLOR: GRAY - BLACK COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY COHESIVE / HIGHLY COHESIVE
	CONSISTENCY (NON COHESIVE SOILS): LOOSE / FIRM / DENSE / VERY DENSE
	PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD CLOSED
	MOISTURE DRY (SLIGHTLY MOIST) MOIST / WET / SATURATED / SUPER SATURATED DISCOLORATION/STAINING OBSERVED (YES) / NO EXPLANATION - GRAY YO BLACK
ļ	HC ODOR DETECTED (YES / NO EXPLANATION - MODERATE
.	SAMPLE TYPE: (GRAD / COMPOSITE - # OF PTS
	BEDROCK
	FIELD 418.1 CALCULATIONS
	SCALE SAMP. TIME SAMPLE I.D. LAB No: WEIGHT (g) ML. FREON DILUTION READING CALC. ppm
	O FT
	7, PIT PERIMETER PIT PROFILE
	OVM OVM
	TEOULO
	SAMPLE FIELD HEADSPACE PID (ppm) 1 @ 6 Z Z Z
	$\begin{array}{c c} & 2 & e \\ \hline & 3 & e \end{array}$
	A 4 @ 100 100 100 100 100 100 100 100 100 1
	A GANNING
SP	mple 12 3']
	3 6 19
	LAB SAMPLES
	SAMPLE ANALYSIS TIME
	TH PD B6) (3' B6) (3' B6) SANDSTONE
	T.H. = TEST HOLE; ~ = APPROX.; B = BELOW
	TRAVEL NOTES: CALLOUT: 6-25-2 1000 ONSITE: 6-25-2 1245



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

1			
Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Dehy C @ 6'	Date Reported:	06-27-02
Laboratory Number	23159	Date Sampled:	06-25-02
Chain of Custody No:	10031	Date Received:	06-25-02
Sample Matrix:	Soil	Date Extracted:	06-25-02
Preservative:	Cool	Date Analyzed:	06-27-02
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	2,010	0.2
Diesel Range (C10 - C28)	28.3	0.1
Total Petroleum Hydrocarbons	2,040	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Heaton Com LS #9.

Analyst Caputa

Review Walters

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Dehy C @ 6'	Date Reported:	06-27-02
Laboratory Number:	23159	Date Sampled:	06-25-02
Chain of Custody:	10031	Date Received:	06-25-02
Sample Matrix:	Soil	Date Analyzed:	06-27 - 02
Preservative:	Cool	Date Extracted:	06-25-02
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
		·
Berzene	24.7	1.8
Toluene	87.3	1.7
Ethylbenzene	ND	1.5
p,m-Xylene	8.8	2.2
o-Xylene	ND	1.0
Total BTEX	121	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
:	Fluorobenzene	96 %
	1,4-difluorobenzene	96 %
1	Bromochlorobenzene	96 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Heaton Com LS #9.

Analyst Caput

Mister m Wester