District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources**

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Pit or Below-Grade Tank Registration or Closure Is pit or below-grade tank covered by a "general plan"? Yes No Decoration: Registration of a pit or below-grade tank Closure of a pit or below-grade tank

Operator: BP America Production Company Telephon	ne:(505)326-9200e-mail address:					
Address: 200 Energy Ct, Farmington, NM 87401						
Facility or well name: MCEWER GC#1A API#: 3	30045	$\sum_{\text{Sec}} 5 \text{T} \frac{31N}{N} \text{R} \frac{10\omega}{M}$				
County: San Juan Latitude	Longitude	NAD: 1927 🗌 1983 🔲				
Surface Owner: Federal State Private Indian						
Pit	Below-grade tank					
Type: Drilling Production Disposal	Volume:bbl Type of fluid:					
Workover ☐ Emergency ☐	Construction material:					
Lined Unlined	Double-walled, with leak detection? Yes If not, explain why not.					
Liner type: Synthetic Thicknessmil Clay						
Pit Volumebbl		18 19 79 30 ST				
	Less than 50 feet	(20 points)				
Depth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less than 100 feet	(10 points) DEC 2005				
high water elevation of ground water.)	100 feet or more	(0 points)				
	Yes	(20 points)) Due Duy				
Wellhead protection area: (Less than 200 feet from a private domestic	No	(0 points)				
water source, or less than 1000 feet from all other water sources.)		To and the same of				
Distance to surface water: (horizontal distance to all wetlands, playas,	Less than 200 feet	(20 points)				
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)				
inigation during, discrete, and personnel and opinionistal water-outside,	1000 feet or more	(0 points)				
	Ranking Score (Total Points)					
If this is a pit closure: (1) Attach a diagram of the facility showing the pit	Personal in the other equipment and touler (2) Ind	lights dismosal laggetion; (shook the angite boy if				
your are burying in place) onsite offsite I foffsite, name of facility						
remediation start date and end date. (4) Groundwater encountered: No [ft. and attach sample results.				
(5) Attach soil sample results and a diagram of sample locations and excava	tions.					
Additional Comments:						
See Attached Documentation						
I hereby certify that the information above is true and complete to the best						
has been/will be constructed or closed according to NMOCD guideline	es 🔼, a general permit 🗀, or an (attached) atteri	nauve OCD-approved plan .				
Date: 11/01/2005						
Printed Name/Title Jeffrey C. Blagg, Agent Signature Lifty C. Sligg						
Your certification and NMOCD approval of this application/closure does otherwise endanger public health or the environment. Nor does it relieve regulations.	not relieve the operator of liability should the conten					
Approval: CFGV CL & GAS NISPECTOR, DIST. (Printed Name/Title	Signature B.L. T.M.	DEC 1 9 2005				

3--15----CLIENT: ___BP BLAGG ENGINEERING, INC. LOCATION NO: 80983 P.O. BOX 87, BLOOMFIELD, NM 87413 C.D.C. ND: ____ (505) 632-1199FIELD REPORT: PIT CLOSURE VERIFICATION PAGE No: / of / LOCATION: NAME: MEEWED GC WELL #: IA TYPE: BLOW DATE STARTED: 5/28/02 DATE FINISHED: QUAD/UNIT: D SEC: 5 TWP: 310 RNG: 10W PM: NM CNTY: 5J ST: NM ENVIRONMENTAL QTR/FOOTAGE:525/2/565 W JULY CONTRACTOR: HIGH DESERT (HERER) SPECIALIST: EXCAVATION APPROX. NA FT. x NA FT. x NA FT. DEEP. CUBIC YARDAGE: DISPOSAL FACILITY: ON-SITE REMEDIATION METHOD: CLOSE AS IS LEASE: CA SRMIZ93 LAND USE: KANGE - BLM FORMATION: FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 10 FT. 5100 FROM WELLHEAD DEPTH TO GROUNDWATER: >100 NEAREST WATER SOURCE: >1000 NEAREST SURFACE WATER: >1000 NMOCD RANKING SCORE: _ O NMOCD TPH CLOSURE STD: 5000 PPM OVM CALIB. READ. 52.8 ppm SOIL AND EXCAVATION DVM CALIB. GAS = 100 ppm RF = 0.52DESCRIPTION: TIME: 10:35 60/DM DATE: 5/28/02 SOIL TYPE: (SAND) SILTY SAND / SILT / SILTY CLAY / CLAY / GRAVEL / OTHER GROVEL
SOIL COLOR: OK. YELL ORRNOE TO OK. GREEWISH GRAY(W/GROVEL) 7-8 BELOW GRAVE COHESION (ALL OTHERS) (NON-COHESIVE) SLIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIVE CONSISTENCY (NON COHESIVE SOILS): LOOSE / FIRM / DENSE / VERY DENSE PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD CLOSED MOISTURE: DRY / SLIGHTLY MOIST / WET / SATURATED / SUPER SATURATED DISCOLORATION/STAINING OBSERVED: YES /ND EXPLANATION -HC ODOR DETECTED: YES / NO EXPLANATION -SAMPLE TYPE: GRAB COMPOSITE - # OF PTS. ADDITIONAL COMMENTS: NO TPH ANALYSIS WITH FIELD 418.1 CALCULATIONS SCALE SAMP. TIME SAMPLE I.D. LAB NO: WEIGHT (q) |ml. FREON | DILUTION | READING | CALC. ppm

O FT							
PIT PERIMETER 1/2			PIT PROFILE				
T.H. P.D. = PIT DEPRESSION; B.G. = BELOW GRADE T.H. = TEST HOLE; ~ = APPROX; B = BELOW TRAVEL NOTES: CALLOUT: 5/28/62	O RES SAMPLE 10 1 @ 8' 2 @ 3 @ 4 @ 5 @ LAB S SAMPLE 1D AN	VM ULTS FIELD HEADSPACE PID (ppm) O. O AMPLES ALYSIS TIME (ISEC		UOT ,	APPLI CA		

revised: 02/27/02