District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144 June 1, 2004

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes 🔀 No 📋 Type of action: Registration of a pit or below-grade tank 🔲 Closure of a pit or below-grade tank 🔀				
Address: 200 Energy Ct, Farmington, NM 87401,	ne: (505)326-9200 e-mail address:			
Facility or well name: Heaton Com 8#2 API#:				
	Longitude	NAD: 1927 🗌 1983 🗍		
Surface Owner: Federal State Private Indian				
Pit Type: Drilling Production Disposal Workover Emergency Lined Unlined Liner type: Synthetic Thicknessmil Clay Pit Volumebbl	Below-grade tank Volume:bbl Type of fluid: Construction material: Double-walled, with leak detection? Yes			
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet 50 feet or more, but less than 100 feet 100 feet or more	(20 points) (10 points) (0 points)		
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes No	(20 points) (0 points)		
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more	(20 points) (10 points) (0 points)		
	Ranking Score (Total Points)			
If this is a pit closure: (1) Attach a diagram of the facility showing the pit your are burying in place) onsite offsite If offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No Attach soil sample results and a diagram of sample locations and excaval Additional Comments:	Yes If yes, show depth below ground surface	description of remedial action taken including		
See Attached Documentation				
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline	of my knowledge and belief. I further certify that es X, a general permit , or an (attached) altern	the above-described pit or below-grade tank ative OCD-approved plan .		
Date: 11/01/2005 Printed Name/Title Jeffrey C. Blagg, Agent Signa Your certification and NMOCD approval of this application/closure does otherwise endanger public health or the environment. Nor does it relieve regulations.	not relieve the operator of liability should the content the operator of its responsibility for compliance with	ts of the pit or tank contaminate ground water or any other federal, state, or local laws and/or		
Approval: EFFTO GL & GAS INTERCTICA, DIST. &	Signature Refer File	DEC 1 9 2005		

BLAGG ENGINEERING, P.O. BOX 87, BLOOMFIELD, (505) 632-1199		LOCATION NO:			
FIELD REPORT: PIT CLOSURE VERIFIC	CATION	PAGE No:/			
QUAD/UNIT: A SEC: 30 TWP: 3/2 RNG: 1/W PM:NM CNT	TY: SJ ST: NM	LENNIDONIMENTAL			
QTR/FOOTAGE: 990'N/990 = NEINE CONTRACTOR: FLINT		SPECIALIST:			
EXCAVATION APPROX. NA FT. x NA FT. x NA FT. E	DEEP. CUBIC	YARDAGE:	AN		
DISPOSAL FACILITY: ON-SITE REMEDIA			i i		
LAND USE: RANGE - BLM LEASE: CA SRM	1508 FO	RMATION:	K		
FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY					
DEPTH TO GROUNDWATER: >100 NEAREST WATER SOURCE: >1000/		E WATER: >/80	∞′		
NMOCD RANKING SCORE: NMOCD TPH CLOSURE STD: 5000 PPM					
SOIL AND EXCAVATION	1	AD. 52.4 ppm S = 120 ppm	PF = 052		
DESCRIPTION:		am 600 DATE: 31			
SOIL TYPE: SAND / SILT / SILTY CLAY / CLAY / GRA	AVEL / DTHER _				
SOIL COLOR: MOO. TO. DK. YELL BROWN COHESION (ALL OTHERS): (NON COHESIVE) SLIGHTLY COHESIVE / COH	HESIVE / HIGHL	Y CDHESIVE			
CONSISTENCY (NON COHESIVE SOILS): LODSE / CIRM / DENSE / VERY	Y DENSE				
PHASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE DENSITY (COHESIVE CLAYS & SILTS): SDFT / FIRM / STIFF / VERY			ASTIC		
MOISTURE: DRY / &LIGHTLY MOIST / WET / SATURATED / SI		CLOSED			
DISCOLORATION/STAINING OBSERVED: YES / ND EXPLANATION - HC ODOR DETECTED: YES / ND EXPLANATION -					
SAMPLE TYPE: GRAB / COMPOSITE - # OF PTS					
ADDITIONAL COMMENTS:					
		······································			
FIELD 418.1 CAL					
SCALE SAMP. TIME SAMPLE I.D. LAB No: WEIGHT (g)	nL. FREON DILL	JTION READING (CALC. ppm		
O FT					
PIT PERIMETER N	PIT	PROFILE			
OVM	1 11	TIOTIL			
RESULTS					
SAMPLE FIELD HEADSPACE ID PID (ppm)					
18' 10' 0.0					
3 @					
8.6.					
)	. ~07	- APPLICABLE	<i>:</i>		
T. H.					
126'	1				
B.P.D.	1				
SEP LAB SAMPLES SAMPLE ANALYSIS TIME					
De 10 TPH (8015B) 0825	-				
J Jew (7055ED)	1				
P.D. = PIT DEPRESSION; B.G. = BELOW GRADE	1				
TRAVEL NOTES: CALLOUT: 3(14/02 - more) ONSITE:	3/15/02-ma	·64 ·			
CALLOUT: WINDSTE:	,				



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 10'	Date Reported:	03-20-02
Laboratory Number:	22305	Date Sampled:	03-15-02
Chain of Custody No:	9799	Date Received:	03-15-02
Sample Matrix:	Soil	Date Extracted:	03-18-02
Preservative:	Cool	Date Analyzed:	03-20-02
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND ·	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2

ND - Parameter not detected at the stated detection limit.

References: Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments: Heaton Com B #2 Separator Pit Grab Sample.

Analyst Column

Review Wasters