District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Pit or Below-Grade Tank Registration or Closure

Type of action: Registration of a pit of	or below-grade tank [] Closure of a pit or below-gra	de tank			
Operator: BP America Production Company Telephor	ne: <u>(505)326-9200</u> e-mail address:				
<u> </u>		•			
Facility or well name: Mudge A #55 API#: 3	50045 29004 U/L or Qtr/Qtr 67	SecLT 3/N_R 11 W			
County: San Juan Latitude	Longitude	NAD: 1927 🗌 1983 🗍			
Surface Owner: Federal State Private Indian					
<u>Pit</u>	Below-grade tank Volume:bbl Type of fluid: Construction material: Double-walled, with leak detection? Yes If not, explain why not.				
Type: Drilling Production Disposal					
Workover					
Lined Unlined					
Liner type: Synthetic Thicknessmil Clay					
Pit Volumebbl					
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points)			
• • • • • • • • • • • • • • • • • • • •	50 feet or more, but less than 100 feet	(10 points)			
high water elevation of ground water.)	100 feet or more	(0 points)			
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)			
water source, or less than 1000 feet from all other water sources.)	No	(0 points)			
water source, or less than 1000 feet from an other water sources.	Less than 200 feet	(20 points)			
Distance to surface water: (horizontal distance to all wetlands, playas,	200 feet or more, but less than 1000 feet	1			
irrigation canals, ditches, and perennial and ephemeral watercourses.)	, i	(10 points)			
	1000 feet or more	(0 points)			
	Ranking Score (Total Points)				
If this is a pit closure: (1) Attach a diagram of the facility showing the pit	s relationship to other equipment and tanks. (2) Indica	ate disposal location: (check the onsite box if			
your are burying in place) onsite 🔲 offsite 🔲 If offsite, name of facility_	(3) Attach a general d	lescription of remedial action taken including			
remediation start date and end date. (4) Groundwater encountered: No 🔲	Yes If yes, show depth below ground surface	ft. and attach sample results.			
(5) Attach soil sample results and a diagram of sample locations and excava	tions.	18 10 3			
Additional Comments:	12/12/10 W	1000			
See Attached Documentation	DEC DEC				
	ERE	2005			
	E VIL COA	19 2			
······································	To DIST	- 1 Harry			
	100	· 68			
	4.0	- 1 1/2 (2)			
I hereby certify that the information above is true and complete to the best	of my knowledge and belief. I further certify that the	he above-described pit or below-grade tank			
has been/will be constructed or closed according to NMOCD guideline	es 🔼, a general permit 📙, or an (attached) alterna	tive OCD-approved plan [
Date: 11/01/2005	1.				
Printed Name/Title Jeffrey C. Blagg, Agent Signature					
Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve to regulations.					
Approval: CA C GAS INSPECTOR, DIST. C	Signature BL Bell	DEC 1 9 2005			

CLIENT: BP	BLAGG ENG P.O. BOX 87, BLO (505)		113 LOCATION NO: <u>80954</u> C.O.C. NO: <u>9812</u>		
FIELD REPORT	T: PIT CLOSURE	C VERIFICATION			
LOCATION: NAME: MUDO			DATE STARTED: 4/16/02 DATE FINISHED:		
	TWP:3(A) RNG: 11W	, ,	ENVIRONMENTAL NV		
	SIDE SWIDE CONTRACTO				
1	02-211E				
	Bim LEASE: _				
			T. S63€ FROM WELLHEAD.		
	NEAREST WATER SOURCE				
NMOCD RANKING SCORE:	NMOCD TPH CLOSURE STI	5000 PPM			
SOIL AND EXCAVATION	ON	1	B. READ. 52.7 ppm		
DESCRIPTION:	_		B. GAS = 100 ppm RF = 0.52 0 am/pm DATE: 4/16/02		
SDIL TYPE: SAND / SILTY	SAND / SILT / SILTY CLAY	/ CLAY / GRAVEL / DT	HER BEDROCK (SANOSTONE)		
	ON COHESIVE / SLIGHTLY C				
	E SOILS): (LODSD / FIRM / PLASTIC / SLIGHTLY PLASTI		DIASTIC / HIGHLY DIASTIC		
DENSITY (COHESIVE CLAYS	& SILTS): SOFT / FIRM /	STIFF / VERY STIFF / H	ARD CLOSED		
MOISTURE: DRY / SLIGHTLY	MOIST / MOIST / WET / S	SATURATED / SUPER SATU ANATION - Sm. OWASTIT	RAILD		
DISCOLORATION/STAINING OBSERVED: (ES) / NO EXPLANATION - SM. QUANTITY AROUND TANK BOTTOM.					
ADDITIONAL COMMENTS: 75	MPOSITE - # OF PTS TEEL TANK REMOVED	PRIOR TO SAMPLINE	. COMPENIENT BEORDER		
	COUNTERED UERY HARD	> , TO STAINING OR O	iscoloration observed		
		[ELD 418.1 CALCULATION	18		
SCALE SAMP. TI	ME SAMPLE I.D. LAB No:	WEIGHT (g) mL. FREON	DILUTION READING CALC. ppm		
O FT					
PIT PERIM	ETER 12		PIT PROFILE		
		MV(
-	TANK SAMPLE	SULTS FIELD HEADSPACE			
17'	1 @ 8	PID (ppm)			
TO	2 <u>e</u> 3 <u>e</u>				
HEAD	19' 4 @ 5 @				
الكما ح		No.	T APPLICABLE		
P.D. 7					
~ 5 SER		I F			
T.H.~3 B. TANK LAB SAMPLES					
T.H.~3 B.	TAPK LAB S	SAMPLES			
Т.H.~3 В. Вопом	TANK LAB S	NALYSIS TIME			
T.H.~3 B.	TANK SAMPLE A Des' TPA	NALYSIS TIME H (BDISB) 1 435			
T.H.~3 B. Bottom	TANK LAB S SAMPLE A ID OES TAN	NALYSIS TIME			
P.D. = PIT DEPRESSION; B.G. T.H. = TEST HOLE; ~ = APPE	TANK LAB S SAMPLE ID A De 8' TPA TRANK BELOW GRADE ROX.; B = BELOW	NALYSIS TIME H (80158) 1 435			
T, H .~ 3 B. Somo P.D. = PIT DEPRESSION; B.G.	TANK LAB S SAMPLE ID A De 8' TPA TRANK BELOW GRADE ROX.; B = BELOW	NALYSIS TIME H (BDISB) 1 435	- AFTER .		



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 8'	Date Reported:	04-19-02
Laboratory Number:	22558	Date Sampled:	04-16-02
Chain of Custody No:	9812	Date Received:	04-17-02
Sample Matrix:	Soil	Date Extracted:	04-18-02
Preservative:	Cool	Date Analyzed:	04-19-02
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Mudge A #55 Separator Pit G

Grab Sample.

Analyst C. Oglina

Christin m Walters