

District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Avenue, Artesia, NM 88210  
District III  
1000 Rio Brazos Road, Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy Minerals and Natural Resources

Oil Conservation Division  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-144  
June 1, 2004

For drilling and production facilities, submit to appropriate NMOCD District Office.  
For downstream facilities, submit to Santa Fe office


**Pit or Below-Grade Tank Registration or Closure**

Is pit or below-grade tank covered by a "general plan"? Yes ☒ No ☐

Type of action: Registration of a pit or below-grade tank ☐ Closure of a pit or below-grade tank ☒

Operator: <u>BP America Production Company</u> Telephone: <u>(505)326-9200</u> e-mail address: _____		
Address: <u>200 Energy Ct. Farmington, NM 87401</u>		
Facility or well name: <u>Sellers Ls#2</u> API #: <u>3004509241</u> U/L or Qtr/Qtr <u>B</u> Sec <u>30</u> T <u>30N</u> R <u>10W</u>		
County: <u>San Juan</u> Latitude _____ Longitude _____ NAD: 1927 <input type="checkbox"/> 1983 <input type="checkbox"/>		
Surface Owner: Federal <input type="checkbox"/> State <input type="checkbox"/> Private <input type="checkbox"/> Indian <input type="checkbox"/>		
<b>Pit</b> Type: Drilling <input type="checkbox"/> Production <input type="checkbox"/> Disposal <input checked="" type="checkbox"/> Workover <input type="checkbox"/> Emergency <input type="checkbox"/> Lined <input type="checkbox"/> Unlined <input type="checkbox"/> Liner type: Synthetic <input type="checkbox"/> Thickness _____ mil Clay <input type="checkbox"/> Pit Volume _____ bbl	<b>Below-grade tank</b> Volume: _____ bbl Type of fluid: _____ Construction material: _____ Double-walled, with leak detection? Yes <input type="checkbox"/> If not, explain why not. _____	
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet	(20 points)
	50 feet or more, but less than 100 feet	(10 points)
	100 feet or more	( 0 points)
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes	(20 points)
	No	( 0 points)
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet	(20 points)
	200 feet or more, but less than 1000 feet	(10 points)
	1000 feet or more	( 0 points)
Ranking Score (Total Points)		

If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if you are burying in place) onsite ☐ offsite ☐ If offsite, name of facility \_\_\_\_\_. (3) Attach a general description of remedial action taken including remediation start date and end date. (4) Groundwater encountered: No ☐ Yes ☐ If yes, show depth below ground surface \_\_\_\_\_ ft. and attach sample results. (5) Attach soil sample results and a diagram of sample locations and excavations.

Additional Comments:
See Attached Documentation


I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☒, a general permit ☐, or an (attached) alternative OCD-approved plan ☐.

Date: 11/01/2005

Printed Name/Title Jeffrey C. Blagg, Agent

Signature Jeffrey C. Blagg

Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.

Approval:

Printed Name/Title DEPUTY OIL & GAS INSPECTOR, DIST. 59

Signature Bob Loh

Date:

DEC 19 2005

CLIENT: <u>BP</u>	BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199	LOCATION NO: <u>80949</u> C.O.C. NO: <u>9820</u>
FIELD REPORT: PIT CLOSURE VERIFICATION		PAGE No: <u>1</u> of <u>1</u>
LOCATION: NAME: <u>SELLERS LS WELL # 2</u> TYPE: <u>ABD # 2</u>		DATE STARTED: <u>4-11-02</u> DATE FINISHED: <u>4-11-02</u>
QUAD/UNIT: <u>B SEC: 30 TWP: 30N RNG: 10W PM: NM CNTY: SJ ST: NM</u>		ENVIRONMENTAL SPECIALIST: <u>JCB</u>
QTR/FOOTAGE: <u>990FNL * 1650 FEL</u> <sup>WINE</sup> CONTRACTOR: <u>FLINT</u>		
EXCAVATION APPROX. <u>18</u> FT. x <u>18</u> FT. x <u>4</u> FT. DEEP. CUBIC YARDAGE: <u>0</u>		
DISPOSAL FACILITY: <u>NA</u> REMEDIATION METHOD: <u>CLOSE AS IS</u>		
LAND USE: <u>RANGE - BLM</u> LEASE: <u>SF - 078195</u> FORMATION: <u>OK</u>		
FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY <u>85</u> FT. <u>S 31°W</u> FROM WELLHEAD.		
DEPTH TO GROUNDWATER: <u>&gt;100</u> NEAREST WATER SOURCE: <u>&gt;1000</u> NEAREST SURFACE WATER: <u>&gt;1000</u>		
NMCD RANKING SCORE: <u>0</u> NMCD TPH CLOSURE STD: <u>5000</u> PPM		
SOIL AND EXCAVATION DESCRIPTION:		DVM CALIB. READ: <u>129.7</u> ppm DVM CALIB. GAS = <u>250</u> ppm RF = <u>0.52</u> TIME: <u>1005</u> am/pm DATE: <u>4-11-02</u>
SOIL TYPE: SAND / SILTY SAND / SILT / SILTY CLAY / CLAY / GRAVEL / OTHER <u>SS. Bedrock @ 5'</u>		
SOIL COLOR: <u>Yellow TAN 0'-5', Black @ 5'</u>		
COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIVE		
CONSISTENCY (NON COHESIVE SOILS): LOOSE / FIRM / DENSE / <u>VERY DENSE</u>		
PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC		
DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / <u>HARD</u> <span style="border: 1px solid black; border-radius: 50%; padding: 2px;">Risk Assessed</span>		
MOISTURE: DRY / SLIGHTLY MOIST / <u>MOIST</u> / WET / SATURATED / SUPER SATURATED		
DISCOLORATION/STAINING OBSERVED: <u>YES</u> NO EXPLANATION - <u>Black @ 5'</u>		
HC ODOR DETECTED: <u>YES</u> NO EXPLANATION - <u>STRONG</u>		
SAMPLE TYPE: <u>GRAB</u> / COMPOSITE - # OF PTS. <u>1</u>		
ADDITIONAL COMMENTS: <u>USE BACKHOE TO DIG TEST Hole &amp; SAMPLE.</u> <span style="border: 1px solid black; padding: 2px;">BEDROCK BOTTOM</span>		

FIELD 418.1 CALCULATIONS							
SAMP. TIME	SAMPLE I.D.	LAB No:	WEIGHT (g)	mL. FREON	DILUTION	READING	CALC. ppm

**PIT PERIMETER**

**PIT PROFILE**

NOT APPLICABLE

OVM RESULTS		
SAMPLE ID	FIELD HEADSPACE PID (ppm)	
1 @ 5'	236	
2 @		
3 @		
4 @		
5 @		

LAB SAMPLES		
SAMPLE ID	ANALYSIS	TIME
C05	TPH/BTEX	0940
<span style="border: 1px solid black; padding: 2px;">TPH - FAILED</span> <span style="border: 1px solid black; padding: 2px;">BTEX - PASSED</span>		

P.D. = PIT DEPRESSION; B.G. = BELOW GRADE  
T.H. = TEST HOLE; ~ = APPROX.; B = BELOW

TRAVEL NOTES: CALLOUT: 4-11-02 @ 7:30 ONSITE: 4/11/02 @ 9:25

# ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

## EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client: Blagg / BP  
Sample ID: Abd #2 C @ 5'  
Laboratory Number: 22505  
Chain of Custody No: 9820  
Sample Matrix: Soil  
Preservative: Cool  
Condition: Cool and Intact


Project #: 94034-010  
Date Reported: 04-15-02  
Date Sampled: 04-11-02  
Date Received: 04-12-02  
Date Extracted: 04-15-02  
Date Analyzed: 04-15-02  
Analysis Requested: 8015 TPH


Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	7,480	0.2
Diesel Range (C10 - C28)	3,630	0.1
Total Petroleum Hydrocarbons	11,110	0.2

ND - Parameter not detected at the stated detection limit.

References: Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Comments: **Sellers LS 2.**

  
Analyst

  
Review

# ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

## EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Abd #2 C @ 5'	Date Reported:	04-15-02
Laboratory Number:	22505	Date Sampled:	04-11-02
Chain of Custody:	9820	Date Received:	04-12-02
Sample Matrix:	Soil	Date Analyzed:	04-15-02
Preservative:	Cool	Date Extracted:	04-15-02
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	268	1.8
Toluene	600	1.7
Ethylbenzene	742	1.5
p,m-Xylene	763	2.2
o-Xylene	1,030	1.0
Total BTEX	3,400	


ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	96 %
	1,4-difluorobenzene	96 %
	Bromochlorobenzene	98 %

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Comments: Sellers LS 2.

  
Analyst

  
Review