District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Santa Fe, NM 87505

Pit or Below-Grade Tank Registration or Closure
Is pit or below-grade tank covered by a "general plan"? Yes No

Type of action: Registration of a pix of	or below-grade tank [] Closure of a pit of below-grad	ic talik ka			
Operator: BP America Production Company Telephone: (505)326-9200 e-mail address:					
Address: 200 Energy Ct, Farmington, NM 87401  Facility or well name: 5 M MONS 6C 6 API #: 30045 2222 U/L or Qtr/Qtr 14 Sec 6 T 31 N R 10 W					
	Longitude				
10 10 an					
Pit Type: Drilling Production Disposal	Volume:bbl Type of fluid:				
Workover Emergency	Construction material:				
Lined Unlined	Double-walled, with leak detection? Yes  If not	explain why old CONS			
Liner type: Synthetic Thickness mil Clay	Boasic-Wallou, With loak detection. Tes II not	DIET. DIV.			
Pit Volumebbl		<del>√∞</del> <del>∞</del>			
The volume	Less than 50 feet	(20 points) (3)			
Depth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less than 100 feet	(10 points)			
high water elevation of ground water.)	100 feet or more	( 0 points)			
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)			
water source, or less than 1000 feet from all other water sources.)	No	( 0 points)			
	Less than 200 feet	(20 points)			
Distance to surface water: (horizontal distance to all wetlands, playas,	200 feet or more, but less than 1000 feet	(10 points)			
irrigation canals, ditches, and perennial and ephemeral watercourses.)	1000 feet or more	( 0 points)			
	Ranking Score (Total Points)				
		<u> </u>			
If this is a pit closure: (1) Attach a diagram of the facility showing the pit'		- ·			
your are burying in place) onsite offsite fill If offsite, name of facility	-				
remediation start date and end date. (4) Groundwater encountered: No 🔲 Y	Yes I If yes, show depth below ground surface	ft. and attach sample results.			
(5) Attach soil sample results and a diagram of sample locations and excava	tions.				
Additional Comments:					
See Attached Documentation					
I hereby certify that the information above is true and complete to the best	of my knowledge and belief. I further certify that the	e above-described pit or below-grade tank			
has been/will be constructed or closed according to NMOCD guidelines A, a general permit , or an (attached) alternative OCD-approved plan .					
Date:					
Printed Name/Title Jeffrey C. Blagg, Agent Signature					
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or					
otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.					
Annrovalt					
Approval:  Printed Name/Title  DEC 1 9 2005  Date:					
Printed Name/Title Signature Date:					

LAB SAMPLES ANALYSIS TIME P.D. TH (6'36) (8'BG) P.D. = PIT DEPRESSION; B.G. = BELOW GRADE; B = BELOW T.H. = TEST HOLE; ~ = APPROX.; T.B. = TANK BOTTOM

0730

ONSITE:

revised: 09/04/02

TRAVEL NOTES:

CALLOUT:

0835



## EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Sep/Comp. C @ 8'	Date Reported:	11-12-02
Laboratory Number:	24249	Date Sampled:	11-08-02
Chain of Custody No:	10418	Date Received:	11-08-02
Sample Matrix:	Soil	Date Extracted:	11-11-02
Preservative:	Cool	Date Analyzed:	11-12-02
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Sammons GC G #1.

Analyst

Prestu of Welter

5796 U.S. Highway 64 • Farmington, NM 87401 • Tel 505 • 632 • 0615 • Fax 505 • 632 • 1865